

Recommended Retail Price

BFM[®] Standard Range

Connectors • Caps • Covers • Spigots

The prices indicated in this document are our Recommended Retail Prices (RRP). There may be slight price variations in local markets.

These prices are based on a NZD/EUR exchange rate of 1 NZD:0.59 EUR. Exchange rates are reviewed at the end of each month. If there is a movement greater than 5% to this rate then the price list will be updated & uploaded by working day 5 of the following month. End of month rates are obtained from <https://www.reuters.com/markets/currencies>

Contents

Spigots01

Lipped Spigot 01

Seeflex 02

Seeflex O40E02

Seeflex O40AS03

Seeflex O20E04

Seeflex O60ES05

Add-Ons 06

TR (Tool Release)06

TR (Tool Release) Tools06

‘Smiley Face’ Hole Punch06

Quick Access Port 07

Rings07

Flexi 08

Flexi / Flexi-Light08

Flexi-Earthed09

Teflex 10

Teflex Woven10

Teflex NP Black 11

Teflex NP Opaque 12

LM3 13

LM4 14

FM1 Breather15

Blanking Cap 16

Blanking Bin17

Kevlar Cover 18

Black-out Cover 19

Bulk Bag Loader 20

Spigots

Welds to your pipes to allow snap-in fitting of BFM® connectors



- Available in 304L SS and 316L SS (Hastelloy available on request)
- The spigot design is slightly tapered, so the OD at the top of the tail is 5mm / 13/64" greater than the base
- BFM® spigots are 89mm (3 1/2") in total length - made up of a head of 37mm (1 29/64") and a 'tail' that is 52mm (2") long

PHYSICAL PROPERTIES:

Material	304L SS or 316L SS
Wall Thickness	2.0mm/ 5/64"

Note:

- The 'tail' of the spigot can be cut to tailor the perfect fit for your available space (ensure caution is used when welding not to distort spigot head).
- Download the BFM® IG (Installation Gap) Calculator App to ensure correct between spigots before welding or contact your BFM® Distributor for help.



DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
304 LSS	20000	122	21287	123	20001	126	20002	137	20003	158	20004	176	20005	199	20006	224	20007	242	20008	281	20009	334	20010	366	20011	381
316 LSS	20020	193	21288	197	20021	221	20022	244	20023	269	20024	307	20025	352	20026	397	20027	478	20028	500	20029	547	20030	561	20031	568

* Ø100mm measured externally (OD), all other Ø measured internally (ID).

DIA:	Ø700mm		Ø750mm		Ø800mm		Ø850mm		Ø900mm		Ø950mm		Ø1,000mm		Ø1,050mm		Ø1,100mm		Ø1,150mm		Ø1,200mm		Ø1,250mm		Ø1,300mm	
	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
304 LSS	20012	789	20013	891	20014	978	20015	1082	20016	1120	20017	1235	20018	1260	22222	1338	21203	1528	22815	1520	21161	1573	21434	1584	20019	1604
316 LSS	20032	867	20033	943	20034	1265	20035	1391	20036	1489	20037	1500	20038	1526	22794	1629	21853	1728	22795	1741	21934	1787	25426	1881	60022	1977

DIA:	Ø1,350mm		Ø1,400mm		Ø1,450mm		Ø1,500mm		Ø1,550mm		Ø1,600mm		Ø1,650mm	
	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
304 LSS	21435	1623	21436	1642	22223	1734	21125	1833	22802	1909	21012	2215	21121	2227
316 LSS	25406	2081	25427	2168	25432	2289	22317	2417	25428	2522	25429	2627	22007	2939

Tool Release Holes: Spigots can be supplied with standard round tool-release holes pre-drilled or smiley-face tool release holes pre-punched for an additional fee of NZ\$50 per hole. **PLEASE NOTE:** These pre-drilled/punched TR spigots have different part numbers to those shown here.

Lipped Spigot

Allows easy integration with quick-connect, clamped modular tubing/piping systems

To enable a BFM® fitting system to be integrated with 'quick connect' modular tubing/piping, a range of our 304SS spigots are available with a 6mm rolled 'lip'. The lip of the spigot clamps in place with the corresponding modular lip using quick-release clamp systems like Jacob.

DIA:	Ø100mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm	
	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
304 LSS	20039	158	20041	162	20042	172	20043	193	20044	212	20045	234	20046	260

The prices shown above indicate our Recommended Retail Prices (RRP).



NOTE: a BFM® Lipped Spigot has a 6mm shorter overall height/length of 83mm.

Seeflex 040E

Strong, resilient, multi-purpose connector




- Used on all types of stationary, vibratory and gyratory sifters, screeners, feeders, bin discharges, hoppers, conveyors, any packing or product handling equipment.
- Superior wear resistance - used in CIP and washing.
- Available as a specially-marked " Wash Sleeve "version (add EU€6 to price below).
- Available as Quick Access Port option

Maximum Diameter: 1,650mm
Maximum Length (≤ Ø650mm): 6,000mm
Available with SS Rings? Yes (≤ Ø500mm)
Available with Plastic Rings? Yes
Available as TR (Tool Release) option? Yes (≤ Ø650mm)

PHYSICAL PROPERTIES:

Material	Ether-based thermoplastic polyurethane alloy
Wall Thickness (±10%)	0.9mm / 1/32 inch
Operating Temp Range	-25 to 110°C / -13 to 230°F (surge to 120°C to 248°F)
Surface Resistivity (Ohms)	10 ¹⁰



Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
80	21871	77	22554	87	21756	89	21395	103	21259	118	21969	136	21984	150	22564	184	22566	203	22166	230	22569	237	22573	287	22413	303
100	20050	81	22000	91	20061	94	20072	109	20083	124	20094	143	20105	159	20116	194	20127	214	20138	232	20149	249	20160	303	20171	319
150	20051	84	22001	93	20062	101	20073	113	20084	129	20095	149	20106	166	20117	207	20128	225	20139	233	20150	260	20161	313	20172	332
200	20052	88	22002	98	20063	107	20074	119	20085	136	20096	156	20107	175	20118	212	20129	236	20140	245	20151	274	20162	330	20173	350
250	20053	100	22168	117	20064	122	20075	145	20086	169	20097	191	20108	221	20119	260	20130	300	20141	314	20152	352	20163	412	20174	438
300	20054	107	22247	129	20065	131	20076	157	20087	183	20098	209	20109	240	20120	281	20131	322	20142	337	20153	378	20164	447	20175	474
350	20055	112	22555	138	20066	141	20077	159	20088	214	20099	215	20110	248	20121	310	20132	329	20143	360	20154	385	20165	470	20176	516
400	20056	114	22071	142	20067	140	20078	160	20089	217	20100	217	20111	255	20122	299	20133	346	20144	362	20155	405	20166	472	20177	518
450	20057	124	22556	156	20068	153	20079	184	20090	225	20101	248	20112	274	20123	333	20134	369	20145	401	20156	432	20167	515	20178	550
500	20058	131	22003	158	20069	161	20080	194	20091	252	20102	262	20113	278	20124	350	20135	388	20146	422	20157	454	20168	543	20179	579
550	20059	140	22557	162	20070	166	20081	209	20092	257	20103	273	20114	293	20125	385	20136	435	20147	466	20158	501	20169	596	20180	634
600	20060	145	21386	163	20071	168	20082	210	20093	267	20104	277	20115	302	20126	412	20137	462	20148	499	20159	539	20170	635	20181	667
650	22552	148	22558	169	21385	179	21208	229	21955	267	21742	297	22562	313	22500	415	22567	465	22170	502	22572	545	22577	638	22578	682
700	21278	149	22559	170	21231	188	21569	238	21353	278	22280	298	22563	329	21405	418	22249	466	21262	507	22571	547	22576	641	22579	685
750	22553	151	22560	179	21794	190	21560	241	21691	280	22338	301	23005	358	22252	427	22568	491	22506	512	22570	576	22575	667	22580	707
800	20570	152	21387	192	20571	191	20572	241	20573	281	20574	317	20575	358	20576	432	20577	500	20578	514	20579	595	20580	669	20581	709
850	24431	182	25562	201	21675	227	21839	267	22874	312	24964	359	24496	365	24771	457	26756	537	26657	559	40695	651	40696	700	40697	753
900	24593	189	28310	210	21943	237	21257	280	21786	324	21282	373	23088	385	21956	479	24320	560	22748	585	40726	679	22803	729	40728	784
950	22855	198	40724	219	22326	247	21607	292	22169	336	22099	388	24424	404	29732	501	21561	582	40725	612	40727	706	26267	758	26453	815
1000	20590	205	21468	228	20591	257	20592	304	20593	348	20594	401	20595	424	20596	523	20597	605	20598	638	20599	733	20600	788	20601	847

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

Seeflex 040AS

Designed to dissipate static, ideal for potentially explosive areas




- Transparent, 'anti-static' connector, designed to dissipate static
- Excellent abrasion, chemical and puncture resistance

PHYSICAL PROPERTIES:

Material	Ether-based thermoplastic polyurethane alloy with an anti-static infusion
Wall Thickness (±10%)	0.9mm / 1/32 inch
Operating Temp Range	-25 to 95°C / -13 to 203°F (surge to 100°C to 212°F)
Surface Resistivity (Ohms)	10 ⁸ (very good at dissipating static)

Maximum Diameter:	1,650mm
Maximum Length (≤ Ø650mm):	6,000mm
Available with SS Rings?	Yes (≤ Ø500mm)
Available with Plastic Rings?	Yes
Available as TR (Tool Release) option?	Yes (≤ Ø650mm)



Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
80	70082	96	70098	110	70114	117	70130	132	70146	150	70162	173	70178	192	70194	237	70210	261	70226	302	70242	310	70258	390	70274	396
100	70083	101	70099	116	70115	123	70131	138	70147	158	70163	182	70179	202	70195	249	70211	278	70227	311	70243	326	70259	394	70275	417
150	70084	101	70100	125	70116	136	70132	145	70148	169	70164	195	70180	217	70196	271	70212	301	70228	314	70244	350	70260	421	70276	447
200	70085	109	70101	126	70117	143	70133	150	70149	178	70165	205	70181	228	70197	281	70213	317	70229	331	70245	369	70261	443	70277	470
250	70086	115	70102	136	70118	148	70134	173	70150	205	70166	240	70182	244	70198	317	70214	368	70230	385	70246	434	70262	507	70278	540
300	70087	122	70103	139	70119	155	70135	182	70151	216	70167	252	70183	285	70199	333	70215	386	70231	406	70247	457	70263	533	70279	569
350	70088	127	70104	146	70120	164	70136	186	70152	260	70168	267	70184	296	70200	358	70216	399	70232	440	70248	471	70264	569	70280	608
400	70089	129	70105	169	70121	167	70137	187	70153	265	70169	278	70185	307	70201	358	70217	420	70233	440	70249	496	70265	571	70281	611
450	70090	143	70106	184	70122	186	70138	219	70154	298	70170	303	70186	338	70202	396	70218	443	70234	486	70250	525	70266	623	70282	667
500	70091	151	70107	196	70123	194	70139	231	70155	313	70171	318	70187	349	70203	417	70219	467	70235	511	70251	552	70267	656	70283	702
550	70092	164	70108	200	70124	201	70140	273	70156	329	70172	340	70188	403	70204	466	70220	525	70236	575	70252	622	70268	734	70284	784
600	70093	176	70109	202	70125	203	70141	275	70157	330	70173	344	70189	439	70205	498	70221	566	70237	631	70253	676	70269	782	70285	811
650	70094	177	70110	207	70126	221	70142	279	70158	331	70174	372	70190	446	70206	517	70222	572	70238	635	70254	680	70270	790	70286	839
700	70095	181	70111	211	70127	235	70143	286	70159	338	70175	387	70191	450	70207	523	70223	584	70239	668	70255	694	70271	807	70287	866
750	70096	183	70112	218	70128	241	70144	288	70160	342	70176	400	70192	454	70208	528	70224	596	70240	689	70256	709	70272	815	70288	875
800	70097	183	70113	230	70129	239	70145	290	70161	343	70177	403	70193	455	70209	530	70225	615	70241	707	70257	732	70273	818	70290	877
850	71021	216	70944	258	70389	272	70352	341	70933	397	71161	462	71162	514	71164	583	71165	685	71167	760	71169	827	71171	920	71173	988
900	70805	225	71149	266	70392	283	70488	355	70291	414	71086	482	70587	537	71183	608	71186	711	71189	789	71192	858	71195	953	71198	1024
950	71177	233	71178	275	70505	293	70487	369	71179	432	71155	502	71180	560	71184	634	71187	737	71190	818	71193	890	71196	987	71199	1061
1000	70795	241	70752	284	70533	304	70379	384	70303	449	70423	522	71182	582	71185	659	71188	763	71191	846	71194	921	71197	1021	71200	1097

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

Seeflex 020E

Lightweight & flexible, ideal for weighscale applications




- Transparent, light weight Seeflex media, specifically designed for load and weigh scale type equipment
- Also very good in applications with vertical movement as it is particularly flexible

PHYSICAL PROPERTIES:

Material	Ether-based thermoplastic polyurethane alloy
Wall Thickness (±10%)	0.35mm / 1/64 inch
Operating Temp Range	-25 to 80°C / -13 to 176°F (surge to 100°C to 212°F)
Surface Resistivity (Ohms)	10 ¹⁰

Maximum Diameter:	1,650mm
Maximum Length (≤ Ø650mm):	6,000mm
Available with SS Rings?	On request only
Available with Plastic Rings?	On request only
Available as TR (Tool Release) option?	Yes (≤ Ø650mm)



Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
80	22155	77	22598	87	22610	89	22615	103	22360	118	21680	136	22622	150	22244	184	22646	203	22156	230	22672	237	22243	287	22699	303
100	20789	81	23000	91	20790	94	20791	109	20792	124	20793	143	21360	159	21361	194	21362	214	21363	232	21364	249	21365	303	21366	319
150	20690	84	23001	93	21222	101	21432	113	21317	129	21787	149	22623	166	22548	207	22647	225	22659	233	22673	260	22686	313	22700	332
200	21849	88	23002	98	21438	107	20692	119	20693	136	20694	156	21207	175	20695	212	20696	236	20697	245	20698	274	20699	330	20703	350
250	22425	100	22599	117	21781	122	21997	145	21613	169	21398	191	22624	221	22635	260	22648	300	22660	314	22674	352	22687	412	22701	438
300	21922	107	22342	129	21195	131	21837	157	21194	183	21384	209	22349	240	22636	281	22649	322	22661	337	22675	378	22688	447	22702	474
350	22590	112	22600	138	21882	141	21838	159	21774	214	21408	215	22625	248	22637	310	22650	329	22662	360	22676	385	22689	470	22703	516
400	22491	114	22601	142	21415	140	21308	160	21307	217	21784	217	22626	255	21806	299	22651	346	22063	362	22677	405	22690	472	22704	518
450	22591	124	22602	156	22492	153	22616	184	22316	225	22620	248	22627	274	22638	333	22652	369	22663	401	22678	432	22691	515	22705	550
500	23004	131	22603	158	22216	161	21303	194	21726	252	21915	262	22628	278	22639	350	22653	388	22664	422	22679	454	22692	543	22706	579
550	22592	140	22604	162	22611	166	21321	209	22445	257	21827	273	22629	293	22640	385	21913	435	22665	466	22680	501	22693	596	22707	634
600	22593	145	22605	163	21941	168	22040	210	22499	267	22621	277	22630	302	22641	412	22654	462	22666	499	22681	539	22694	635	22708	667
650	22594	148	22606	169	21369	179	22336	229	22618	267	21591	297	22631	313	22642	415	22655	465	22667	502	22682	545	22695	638	22709	682
700	22595	149	22607	170	22612	188	22104	238	22619	278	21636	298	22632	329	22643	418	22656	466	22668	507	22683	547	22696	641	22710	685
750	22596	151	22608	179	22613	190	22617	241	22150	280	21624	301	22633	358	22644	427	22657	491	22669	512	22684	576	22697	667	22711	707
800	22597	152	22609	192	22614	191	21714	241	22142	281	21189	317	22634	358	22645	432	22658	500	22670	514	22685	595	22698	669	22712	709
850	29178	182	41568	201	29459	227	24342	267	22315	312	23059	359	24837	365	24839	457	41573	537	26658	559	41581	651	41585	700	41588	753
900	41566	189	41569	210	22077	237	23154	280	23167	324	23168	373	24838	385	24840	479	41574	560	41578	585	41582	679	41586	729	41589	784
950	41567	198	41570	219	24767	247	22034	292	21699	336	40701	388	41571	404	24841	501	41575	582	41579	612	41583	706	41587	758	41590	815
1000	27031	205	26569	228	40148	257	21448	304	21631	348	21592	401	41572	424	41577	523	41576	605	41580	638	41584	733	22058	788	41591	847

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

Seeflex 060ES

Superior strength for over-pressure situations




- Pressure-resistant Seeflex 060ES is a semi-transparent connector with an internal polyester scrim
- The internally bonded scrim restricts the Seeflex sleeve from stretching
- For over-pressure situations for continuous pressure up to 1.7 bar

PHYSICAL PROPERTIES:

Material	Seeflex - Ether-based thermoplastic polyurethane alloy with internally bonded polyester scrim
Wall Thickness (±10%)	1.3mm / 1/16 inch
Operating Temp Range:	-25 - 120°C / -13 - 248°F (surge to 140°C / 284°F)

Maximum Diameter:	1,650mm
Maximum Length:	1,000mm
Available with SS Rings?	No
Available with Plastic Rings?	No
Available as TR (Tool Release) option?	Yes (≤ Ø650mm)



* Longer lengths only

Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
80	30763	146	30764	160	30856	175	30869	196	30929	223	30779	254	30780	278	30912	313	30930	341	31109	351	31121	379	31136	434	31151	460
100	30782	146	30806	160	30776	175	30760	196	30748	223	30731	254	30739	278	30836	313	30767	341	30827	351	30837	379	30925	434	31029	460
150	30773	154	30753	169	30746	185	30761	209	30762	237	30769	271	30727	297	30730	334	30790	363	30891	376	30832	405	31137	462	30890	490
200	30788	162	30908	178	30726	195	30729	221	30740	252	30771	287	30766	315	30770	354	30768	385	30732	400	30797	432	30794	490	30755	520
250	30887	170	31045	187	30777	205	30778	233	30818	266	30723	303	30867	333	30781	375	30951	408	30972	424	31122	458	30858	519	31152	551
300	30789	178	30988	196	30803	215	30831	245	30785	280	30819	319	30826	352	30888	395	31096	430	30855	449	30962	484	31138	548	31153	582
350	30933	186	31046	205	31057	225	30843	257	30821	294	30889	335	30913	371	30986	415	31097	453	30859	473	31123	511	30866	576	31154	612
400	30934	194	31047	214	31058	235	30845	269	31065	309	30744	351	30765	389	31086	435	31098	475	31110	498	31124	537	31139	604	31155	643
450	30935	202	30970	224	30917	245	30943	281	30820	323	31073	367	30846	407	30939	455	31099	497	30896	522	31125	563	31140	633	31156	673
500	31038	210	31048	232	31012	255	30942	293	30754	337	30931	384	31079	425	31087	476	31100	520	31111	547	31126	590	31141	661	31157	703
550	30857	218	31049	242	30906	266	31060	306	30863	351	30798	399	30904	444	30745	496	31101	542	31112	571	31127	616	31142	690	31158	734
600	30851	226	30910	251	30997	276	30811	317	30828	365	30796	415	30886	463	31088	516	30737	565	31113	595	31128	643	31143	719	31159	765
650	31039	234	31050	260	30918	286	30909	329	31066	379	31074	432	30847	481	31089	537	31102	587	31114	620	31129	669	31144	747	31160	795
700	31040	242	31051	269	30919	296	31061	342	31067	394	31075	448	31080	499	31090	557	31103	609	31115	644	31130	695	31145	775	31161	825
750	31041	250	31052	278	31059	306	31062	353	31068	408	31076	464	31081	517	31091	578	31104	632	31116	669	31131	722	31146	804	31162	856
800	31042	258	31053	287	30860	316	30873	366	31069	422	30932	480	31082	536	31092	598	31105	654	31117	693	31132	748	31147	832	31163	887
850	30861	266	31054	297	30959	326	31063	378	31070	437	31077	496	31083	554	31093	618	31106	677	31118	718	31133	774	31148	861	31164	917
900	31043	274	31055	306	30981	336	30998	390	31071	451	30905	512	31084	573	31094	638	31107	699	31119	742	31134	801	31149	889	31165	948
950	31044	281	31056	314	30944	346	31064	402	31072	465	31078	529	31085	591	31095	658	31108	722	31120	766	31135	827	31150	918	31166	978
1000	31030	290	31032	324	30772	356	30795	414	30877	479	30949	545	31033	609	31034	679	31035	744	31036	791	31037	854	31028	946	31027	1008

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

TR (Tool Release)

As an added safety option, all BFM® fitting connectors are available in a TR (Tool Release) version which have a firmer snap-band that is virtually impossible to remove by hand. To calculate the price of a TR version of a connector, **simply add the following to the RRP of the standard connector price (based on the Diameter):**

Maximum possible diameter for TR is Ø650mm

DIA:	Ø100mm	Ø125mm	Ø150mm	Ø200mm	Ø250mm	Ø300mm	Ø350mm	Ø400mm	Ø450mm	Ø500mm	Ø550mm	Ø600mm	Ø650mm
	RRPEU€:	RRPEU€:	RRPEU€:	RRPEU€:	RRPEU€:	RRPEU€:	RRPEU€:	RRPEU€:	RRPEU€:	RRPEU€:	RRPEU€:	RRPEU€:	RRPEU€:
Surcharge on standard Connector	14	14	17	19	21	24	26	30	57	58	62	65	68

TR (Tool Release) Tools

To remove the TR Connectors, a special BFM® 'TR Tool' is required. Our standard TR Tool option features a rounded end tool and only requires the spigot to have a 6mm hole drilled in the outer most ridge. The 'Smiley Face' tool has an additional level of safety as it is used with a specially shaped hole (see adjacent information).

	Part No:	RRPEU€:
Standard Tool Release Tool	304990	47
Smiley Face Tool Release Tool	304991	47



'Smiley Face' Hole Punch

For additional security, and to avoid staff improvising tools to remove connectors, our 'Smiley Face' Tool Release option is a popular choice. There is a special pneumatic 'punch tool' (shown right) that makes the custom-shaped holes. Spigots can be supplied with the holes pre-punched for a small additional charge. Contact your local distributor for more information.

	Part No:	RRPEU€:
Smiley Face Hole Punch	10402	P.O.A.



The prices shown above indicate our Recommended Retail Prices (RRP).

Quick Access Port

The Quick Access Port is a removable screw in plug that can be added to the wall of Seeflex O40E and Seeflex O60ES connectors to aid in-line testing/sampling (includes tapered versions).

For minimum 150mm diameter and 150mm length connectors.



	RRP EU€:
Surcharge on standard Connector RRP price	234

Rings

Applicable to: Seeflex O40E (including Wash Sleeves and Blanking Socks/Bins). Seeflex O40AS, LM3, LM4, Teflex and Teflex NP.

Anti-collapse rings can be added to help keep the connector walls open. This is particularly useful if operating under vacuum or for longer connectors where there may be the potential for the connector walls to be 'sucked' inwards. Rings are available in stainless steel (to Ø500mm) or plastic (to Ø1,650mm & max operating temperature of 110°C/230°F) and can be added to connectors at least 150mm (5") long if made from the materials listed above (subject maximum applicable diameters).

To calculate the price of a ringed version of a connector, simply add the following price per ring to the RRP of the standard connector price (based on the Diameter):

DIA(mm):	Ø100	Ø125	Ø150	Ø200	Ø250	Ø300	Ø350	Ø400	Ø450	Ø500	Ø550	Ø600	Ø650	Ø700	Ø750	Ø800	Ø850	Ø900	Ø950	Ø1000
	RRP EU€:	RRP EU€:	RRP EU€:	RRP EU€:	RRP EU€:	RRP EU€:	RRP EU€:	RRP EU€:	RRP EU€:	RRP EU€:	RRP EU€:	RRP EU€:	RRP EU€:	RRP EU€:	RRP EU€:	RRP EU€:	RRP EU€:	RRP EU€:	RRP EU€:	RRP EU€:
Stainless Steel Rings	49	52	58	68	71	75	84	91	97	104	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Plastic Rings	65	71	78	84	91	97	104	107	110	110	110	110	117	156	169	182	201	214	227	247

- The distance between spigot & rings is 75mm (3") for 150mm long connectors, and 100mm (4") for all others.
- Multiple rings need to be evenly spaced at a minimum of 100mm (4") apart for connectors up to 800mm long inclusive (maximum 4 rings) and 200mm (8") apart for connectors 850mm long and over (maximum 10 rings). Refer to our 'Quick Ref Limitations Summary' document for more information.
- The diameter of the steel ring itself is 6mm (15/64), the plastic ring itself is 8mm (5/16") and the 'connector' that joins the plastic ring together is approx. 10mm (25/64").



The prices shown above indicate our Recommended Retail Prices (RRP).

Flexi / Flexi-Light

Lightweight connector with support coil - ideal for bag feeders & filling heads




- A lightweight Seeflex connector with an encased 316 stainless steel wire coil to support flex and compression
- Used for bag feeders, filling heads or bulk bag fillers.
- Flexi-Light features a slightly lighter material and wire coil

PHYSICAL PROPERTIES:

Material	Ether-based thermoplastic polyurethane with a 316 stainless steel wire coil	
Wall Thickness (±10%):	FLEXi	0.60mm / 1/32" (Ø100 - 200mm / 4 - 8") 0.70mm / 1/32" (Ø250 - 300mm/10 - 12")
	FLEXI-LIGHT	0.4mm / 1/64"
Wire Coil Diameter	FLEXI	2.6mm / 1/8"
	FLEXI-LIGHT	1.6mm / 1/16"
Operating Temp Range:	- 20 to 85°C / - 4 to 185°F	

Available Diameters:	100mm, 150mm, 200mm, 250mm, 300mm
Minimum Length:	200mm
Maximum Length:	6,000mm
Available as TR (Tool Release) option?	Yes



* Subject to length & movement restrictions.

FLEXI:

DIA:	Ø100mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm	
LENGTH: (mm)	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
200	25701	451	26152	466	22116	501	25910	617	21197	646
250	26905	460	26139	481	22190	524	26000	644	22938	679
300	26009	471	25871	492	21623	540	26825	667	21732	709
350	26233	479	25898	506	22136	562	26419	694	23104	737
400	25877	487	25615	519	23100	582	25789	719	21765	768
450	26156	497	25798	537	23101	601	25836	746	23099	799
500	26027	506	25899	545	23102	621	26415	770	60023	831
550	28884	517	25950	558	23103	641	25790	787	40277	863
600	25761	526	26640	572	23087	661	25791	805	22757	895
650	29278	536	28090	585	23111	683	28503	834	25207	926
700	26246	546	26252	599	24293	700	26430	863	25507	955
750	28883	553	26033	612	24645	721	26371	893	23105	985
800	25592	564	26358	625	22392	741	25720	922	22793	1019
850	29028	575	25593	638	24660	763	26904	945	22804	1051
900	26525	579	25999	654	24818	783	25650	966	22137	1082
950	26067	589	29970	669	26681	802	25668	991	25671	1113
1000	25927	598	25928	685	24334	821	26581	1024	26866	1144

FLEXI - LIGHT:

DIA:	Ø100mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm	
LENGTH: (mm)	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
200	28372	431	28279	449	28278	463	28869	559	29260	585
250	29479	440	28201	462	28200	481	29241	582	29736	614
300	40300	450	28262	475	28264	500	28261	605	28742	641
350	40301	462	29077	488	29194	518	29067	628	28744	668
400	29565	473	28934	501	28199	536	28877	650	28743	696
450	40302	484	28280	514	29259	554	28768	673	28500	724
500	28914	495	29157	527	29274	572	29193	696	29504	751
550	40303	502	40312	540	29569	591	40321	719	28918	779
600	28856	510	40313	553	29566	609	28494	741	29322	806
650	40304	517	40314	566	29328	627	40322	764	40258	834
700	40305	525	28281	579	40319	645	28941	786	40257	861
750	40306	533	40315	592	29060	663	40323	809	40267	889
800	40307	540	28552	605	29641	681	40324	832	40329	916
850	40308	549	40316	618	40320	700	40325	855	29607	945
900	40309	556	29547	631	40150	718	28481	877	40330	972
950	40310	564	40317	644	29966	737	40326	900	40331	999
1000	40311	572	40318	657	29593	755	40327	923	40332	1027

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector, please refer to the 'Add-ons' pages.

Flexi-Earthed

Flexi-connector with support coil & earthing terminal lugs



- A standard Flexi connector with built-in terminal earthing lugs attached to the ends of the wire coil.
- Terminal lugs are designed to be attached to earthing cables to provide maximum electrostatic safety.

PHYSICAL PROPERTIES:

Material	Ether-based thermoplastic polyurethane with a 316 stainless steel wire coil & Ø5mm SS earthing lugs
Wall Thickness (±10%):	0.60mm / 1/32" (Ø100 – 200mm / 4 – 8") 0.70mm / 1/32" (Ø250 – 300mm/10 – 12")
Wire Coil Diameter	2.6mm / 1/64"
Operating Temp Range:	- 20 to 85°C / - 4 to 185°F

Available Diameters:

100mm, 150mm, 200mm, 250mm, 300mm


Minimum Length:

250mm

Maximum Length:

6,000mm

Available as TR (Tool Release) option? Yes



* Subject to length and movement restrictions

FLEXI - EARTHED:

DIA:	Ø100mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm	
LENGTH: (mm)	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
250	29256	506	28795	527	28360	569	28845	690	28432	724
300	28825	516	28826	537	28314	586	28412	712	28872	755
350	40363	525	40265	552	28741	607	28448	739	28875	782
400	29083	532	28472	564	28864	628	29017	765	28519	814
450	40766	542	29023	582	28345	647	28701	792	28471	844
500	29497	552	28849	590	28529	667	28491	815	28660	876
550	40298	563	29917	603	29665	687	29942	832	28963	909
600	40360	572	29551	617	28833	707	28359	850	29321	940
650	29627	582	40770	631	29196	729	40774	880	40778	971
700	40767	591	29197	645	28848	746	28897	909	40779	1001
750	40299	599	40771	658	28766	766	40755	939	40780	1031
800	29967	609	29292	671	28185	786	29057	968	40781	1064
850	40768	620	40772	683	28501	809	40775	991	40782	1096
900	29074	625	29075	699	28957	828	40776	1011	29390	1127
950	40769	634	29577	714	40400	848	40777	1037	40783	1159
1000	29289	643	40773	730	28765	867	28730	1070	28775	1189



Flexi-Earthed Terminal Lugs:



The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector, please refer to the 'Add-ons' pages.

BFM® GLOBAL LTD. | To order BFM® fitting products, please contact your local Distributor - you can find them at BFMfitting.com

Teflex Woven

100% woven Polyester - suitable for higher temperatures




- Capable of running at high temperatures – continuously operating at 260°C / 500°F with short term surges at 280°C / 536°F.
- Can be used on products across the full pH scale, i.e. either caustic or acid products will not effect Teflex Woven.

PHYSICAL PROPERTIES:

Material	Woven PTFE	
Weight (±10%)	678g/m ² / 20oz/yd ²	
Operating Temp Range	-40 - 260°C / -40 - 500°F (surge to 280°C / 536°F)	
Air Permeability	(cm ³ /cm ² /sec@125Pa)	(ft ³ /ft ² /min@0.5" wg)
	0.3	0.5

Maximum Diameter: 1,650mm
Maximum Length (≤ Ø650mm): 1,500mm
Available with SS Rings? Yes (≤ Ø500mm)
Available with Plastic Rings?* Yes
Available as TR (Tool Release) option?* Yes (≤ Ø650mm)

*to Max. Operating Temp of 110°C / 230°F



Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
80	30465	261	40909	281	26659	373	30443	526	25395	597	30308	670	25284	694	30488	719	31280	784	26304	868	31281	958	31282	1325	31283	1435
100	30079	261	30080	281	30081	373	21507	526	30065	597	21534	670	21470	694	30082	719	30083	784	30084	868	30085	958	21535	1325	30086	1435
150	30001	290	30056	351	21537	413	21939	529	30063	623	21928	725	21505	768	21637	895	21926	1008	30311	1123	30312	1215	21927	1428	30310	1629
200	30096	312	30638	372	30061	432	21439	533	30057	629	20558	752	21506	823	20557	959	20556	1008	30058	1123	30059	1215	21577	1428	30060	1629
250	30186	391	40235	448	21986	508	21341	636	21473	767	21475	902	21471	1017	21472	1154	21492	1286	21474	1424	24847	1563	26300	1680	27083	1816
300	30107	431	30804	497	30103	563	21343	706	30210	851	21339	1001	21957	1130	22898	1283	21166	1429	30101	1582	26051	1736	26052	1867	30160	2019
350	28881	471	40910	545	30209	618	21527	776	30211	934	30212	1099	21528	1244	24748	1411	24991	1572	21686	1741	41082	1909	40393	2055	30155	2223
400	40895	511	40911	594	30176	673	22357	845	21558	1018	30280	1198	25171	1357	24749	1540	21627	1715	30223	1899	30224	2083	41103	2243	22011	2426
450	30325	550	40912	642	26204	727	22483	916	24711	1101	30259	1296	29047	1471	21337	1669	21600	1858	29923	2057	41083	2256	28034	2430	28032	2630
500	30605	590	40913	690	30392	782	30273	985	23150	1185	30366	1395	40976	1584	24297	1798	41013	2001	30196	2215	41084	2430	28035	2618	41119	2833

All BFM fitting connectors comply with 3-A 60-64 Sanitary Fittings

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

Teflex NP Black

PTFE laminate for temperature & chemical extremes



- Non-permeable PTFE laminate that can be used on products across the full pH scale, ie. caustic or acid products will not effect Teflex NP Black
- Capable of running at high and low temperatures
- Designed to dissipate electrical charge - 10⁶Ω

PHYSICAL PROPERTIES:

Material	Pure PTFE
Weight (±10%)	459g/m ² / 13.5oz/yd ²
Operating Temp Range	-73 - 300°C / -99 - 572°F (surge to 316°C / 600°F)
Surface Resistivity (Ohms)	10 ⁶

Maximum Diameter:	500mm
Maximum Length:	1,000mm
Available with SS Rings?	Yes
Available with Plastic Rings?	No
Available as TR (Tool Release) option?	Yes

<input checked="" type="checkbox"/> VIBRATION	<input checked="" type="checkbox"/> OSCILLATION	<input checked="" type="checkbox"/> COMPRESSION	<input checked="" type="checkbox"/> DUST TIGHT	<input checked="" type="checkbox"/> FOOD SAFETY	<input checked="" type="checkbox"/> ATEX
---	---	---	--	---	--

* Expect shorter life-span if used # All BFM® fitting connectors comply with 3-A 60-64 Sanitary Fittings

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm	
LENGTH: (mm)	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
80	41175	235	41176	253	29938	316	29859	420	29858	498	29631	563	41296	625	29820	647	41297	705	41313	781
100	40873	235	41060	253	29093	316	29041	420	29043	498	29042	563	29787	625	29531	647	29532	705	29816	781
150	41042	261	41061	316	29106	346	29124	433	29133	513	29087	579	29788	691	29506	805	41298	907	29844	1011
200	41043	280	41062	335	29108	362	28819	442	29135	524	28718	609	29552	740	29501	863	29510	907	40152	1011
250	41044	352	41063	404	29127	423	29071	595	29137	702	29147	794	29927	915	29489	1038	29760	1157	41314	1281
300	41045	388	41064	447	29129	470	29078	627	29144	739	29080	871	29763	1017	29845	1155	41299	1286	41295	1424
350	41046	424	41065	491	41179	556	29629	698	41253	841	29800	989	29910	1119	41282	1270	41300	1415	29924	1566
400	41047	460	41066	535	29601	605	29757	761	29936	916	40657	1078	40764	1221	41283	1386	41301	1543	29925	1709
450	41048	496	41067	578	29602	654	29535	824	40188	991	40658	1167	40765	1323	29511	1502	40337	1672	29926	1851
500	41049	531	41068	621	40174	704	29852	887	29630	1066	29930	1256	41271	1426	29513	1618	41302	1801	41315	1994
550	41050	567	41069	665	41180	753	41247	950	29937	1141	41261	1344	41272	1528	41284	1733	41303	1930	41316	2136
600	41051	603	41070	709	41181	802	40269	1012	40232	1216	41262	1433	41273	1630	41285	1850	41304	2059	41317	2279
650	41052	638	41071	752	41241	852	41248	1076	41254	1292	41263	1522	41274	1732	41286	1965	41305	2187	41318	2422
700	41053	674	41072	795	41242	901	41249	1139	41255	1366	41264	1610	41276	1835	41287	2081	41306	2316	41319	2564
750	41054	710	41073	839	41243	950	41250	1201	41256	1441	41265	1699	41277	1937	41288	2197	41307	2445	41320	2707
800	41055	746	41074	883	40355	999	40872	1264	41257	1517	41266	1788	41278	2039	41289	2313	41308	2574	41321	2849
850	41056	782	41075	926	41244	1049	41251	1327	41258	1592	41267	1876	41279	2141	41290	2428	41309	2702	41322	2992
900	41057	818	41076	970	41245	1098	40663	1390	41259	1667	41268	1965	41280	2244	41291	2545	41310	2831	41323	3134
950	41058	853	41077	1013	41246	1148	41252	1453	41260	1742	41269	2054	41281	2346	41292	2660	41311	2959	41324	3277
1000	41059	889	41078	1057	29972	1197	40346	1516	40133	1817	40343	2143	41293	2448	41294	2776	41312	3089	41325	3419



The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

Teflex NP Opaque

Semi-transparent PTFE laminate for temperature & chemical extremes




- Non-permeable PTFE laminate that can be used on products across the full pH scale, ie. caustic or acid products will not effect Teflex NP Opaque
- Capable of running at high and low temperatures
- Semi-transparent to allow product-flow visibility

Maximum Diameter: 500mm
Maximum Length: 1,000mm
Available with SS Rings? Yes
Available with Plastic Rings? No
Available as TR (Tool Release) option? Yes

PHYSICAL PROPERTIES:

Material	Pure PTFE
Weight (±10%)	459g/m ² / 13.5oz/yd ²
Operating Temp Range	-73 - 300°C / -99 - 572°F (surge to 316°C / 600°F)
Surface Resistivity (Ohms)	Insulative



* Expect shorter life-span if used # All BFM[®] fitting connectors comply with 3-A 60-64 Sanitary Fittings

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm	
LENGTH: (mm)	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
80	41177	235	41178	253	29900	316	40250	420	41356	498	40247	563	40252	625	41396	647	41412	705	40749	781
100	41137	235	41156	253	40649	316	29934	420	29687	498	40256	563	40248	625	40630	647	41413	705	40251	781
150	41138	261	41157	316	29861	346	29933	433	29943	513	40246	579	41381	691	40661	805	41414	907	41430	1011
200	41139	280	41158	335	40249	362	29905	442	40270	524	29751	609	40245	740	40852	863	29963	907	41431	1011
250	41140	352	41159	404	40639	423	29866	595	41357	702	29850	794	41009	915	41397	1038	29907	1157	40638	1281
300	41141	388	41160	447	29929	470	29847	627	29848	739	29849	871	29906	1017	29846	1155	41415	1286	41432	1424
350	41142	424	41161	491	41328	556	41343	698	41007	841	41008	989	41382	1119	41398	1270	41416	1415	41433	1566
400	41143	460	41162	535	29904	605	40746	761	41358	916	40832	1078	41383	1221	41399	1386	41417	1543	41434	1709
450	41144	496	41163	578	41329	654	41344	824	41359	991	41370	1167	41384	1323	41400	1502	41418	1672	41435	1851
500	41145	531	41164	621	41330	704	40874	887	41360	1066	41371	1256	41385	1426	41401	1618	41419	1801	41436	1994
550	41146	567	41165	665	41331	753	41345	950	41361	1141	41372	1344	41386	1528	41402	1733	41420	1930	41437	2136
600	41147	603	41166	709	41332	802	41346	1012	41362	1216	40888	1433	41387	1630	41403	1850	41421	2059	41438	2279
650	41148	638	41167	752	41333	852	41347	1076	41363	1292	41373	1522	41388	1732	41404	1965	41422	2187	41439	2422
700	41149	674	41168	795	41334	901	41348	1139	41364	1366	41374	1610	41389	1835	41405	2081	41423	2316	41440	2564
750	41150	710	41169	839	41335	950	41349	1201	41365	1441	41375	1699	41390	1937	41406	2197	41424	2445	41441	2707
800	41151	746	41170	883	41336	999	40875	1264	41366	1517	41376	1788	41391	2039	41407	2313	41425	2574	41442	2849
850	41152	782	41171	926	41337	1049	41352	1327	41367	1592	41377	1876	41392	2141	41408	2428	41426	2702	41443	2992
900	41153	818	41172	970	41338	1098	41353	1390	41368	1667	41378	1965	41393	2244	41409	2545	41427	2831	41444	3134
950	41154	853	41173	1013	41339	1148	41354	1453	41369	1742	41379	2054	41394	2346	41410	2660	41428	2959	41445	3277
1000	41155	889	41174	1057	41342	1197	41355	1516	40351	1817	41380	2143	41395	2448	41411	2776	41429	3089	41446	3419

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

LM3

100% Woven polypropylene - breathable & suitable for low temperatures




- Ideal for low temperature environments (down to -70°C/-94°F)
- Perfect for food processing, especially when some breathability is required to alleviate pressure.

PHYSICAL PROPERTIES:

Material	100% woven polypropylene	
Weight (±10%)	295g/m ² / 8.7oz/yd ²	
Operating Temp. Range	-70 to 94°C / -94 to 201°F (surge to 107°C / 225°F)	
Air Permeability	(cm ³ /cm ² /sec@125Pa)	(ft ³ /ft ² /min@0.5" wg)
	13	25

Maximum Diameter: 1,650mm
Maximum Length (≤ Ø650mm): 1,500mm
Available with SS Rings? Yes (≤ Ø500mm)
Available with Plastic Rings? Yes
Available as TR (Tool Release) option? Yes (≤ Ø650mm)



All BFM® fitting connectors comply with 3-A 60-64 Sanitary Fittings
Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
80	50671	70	51087	73	50768	77	50670	86	50709	94	50623	99	51206	113	51227	121	51248	135	51274	155	51298	167	51327	176	51355	186
100	50602	70	50522	73	50539	77	50520	86	50540	94	50541	99	50542	113	50543	121	50544	135	50603	155	50647	167	51328	176	50707	186
150	50628	72	50672	74	50521	77	50546	87	50665	95	50622	104	51207	114	50669	123	51619	135	50604	158	51299	168	50777	179	51356	189
200	50701	82	51088	84	25277	89	50519	89	50532	97	50552	110	50715	117	50553	130	50783	140	50605	162	51300	173	51329	183	51357	195
250	50710	85	51089	89	50594	93	50626	106	50627	119	50625	128	50789	142	50711	163	51249	182	50780	201	51301	244	51330	255	51358	267
300	30751	89	50751	92	26870	97	26871	110	25275	124	50644	134	50645	148	51476	171	51250	189	50613	209	51302	251	51331	264	51359	276
350	51066	92	51090	96	51139	101	50641	115	25276	129	50723	140	50747	154	51753	177	51251	196	51275	217	51303	258	51332	271	51360	284
400	51067	96	50750	100	50722	106	50759	120	50754	134	25296	146	50767	160	51228	184	51252	203	26701	225	51304	266	51333	280	51361	293
450	50525	99	50752	104	50535	110	50736	124	50746	139	26837	152	51057	167	26838	191	51253	210	51276	232	51305	273	50656	287	51362	301
500	50526	102	51091	108	50634	114	50635	129	26921	145	26923	158	51208	173	51754	198	51254	217	51277	240	51306	280	51334	295	51363	310
550	51068	106	51092	112	51140	119	51154	133	51171	149	51188	163	51209	179	51229	204	51255	224	51278	248	51307	287	51335	303	51364	319
600	51138	109	51093	116	50776	123	50774	138	50708	155	50652	169	50787	186	51230	211	51256	231	51279	256	51308	294	51336	311	51365	327
650	51069	113	51094	120	51141	127	51155	143	51172	160	51189	175	51210	192	51231	218	51257	238	51280	264	51309	301	51337	319	51366	336
700	51070	116	51095	124	51142	132	50779	148	51173	165	51190	181	51211	199	51232	225	51258	245	51281	271	51310	309	51338	327	51367	345
750	51071	119	51096	128	51143	136	51156	152	51174	170	51191	187	51212	205	50705	231	50706	252	51282	279	51311	316	51339	335	51368	353
800	51072	123	51097	132	51755	140	50775	156	50712	175	51192	193	51213	211	51233	238	51259	259	51283	287	51312	324	51340	343	51369	362
850	51073	126	51098	136	51144	145	51157	161	51175	180	51193	199	51214	218	51234	245	51260	266	51284	295	51313	331	51341	350	51370	371
900	51074	130	51099	140	51145	149	51158	166	51176	185	51194	205	51752	224	51235	251	51261	273	51285	303	51314	338	51342	358	51371	379
950	51075	133	51100	143	51146	153	51159	171	51177	191	51195	211	51215	231	51236	258	51262	280	51286	310	51315	346	51343	366	51372	388
1000	51076	136	51101	148	51487	158	51160	175	26922	195	50655	217	51216	237	51237	265	51263	287	51287	319	51316	598	51344	598	51373	598

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

LM4

100% woven Polyester - suitable for higher temperatures



- Used for higher temperature environments (up to 130°C / 266°F).
- Ideal for use where air needs to be vented through the walls of the flexible connector.

PHYSICAL PROPERTIES:

Material	100% woven polyester fibre	
Weight (±10%)	393g/m ² / 11.6oz/yd ²	
Operating Temp Range	-40 - 130°C / -40 - 266°F (surge to 150°C / 302°F)	
Air Permeability	(cm ³ /cm ² /sec@125Pa)	(ft ³ /ft ² /min@0.5" wg)
	0.4	0.8

Maximum Diameter:	1,650mm
Maximum Length (≤ Ø650mm):	1,500mm
Available with SS Rings?	Yes (≤ Ø500mm)
Available with Plastic Rings?*	Yes
Available as TR (Tool Release) option?	Yes (≤ Ø650mm)

*to Max. Operating Temp of 110°C / 230°F

VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	3-A 60-64	FOOD SAFETY		ATEX

All BFM fitting connectors comply with 3-A 60-64 Sanitary Fittings

Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
80	26101	70	41664	73	50506	77	26344	86	50507	94	26239	99	29840	113	26262	121	21453	135	26305	155	41665	167	41666	176	41667	186
100	20900	70	51000	73	20901	77	20902	86	20903	94	20904	99	20905	113	20906	121	20907	135	20908	155	20909	167	20910	176	20911	186
150	20509	72	51001	74	19569	77	50009	87	50014	95	50015	104	50406	114	22089	123	50424	135	50425	158	50426	168	50427	179	50428	189
200	20912	82	51002	84	21847	89	19399	89	20510	97	20511	110	20512	117	20483	130	20513	140	20514	162	20515	173	20516	183	20517	195
250	25238	85	50140	89	21987	93	21477	106	21614	119	21812	128	22897	142	21622	163	22927	182	26531	201	40791	244	24391	255	28822	267
300	20914	89	50137	92	20915	97	20916	110	21924	124	20918	134	20919	148	20920	171	20921	189	20922	209	20923	251	20924	264	20925	276
350	25595	92	23146	96	21883	101	22367	115	50004	129	22852	140	20314	154	26532	177	50523	196	26533	217	29965	258	41226	271	41233	284
400	20926	96	28689	100	20927	106	20928	120	20929	134	20650	146	20931	160	20932	184	20933	203	20934	225	20935	266	20936	280	20937	293
450	26254	99	29187	104	22366	110	22800	124	50404	139	50405	152	50407	167	50499	191	29589	210	28349	232	50501	273	26567	287	24486	301
500	22758	102	23206	108	20939	114	22208	129	20941	145	20942	158	20943	173	24296	198	20945	217	25410	240	20947	280	20948	295	20949	310
550	26381	106	41192	112	28688	119	26243	133	41201	149	29564	163	24809	179	41207	204	41209	224	41213	248	41219	287	41227	303	41234	319
600	20956	109	28431	116	20957	123	20958	138	20959	155	20960	169	20961	186	20962	211	20963	231	20964	256	20965	294	20966	311	20967	327
650	26141	113	41193	120	26087	127	25862	143	28716	160	23017	175	41206	192	22376	218	41210	238	41214	264	41220	301	41228	319	23199	336
700	41188	116	41194	124	50013	132	22132	148	22131	165	25669	181	23228	199	41208	225	29585	245	21355	271	41221	309	41229	327	41235	345
750	26346	119	50619	128	41197	136	24951	152	23051	170	22965	187	40237	205	25642	231	24955	252	21754	279	41222	316	41230	335	41236	353
800	20968	123	25560	132	50673	140	20970	156	20971	175	21903	193	20973	211	20974	238	20975	259	41215	287	20977	324	20978	343	20979	362
850	41189	126	25561	136	41198	145	22163	161	41202	180	41204	199	24833	218	24835	245	25111	266	41216	295	41223	331	41231	350	41237	371
900	41190	130	41195	140	41199	149	22162	166	24283	185	21901	205	24834	224	22395	251	41211	273	41217	303	41224	338	22982	358	41238	379
950	41191	133	41196	143	41200	153	25966	171	41203	191	41205	211	40111	231	24836	258	41212	280	41218	310	41225	346	41232	366	41239	388
1000	20980	136	25607	148	20981	158	21878	175	20983	195	20985	217	26215	237	20986	265	20987	287	20988	319	20989	353	20990	374	20991	396

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

FM1 Breather

Woven polyester breather bag for venting contained vessels




- Designed for breathing applications such as venting hoppers and other contained vessels
- The BFM® breather may become required as the BFM® connectors create a 100% sealed system.

PHYSICAL PROPERTIES:

Material	100% woven polyester needlefelt	
Weight (±10%)	550g/m ² / 16.22oz/yd ²	
Operating Temp Range	-20 - 130 °C / -4 - 266 °F (surge to 150 °C / 302 °F)	
Air Permeability	(cm ³ /cm ² /sec@125Pa)	(ft ³ /ft ² /min@0.5" wg)
	17	33

Maximum Diameter:	650mm
Maximum Length (≤ Ø650mm):	1,000mm
Available with SS Rings?	No
Available with Plastic Rings?	No
Available as TR (Tool Release) option?	Yes



All BFM® fitting connectors comply with 3-A 60-64 Sanitary Fittings

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
100	30544	93	30711	97	30553	100	30562	104	30546	109	30612	118	30807	123	31234	159	30608	186	30654	232	31421	285	31422	301	31424	319
150	30534	93	30668	97	30566	101	30590	104	30716	109	30635	118	30632	123	31235	161	30669	186	31254	234	31426	289	31441	305	31455	323
200	30528	93	30533	97	30569	101	30530	105	30602	110	30629	118	30630	124	30572	163	30689	187	31255	237	31427	293	31167	309	31456	327
250	30540	93	30576	97	30586	102	30601	109	30588	112	30607	119	31229	126	31236	168	31243	188	30805	240	31428	297	31442	313	31457	332
300	30517	94	30525	98	30258	104	30334	110	30545	112	30615	119	30631	127	30604	173	31244	188	30532	240	31429	301	31443	317	31458	336
350	30661	99	30625	100	30600	104	30535	110	30624	115	30637	119	31207	129	31237	175	31245	189	31256	246	31430	306	31444	322	31459	341
400	30589	101	30702	101	30542	104	30567	111	30537	116	30551	119	31022	129	31238	176	30955	189	31201	252	31431	310	31445	326	31460	345
450	30568	101	30666	109	30585	116	30656	122	30791	137	31206	143	31004	150	31239	187	30593	194	31257	258	31432	314	31446	330	31461	350
500	30515	114	30640	117	30548	120	30539	123	30513	137	30557	145	30667	154	30559	192	30598	201	30597	264	31433	318	31447	334	31462	354
550	31200	115	31214	119	30616	124	30606	132	30963	137	30937	147	31230	154	30704	200	31246	202	30623	270	31434	322	31448	338	31463	359
600	30571	116	30854	124	30583	124	30580	132	30541	138	30717	147	30985	154	31240	201	31247	203	30840	274	31435	326	30543	342	31464	363
650	30718	116	31215	124	30610	124	30662	132	30783	138	30619	148	31231	155	31241	201	31248	204	31258	277	31436	330	31449	346	31465	368
700	32190	119	31216	124	30878	124	30688	142	30660	142	30646	149	30956	156	31242	202	32110	205	30671	280	30577	335	31450	350	31466	372
750	30757	124	31217	124	30621	124	30645	142	30524	142	30676	150	31232	160	30850	203	31249	214	31259	284	30574	339	31451	355	31467	376
800	30613	124	31218	124	30614	124	30563	143	30633	143	30558	151	30971	162	30560	205	31250	224	31260	287	31437	343	30651	359	31468	381
850	31210	128	31219	143	30611	143	31222	149	31224	150	31227	163	31182	174	31183	211	31251	234	31261	290	31438	347	31452	363	31469	385
900	31211	131	31220	145	30581	162	30659	162	31225	164	32116	175	31181	185	30808	215	32109	244	31262	293	31439	352	31453	367	31470	389
950	31212	134	31221	148	31180	162	31223	163	31226	165	31228	176	31233	186	31190	221	31252	253	31263	296	31440	356	31454	371	31296	392
1000	32091	136	30674	149	30675	162	30617	163	30564	166	30626	177	30591	186	30677	225	31253	262	30650	299	30516	360	31423	375	31289	396

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of an FM1 Breather Bag, please refer to the 'Add-ons' page 6.

Blanking Cap (Seeflex 040E)

Prevents contamination/used as sight-glasses




- Used to prevent contamination during clean down or change-over.
- They protect products and prevent dust emission into the factory.
- Ideal as sight-glasses for sifters, and other equipment.

Maximum Diameter: 1,650mm
Available as TR (Tool Release) option? Yes (≤ 650mm)

PHYSICAL PROPERTIES:

Material	Ether-based thermoplastic polyurethane alloy
Wall Thickness (±10%)	0.9mm / 1/32 inch
Operating Temp Range	-25 to 110°C / -13 to 230°F (surge to 120°C to 248°F)
Height (Length)	30mm (1 3/16")



DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm	
	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
	20750	80	20761	84	20751	86	20752	93	20709	101	20753	114	20754	133	20755	157	20756	169	20757	204	20758	253

DIA:	Ø600mm		Ø650mm		Ø700mm		Ø750mm		Ø800mm		Ø850mm		Ø900mm		Ø950mm		Ø1,000mm		Ø1,050mm		Ø1,100mm	
	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
	20759	274	20760	288	21865	496	22868	507	21476	511	25086	519	28285	533	60013	554	21866	669	24667	720	21867	735

DIA:	Ø1,150mm		Ø1,200mm		Ø1,250mm		Ø1,300mm		Ø1,350mm		Ø1,400mm		Ø1,450mm		Ø1,500mm		Ø1,550mm		Ø1,600mm		Ø1,650mm	
	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
	22382	785	25197	818	22345	859	29391	916	26468	958	40402	999	24668	1039	24576	1177	40403	1225	26743	1271	28202	1325



The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a Tool Release version of a Blanking Cap, please refer to the 'Add-ons' page 6.

Blanking Bin (Seeflex 040E)

Ideal for sifter oversize collection bins




- Used for collecting overs/reject product on sifters/sieves etc.
- Can be lined with plastic bags for easy disposal of reject product.
- Allows for visibility of product full level and reject consistency.

PHYSICAL PROPERTIES:

Material	Seeflex ether-based thermoplastic polyurethane
Wall Thickness (±10%)	0.9mm / 1/32 inch
Operating Temp Range	-25 to 110°C / -13 to 230°F (surge to 120°C to 248°F)
Height (Length)	30mm (1 1/16")

Maximum Diameter:	1,650mm
Maximum Length:	1,000mm
Available with SS Rings:	Yes (≤ Ø500mm)
Available with Plastic Rings:	No
Available as TR (Tool Release) option?	Yes (≤ Ø650mm)



DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
100	25117	129	29059	137	22733	150	24323	157	22732	173	24437	200	25868	212	26258	273	27033	310	26129	358	29568	394	27032	433	40397	471
150	22851	132	21852	142	25630	155	21709	164	28216	182	21589	211	26194	225	28011	286	24451	324	40474	373	40487	411	40504	451	40521	491
200	21576	135	23022	145	22744	160	24360	171	25350	191	22546	221	26193	237	26709	299	40461	338	29222	389	25870	428	40505	470	40522	510
250	24779	137	22352	149	21309	164	25379	178	24450	200	23039	232	28226	250	40444	312	40462	352	40476	404	40489	445	40506	487	40523	530
300	21967	140	22161	153	21458	169	22878	185	26319	209	25869	242	25842	263	27125	325	50510	366	26624	420	40490	463	40507	506	40524	550
350	21170	143	21804	156	24774	173	60020	192	26176	218	40434	254	25843	276	40445	338	40464	381	40477	435	40491	480	40508	524	40525	569
400	21520	146	22353	160	24638	178	21171	199	23207	227	28530	264	25241	289	29004	351	21908	395	24531	451	40492	497	40509	542	40526	589
450	22946	149	26467	164	22742	182	22231	206	26454	237	22042	275	26200	302	24464	364	28942	409	40479	467	40493	513	40510	561	40527	609
500	22716	152	22212	168	22528	187	21791	213	22885	245	25199	286	25844	315	24938	377	26334	423	28874	482	40494	530	40511	579	40528	629
550	22717	155	40423	171	24755	192	26598	219	27052	255	26950	296	40438	328	40455	390	40467	437	40480	498	40495	548	40512	597	40529	648
600	60012	158	24563	175	24306	196	22088	227	22530	264	22087	307	22487	341	24939	402	40468	451	28332	513	40496	565	40513	615	40530	668
650	26789	160	26798	179	24777	201	24456	234	40432	273	28702	317	40439	354	26337	415	40469	466	40481	529	40497	582	40514	634	40531	688
700	40415	163	26478	182	60017	205	22760	241	25210	282	28068	329	24727	367	25388	428	40470	480	40482	545	40498	599	40515	652	40532	707
750	27126	166	40427	186	25327	209	28514	248	21719	291	28151	339	40440	380	40457	441	24970	494	28072	560	40499	616	40516	670	40533	727
800	25425	169	29198	190	22759	214	22787	254	23156	300	24346	350	26540	393	25394	454	40472	509	40483	576	40500	633	40517	689	40534	747
850	25753	172	40428	194	29600	219	22756	261	29039	310	40435	360	40441	406	24776	467	40473	523	40484	591	40501	650	40518	707	40535	766
900	40417	175	40429	198	25663	223	26014	268	26013	319	25692	371	25780	419	40459	480	25186	537	40485	607	40502	667	40519	725	40536	786
950	40418	178	40430	201	29250	228	28446	276	24794	327	25727	382	40443	432	40460	493	29674	551	40486	622	40503	684	40520	743	40537	806
1000	60026	181	29038	205	60027	232	60028	283	25892	337	25057	393	40385	445	40389	506	28772	565	40391	638	40398	702	40406	761	40407	825

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a Tool Release version or to add Rings, please refer to the 'Add-ons' page 6.

Kevlar Cover

Flame resistant cover to reduce the risk of consequential fires



- Typically used in over pressure and potentially explosive applications.
- Designed to fit over existing connectors and tightened onto the BFM[®] spigot using butterfly clamps.

Maximum Diameter: 1,650mm
Maximum Length: 1,000mm
Available with SS Rings? No
Available with Plastic Rings? No

PHYSICAL PROPERTIES:

Material	Woven Kevlar (Aramid) fibre
Weight (±10%)	447g/m ² / 13.2oz/yd ²
Max. Operating Temp	260°C / 500°F (surge to 300°C / 572°F) (NB: Limited to max. operating temperature of connector underneath)

VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	FOOD SAFETY	ATEX

* Does not come in contact with product therefore can be used in conjunction with a 3A certified inner connector
 Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
80	80273	276	80274	281	80049	285	80130	294	80137	306	80136	314	80135	317	80131	332	80327	351	80141	371	80345	389	80133	409	80134	430
100	80044	276	80123	281	80089	285	80022	294	80068	306	80030	314	80031	317	80098	332	80099	351	80041	371	80055	389	80122	409	80077	430
150	80026	284	80124	290	80025	296	80034	317	80086	329	80023	342	80011	355	80043	369	80085	394	80058	418	80162	442	80016	460	80079	485
200	80045	293	80109	300	80050	306	80002	317	80027	329	80003	342	80057	355	80029	369	80061	394	80004	418	80013	442	80028	460	80095	485
250	80145	301	80275	310	80108	316	80071	328	80090	344	80129	360	80180	375	80069	391	80174	417	80054	443	80175	469	80173	490	80176	517
300	80046	311	80246	321	80019	326	80018	340	80020	360	80021	378	80172	396	80103	414	80212	441	80116	468	80117	496	80118	520	80114	550
350	80263	320	80276	332	80210	337	80119	351	80226	375	80190	396	80177	416	80104	436	80239	466	80217	494	80346	523	80249	550	80231	583
400	80047	329	80277	342	80248	347	80084	363	80216	391	80150	414	80036	436	80017	458	80037	489	80009	519	80347	550	80359	579	80369	615
450	80264	337	80278	352	80289	358	80297	374	80148	407	80107	432	80208	457	80235	481	80328	513	80163	545	80348	577	80144	609	80214	648
500	80048	347	80279	363	80051	368	80052	386	80053	422	80311	450	80065	477	80066	504	80067	537	80243	570	80349	604	80170	640	80370	680
550	80265	356	80280	373	80186	378	80298	397	80300	438	80386	467	80230	497	80183	526	80329	562	80337	595	80350	631	80360	669	80371	713
600	80222	365	80281	384	80236	388	80229	409	80038	454	80205	486	80178	517	80070	549	80330	585	80338	621	80351	658	80361	699	80372	746
650	80266	373	80282	395	80290	399	80299	421	80302	469	80312	503	80211	538	80322	571	80331	609	80339	646	80352	685	80362	729	80223	778
700	80267	383	80283	405	80291	409	80221	432	80305	485	80313	522	80191	558	80152	594	80153	634	80340	671	80353	712	80363	759	80373	811
750	80268	392	80284	415	80292	419	80301	444	80306	501	80014	539	80097	579	80101	617	80332	657	80096	696	80354	739	80364	789	80374	844
800	80269	401	80285	426	80293	430	80181	455	80106	516	80314	557	80318	599	80323	639	80333	681	80341	722	80355	766	80365	818	80375	876
850	80270	409	80286	437	80294	440	80234	467	80307	532	80315	575	80319	619	80324	661	80334	706	80342	747	80356	792	80366	848	80376	909
900	80271	419	80287	447	80295	451	80303	478	80308	548	80316	593	80320	640	80325	684	80335	729	80343	772	80357	820	80367	878	80377	942
950	80272	428	80288	457	80296	461	80304	490	80309	563	80317	611	80321	660	80326	706	80336	753	80344	798	80358	847	80368	908	80378	974
1000	80252	437	80032	468	80253	471	80254	501	80128	579	80255	629	80256	680	80257	729	80258	777	80259	825	80260	874	80261	938	80262	1007

The prices shown above indicate our Recommended Retail Prices (RRP).

Black-out Cover

Designed for light sensitive applications, fits over our entire connector range.



- The cover cuts out all light and is for use in light sensitive areas
- Designed to fit over existing BFM® connectors.
- Easy to install and no tools are required.

PHYSICAL PROPERTIES:

Material	Polypropylene (wire used for the holders is 6mm 304 stainless steel)
Weight (±10%)	207 g/m ² / 6.1 oz/yd ²
Max. Operating Temp	95°C / 203°F

Maximum Diameter:	1,650mm
Maximum Length:	1,000mm
Available with SS Rings?	No
Available with Plastic Rings?	No

VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	FOOD SAFETY	ATEX

* Does not come in contact with product therefore can be used in conjunction with a 3A certified inner connector

Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
80	60057	250	60214	255	60188	258	60184	267	60032	277	60034	285	60037	288	60311	301	60325	318	60189	336	60352	353	60078	371	60381	390
100	60108	250	60234	255	80245	258	60058	267	60033	277	60035	285	60038	288	60039	301	60061	318	60044	336	60074	353	60076	371	60060	390
150	60097	257	60235	263	60046	268	60056	287	60066	298	60036	310	60086	322	60040	335	60201	356	60065	379	60055	401	60219	417	60215	440
200	60220	266	60236	272	60182	277	60030	287	60031	298	60042	310	60048	322	60049	335	60102	356	60045	379	60202	401	60043	417	60187	440
250	60221	274	60237	281	60104	287	60105	298	60073	312	60068	326	60081	340	60064	355	60218	378	60067	402	60353	425	60367	444	60382	469
300	60080	282	60238	291	60178	296	60216	308	60089	326	60287	343	60213	359	60312	375	60099	400	60339	425	60354	450	60368	471	60383	499
350	60222	290	60239	301	60179	306	60262	319	60274	340	60209	359	60300	377	60106	396	60103	422	60340	448	60355	474	60075	499	60384	529
400	60223	298	60240	310	60180	314	60053	329	60275	355	60288	375	60072	396	60088	416	60326	443	60341	471	60356	499	60369	526	60385	558
450	60224	306	60241	320	60253	324	60263	339	60276	369	60289	392	60217	414	60313	437	60327	466	60342	494	60357	523	60370	553	60386	588
500	60183	314	60242	329	60490	333	60264	350	60098	383	60290	408	60181	432	60314	457	60328	487	60343	517	60191	548	60371	580	60493	617
550	60054	323	60243	339	60491	343	60265	360	60277	397	60291	424	60301	451	60315	477	60329	509	60344	540	60358	572	60372	607	60387	647
600	60225	331	60244	348	60254	352	60266	371	60278	411	60292	440	60302	470	60316	498	60330	530	60194	563	60192	596	60205	634	60193	676
650	60226	339	60245	358	60255	362	60267	381	60279	425	60293	457	60303	488	60317	518	60331	552	60345	586	60359	621	60373	661	60388	706
700	60227	347	60246	368	60256	371	60063	392	60280	440	60294	473	60304	506	60318	539	60332	573	60346	609	60360	645	60374	688	60389	736
750	60228	355	60247	377	60257	381	60268	402	60281	454	60295	489	60305	525	60319	559	60333	596	60203	633	60361	670	60375	715	60204	765
800	60229	363	60248	386	60258	390	60269	412	60282	468	60296	506	60306	543	60320	579	60334	617	60347	655	60362	694	60376	742	60391	795
850	60230	372	60249	396	60259	399	60270	423	60283	483	60297	522	60307	562	60321	600	60335	640	60348	679	60363	719	60377	769	60392	824
900	60231	380	60250	405	60260	409	60271	434	60284	497	60210	538	60308	580	60322	620	60336	661	60349	702	60364	743	60378	797	60393	854
950	60232	388	60251	415	60185	418	60272	444	60285	511	60298	554	60309	598	60323	641	60337	683	60350	725	60365	768	60379	824	60394	883
1000	60233	396	60252	424	60261	427	60273	454	60286	525	60299	571	60310	617	60324	661	60338	706	60351	750	60366	792	60380	851	60395	913

The prices shown above indicate our Recommended Retail Prices (RRP).

Bulk Bag Loader

A three-layered, inflatable filling head featuring a stainless steel core fully encased in Seeflex ether-based urethane.



- Includes external air fitting that plugs into an 8mm pneumatic air line to inflate super strong & flexible outer layer.
- Top of loader simply snaps into a BFM® fitting spigot and features a fully encapsulated stainless steel ring to support lower end.
- All Bulk Bag Loaders are a standard length of 330mm.

PHYSICAL PROPERTIES:

Material	Seeflex -Ether-based thermoplastic polyurethane with stainless steel core
Wall Thickness (±10%)	0.9mm / 1/32 inch
Operating Temp Range	-25 to 110°C / -13 to 230°F (surge to 120°C to 248°F)
Surface Resistivity(Ohms)	10 ¹⁰

Maximum Diameter:	450mm
Available with SS Rings?	No
Available with Plastic Rings?	No



* Material only

DIA:	Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm	
LENGTH: (mm)	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:	Part No:	RRP EU€:
330mm	305078	844	305075	876	304794	909	304793	941	304791	974	302363	1006	304828	1071



The prices shown above indicate our Recommended Retail Prices (RRP).

BFM® GLOBAL LTD. | To order BFM® fitting products, please contact your local Distributor - you can find them at BFMfitting.com