

# Recommended Retail Price

BFM<sup>®</sup> Standard Range

**Connectors • Caps • Covers • Spigots**

The prices indicated in this document are our Recommended Retail Prices (RRP). There may be slight price variations in local markets.

These prices are based on a NZD/USD exchange rate of 1 NZD:0.63 USD. Exchange rates are reviewed at the end of each month. If there is a movement greater than 5% to this rate then the price list will be updated & uploaded by working day 5 of the following month. End of month rates are obtained from <https://www.reuters.com/markets/currencies>

# Contents

## Spigots .....01

Lipped Spigot ..... 01

## Seeflex ..... 02

Seeflex O40E .....02

Seeflex O40AS .....03

Seeflex O20E .....04

Seeflex O60ES .....05

## Add-Ons ..... 06

TR (Tool Release) .....06

TR (Tool Release) Tools .....06

'Smiley Face' Hole Punch .....06

Quick Access Port ..... 07

Rings .....07

## Flexi ..... 08

Flexi / Flexi-Light .....08

Flexi-Earthed .....09

## Teflex ..... 10

Teflex Woven .....10

Teflex NP Black ..... 11

Teflex NP Opaque ..... 12

## LM3 ..... 13

## LM4 ..... 14

## FM1 Breather .....15

## Blanking Cap ..... 16

## Blanking Bin .....17

## Kevlar Cover ..... 18

## Black-out Cover ..... 19

## Bulk Bag Loader ..... 20

## Spigots

Welds to your pipes to allow snap-in fitting of BFM® connectors



- Available in 304L SS and 316L SS (Hastelloy available on request)
- The spigot design is slightly tapered, so the OD at the top of the tail is 5mm / 13/64" greater than the base
- BFM® spigots are 89mm (3 1/2") in total length - made up of a head of 37mm (1 29/64") and a 'tail' that is 52mm (2") long

**Note:**

- The 'tail' of the spigot can be cut to tailor the perfect fit for your available space (ensure caution is used when welding not to distort spigot head).
- Download the BFM® IG (Installation Gap) Calculator App to ensure correct between spigots before welding or contact your BFM® Distributor for help.

**PHYSICAL PROPERTIES:**

Material	304L SS or 316L SS
Wall Thickness	2.0mm/ 5/64"



DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
<b>304 LSS</b>	20000	130	21287	132	20001	135	20002	146	20003	168	20004	188	20005	212	20006	239	20007	259	20008	300	20009	357	20010	391	20011	406
<b>316 LSS</b>	20020	206	21288	210	20021	236	20022	260	20023	287	20024	328	20025	375	20026	424	20027	511	20028	534	20029	584	20030	599	20031	607

\* Ø100mm measured externally (OD), all other Ø measured internally (ID).

DIA:	Ø700mm		Ø750mm		Ø800mm		Ø850mm		Ø900mm		Ø950mm		Ø1,000mm		Ø1,050mm		Ø1,100mm		Ø1,150mm		Ø1,200mm		Ø1,250mm		Ø1,300mm	
	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
<b>304 LSS</b>	20012	843	20013	952	20014	1045	20015	1155	20016	1196	20017	1319	20018	1346	22222	1429	21203	1631	22815	1623	21161	1680	21434	1691	20019	1712
<b>316 LSS</b>	20032	926	20033	1007	20034	1351	20035	1486	20036	1590	20037	1602	20038	1630	22794	1739	21853	1845	22795	1859	21934	1908	25426	2008	60022	2111

DIA:	Ø1,350mm		Ø1,400mm		Ø1,450mm		Ø1,500mm		Ø1,550mm		Ø1,600mm		Ø1,650mm	
	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
<b>304 LSS</b>	21435	1733	21436	1753	22223	1852	21125	1957	22802	2039	21012	2365	21121	2378
<b>316 LSS</b>	25406	2222	25427	2315	25432	2444	22317	2580	25428	2693	25429	2805	22007	3139

**Tool Release Holes:** Spigots can be supplied with standard round tool-release holes pre-drilled or smiley-face tool release holes pre-punched for an additional fee of NZ\$50 per hole. **PLEASE NOTE: These pre-drilled/punched TR spigots have different part numbers to those shown here.**

## Lipped Spigot

Allows easy integration with quick-connect, clamped modular tubing/piping systems

To enable a BFM® fitting system to be integrated with 'quick connect' modular tubing/piping, a range of our 304SS spigots are available with a 6mm rolled 'lip'. The lip of the spigot clamps in place with the corresponding modular lip using quick-release clamp systems like Jacob.

DIA:	Ø100mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm	
	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
<b>304 LSS</b>	20039	168	20041	173	20042	184	20043	206	20044	226	20045	250	20046	277

The prices shown above indicate our Recommended Retail Prices (RRP).



**NOTE:** a BFM® Lipped Spigot has a 6mm shorter overall height/length of 83mm.

## Seeflex 040E

Strong, resilient, multi-purpose connector




- Used on all types of stationary, vibratory and gyratory sifters, screeners, feeders, bin discharges, hoppers, conveyors, any packing or product handling equipment.
- Superior wear resistance - used in CIP and washing.
- Available as a specially-marked " Wash Sleeve "version (add US\$7 to price below).
- Available as Quick Access Port option

**Maximum Diameter:** 1,650mm  
**Maximum Length (≤ Ø650mm):** 6,000mm  
**Available with SS Rings?** Yes (≤ Ø500mm)  
**Available with Plastic Rings?** Yes  
**Available as TR (Tool Release) option?** Yes (≤ Ø650mm)

### PHYSICAL PROPERTIES:

<b>Material</b>	Ether-based thermoplastic polyurethane alloy
<b>Wall Thickness (±10%)</b>	0.9mm / 1/32 inch
<b>Operating Temp Range</b>	-25 to 110°C / -13 to 230°F (surge to 120°C to 248°F)
<b>Surface Resistivity (Ohms)</b>	10 <sup>10</sup>



Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
80	21871	83	22554	93	21756	95	21395	110	21259	126	21969	145	21984	161	22564	197	22566	217	22166	245	22569	253	22573	307	22413	324
100	20050	87	22000	98	20061	101	20072	116	20083	133	20094	153	20105	170	20116	207	20127	228	20138	248	20149	266	20160	323	20171	341
150	20051	90	22001	99	20062	108	20073	120	20084	138	20095	159	20106	177	20117	221	20128	240	20139	249	20150	278	20161	335	20172	355
200	20052	94	22002	105	20063	115	20074	127	20085	146	20096	167	20107	186	20118	227	20129	252	20140	262	20151	292	20162	353	20173	374
250	20053	106	22168	125	20064	130	20075	155	20086	181	20097	203	20108	236	20119	277	20130	320	20141	335	20152	375	20163	440	20174	468
300	20054	115	22247	138	20065	140	20076	168	20087	195	20098	224	20109	256	20120	301	20131	344	20142	360	20153	404	20164	477	20175	507
350	20055	120	22555	147	20066	151	20077	170	20088	228	20099	230	20110	265	20121	331	20132	351	20143	385	20154	411	20165	501	20176	551
400	20056	122	22071	152	20067	150	20078	171	20089	231	20100	231	20111	272	20122	319	20133	369	20144	386	20155	432	20166	504	20177	553
450	20057	133	22556	167	20068	164	20079	197	20090	240	20101	265	20112	293	20123	355	20134	394	20145	428	20156	461	20167	550	20178	588
500	20058	140	22003	169	20069	172	20080	207	20091	269	20102	280	20113	297	20124	374	20135	415	20146	451	20157	485	20168	580	20179	619
550	20059	150	22557	173	20070	178	20081	224	20092	275	20103	292	20114	312	20125	411	20136	464	20147	497	20158	535	20169	636	20180	677
600	20060	154	21386	175	20071	179	20082	224	20093	285	20104	296	20115	323	20126	440	20137	493	20148	533	20159	576	20170	678	20181	713
650	22552	158	22558	180	21385	191	21208	244	21955	285	21742	318	22562	334	22500	444	22567	496	22170	536	22572	581	22577	681	22578	728
700	21278	159	22559	181	21231	201	21569	255	21353	297	22280	318	22563	351	21405	446	22249	498	21262	542	22571	584	22576	684	22579	731
750	22553	161	22560	192	21794	203	21560	257	21691	299	22338	321	23005	382	22252	456	22568	524	22506	547	22570	615	22575	713	22580	755
800	20570	162	21387	205	20571	203	20572	258	20573	301	20574	338	20575	382	20576	461	20577	534	20578	549	20579	635	20580	714	20581	757
850	24431	194	25562	215	21675	242	21839	285	22874	333	24964	384	24496	390	24771	488	26756	574	26657	597	40695	696	40696	748	40697	804
900	24593	202	28310	224	21943	253	21257	299	21786	346	21282	399	23088	411	21956	512	24320	598	22748	625	40726	725	22803	779	40728	837
950	22855	211	40724	234	22326	263	21607	312	22169	359	22099	414	24424	432	29732	535	21561	622	40725	653	40727	753	26267	810	26453	871
1000	20590	219	21468	243	20591	275	20592	325	20593	372	20594	428	20595	452	20596	558	20597	646	20598	682	20599	782	20600	841	20601	904

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

## Seeflex 040AS

Designed to dissipate static, ideal for potentially explosive areas




- Transparent, 'anti-static' connector, designed to dissipate static
- Excellent abrasion, chemical and puncture resistance

### PHYSICAL PROPERTIES:

Material	Ether-based thermoplastic polyurethane alloy with an anti-static infusion
Wall Thickness (±10%)	0.9mm / 1/32 inch
Operating Temp Range	-25 to 95°C / -13 to 203°F (surge to 100°C to 212°F)
Surface Resistivity (Ohms)	10 <sup>8</sup> (very good at dissipating static)

Maximum Diameter:	1,650mm
Maximum Length (≤ Ø650mm):	6,000mm
Available with SS Rings?	Yes (≤ Ø500mm)
Available with Plastic Rings?	Yes
Available as TR (Tool Release) option?	Yes (≤ Ø650mm)



Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
80	70082	103	70098	117	70114	125	70130	140	70146	160	70162	185	70178	205	70194	253	70210	278	70226	323	70242	331	70258	416	70274	423
100	70083	108	70099	123	70115	131	70131	147	70147	168	70163	195	70179	216	70195	266	70211	297	70227	332	70243	348	70259	420	70275	445
150	70084	108	70100	134	70116	146	70132	155	70148	180	70164	208	70180	231	70196	290	70212	321	70228	335	70244	374	70260	449	70276	477
200	70085	116	70101	134	70117	153	70133	160	70149	190	70165	219	70181	244	70197	300	70213	338	70229	353	70245	394	70261	473	70277	501
250	70086	123	70102	146	70118	158	70134	185	70150	219	70166	256	70182	260	70198	338	70214	392	70230	411	70246	464	70262	541	70278	577
300	70087	130	70103	148	70119	166	70135	195	70151	231	70167	269	70183	304	70199	355	70215	413	70231	433	70247	488	70263	570	70279	608
350	70088	135	70104	156	70120	175	70136	199	70152	277	70168	285	70184	316	70200	382	70216	427	70232	469	70248	503	70264	608	70280	650
400	70089	138	70105	181	70121	178	70137	200	70153	283	70169	297	70185	328	70201	382	70217	449	70233	470	70249	529	70265	610	70281	652
450	70090	153	70106	197	70122	198	70138	234	70154	318	70170	323	70186	361	70202	423	70218	473	70234	518	70250	560	70266	665	70282	713
500	70091	161	70107	209	70123	207	70139	246	70155	334	70171	340	70187	372	70203	445	70219	498	70235	546	70251	590	70267	701	70283	750
550	70092	175	70108	214	70124	214	70140	292	70156	351	70172	363	70188	430	70204	497	70220	561	70236	614	70252	664	70268	784	70284	837
600	70093	188	70109	216	70125	217	70141	294	70157	353	70173	367	70189	469	70205	532	70221	605	70237	674	70253	722	70269	835	70285	866
650	70094	189	70110	221	70126	236	70142	298	70158	353	70174	398	70190	476	70206	553	70222	610	70238	679	70254	726	70270	844	70286	896
700	70095	193	70111	226	70127	251	70143	305	70159	361	70175	413	70191	481	70207	559	70223	624	70239	714	70255	742	70271	861	70287	924
750	70096	195	70112	232	70128	257	70144	307	70160	365	70176	427	70192	484	70208	564	70224	637	70240	736	70256	757	70272	871	70288	934
800	70097	196	70113	245	70129	255	70145	309	70161	366	70177	430	70193	486	70209	566	70225	656	70241	755	70257	781	70273	873	70290	937
850	71021	231	70944	275	70389	290	70352	364	70933	424	71161	493	71162	549	71164	622	71165	731	71167	811	71169	883	71171	983	71173	1055
900	70805	240	71149	284	70392	302	70488	379	70291	442	71086	515	70587	573	71183	650	71186	759	71189	842	71192	917	71195	1018	71198	1094
950	71177	249	71178	294	70505	313	70487	394	71179	461	71155	536	71180	598	71184	677	71187	787	71190	873	71193	950	71196	1054	71199	1133
1000	70795	258	70752	303	70533	324	70379	410	70303	479	70423	557	71182	622	71185	704	71188	815	71191	903	71194	983	71197	1090	71200	1172

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

## Seeflex 020E

Lightweight & flexible, ideal for weighscale applications




- Transparent, light weight Seeflex media, specifically designed for load and weigh scale type equipment
- Also very good in applications with vertical movement as it is particularly flexible

### PHYSICAL PROPERTIES:

Material	Ether-based thermoplastic polyurethane alloy
Wall Thickness (±10%)	0.35mm / 1/64 inch
Operating Temp Range	-25 to 80°C / -13 to 176°F (surge to 100°C to 212°F)
Surface Resistivity (Ohms)	10 <sup>10</sup>

Maximum Diameter:	1,650mm
Maximum Length (≤ Ø650mm):	6,000mm
Available with SS Rings?	On request only
Available with Plastic Rings?	On request only
Available as TR (Tool Release) option?	Yes (≤ Ø650mm)



Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
80	22155	83	22598	93	22610	95	22615	110	22360	126	21680	145	22622	161	22244	197	22646	217	22156	245	22672	253	22243	307	22699	324
100	20789	87	23000	98	20790	101	20791	116	20792	133	20793	153	21360	170	21361	207	21362	228	21363	248	21364	266	21365	323	21366	341
150	20690	90	23001	99	21222	108	21432	120	21317	138	21787	159	22623	177	22548	221	22647	240	22659	249	22673	278	22686	335	22700	355
200	21849	94	23002	105	21438	115	20692	127	20693	146	20694	167	21207	186	20695	227	20696	252	20697	262	20698	292	20699	353	20703	374
250	22425	106	22599	125	21781	130	21997	155	21613	181	21398	203	22624	236	22635	277	22648	320	22660	335	22674	375	22687	440	22701	468
300	21922	115	22342	138	21195	140	21837	168	21194	195	21384	224	22349	256	22636	301	22649	344	22661	360	22675	404	22688	477	22702	507
350	22590	120	22600	147	21882	151	21838	170	21774	228	21408	230	22625	265	22637	331	22650	351	22662	385	22676	411	22689	501	22703	551
400	22491	122	22601	152	21415	150	21308	171	21307	231	21784	231	22626	272	21806	319	22651	369	22063	386	22677	432	22690	504	22704	553
450	22591	133	22602	167	22492	164	22616	197	22316	240	22620	265	22627	293	22638	355	22652	394	22663	428	22678	461	22691	550	22705	588
500	23004	140	22603	169	22216	172	21303	207	21726	269	21915	280	22628	297	22639	374	22653	415	22664	451	22679	485	22692	580	22706	619
550	22592	150	22604	173	22611	178	21321	224	22445	275	21827	292	22629	312	22640	411	21913	464	22665	497	22680	535	22693	636	22707	677
600	22593	154	22605	175	21941	179	22040	224	22499	285	22621	296	22630	323	22641	440	22654	493	22666	533	22681	576	22694	678	22708	713
650	22594	158	22606	180	21369	191	22336	244	22618	285	21591	318	22631	334	22642	444	22655	496	22667	536	22682	581	22695	681	22709	728
700	22595	159	22607	181	22612	201	22104	255	22619	297	21636	318	22632	351	22643	446	22656	498	22668	542	22683	584	22696	684	22710	731
750	22596	161	22608	192	22613	203	22617	257	22150	299	21624	321	22633	382	22644	456	22657	524	22669	547	22684	615	22697	713	22711	755
800	22597	162	22609	205	22614	203	21714	258	22142	301	21189	338	22634	382	22645	461	22658	534	22670	549	22685	635	22698	714	22712	757
850	29178	194	41568	215	29459	242	24342	285	22315	333	23059	384	24837	390	24839	488	41573	574	26658	597	41581	696	41585	748	41588	804
900	41566	202	41569	224	22077	253	23154	299	23167	346	23168	399	24838	411	24840	512	41574	598	41578	625	41582	725	41586	779	41589	837
950	41567	211	41570	234	24767	263	22034	312	21699	359	40701	414	41571	432	24841	535	41575	622	41579	653	41583	753	41587	810	41590	871
1000	27031	219	26569	243	40148	275	21448	325	21631	372	21592	428	41572	452	41577	558	41576	646	41580	682	41584	782	22058	841	41591	904

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.



## Seeflex 060ES

Superior strength for over-pressure situations




- Pressure-resistant Seeflex 060ES is a semi-transparent connector with an internal polyester scrim
- The internally bonded scrim restricts the Seeflex sleeve from stretching
- For over-pressure situations for continuous pressure up to 1.7 bar

### PHYSICAL PROPERTIES:

<b>Material</b>	Seeflex - Ether-based thermoplastic polyurethane alloy with internally bonded polyester scrim
<b>Wall Thickness (±10%)</b>	1.3mm / 1/16 inch
<b>Operating Temp Range:</b>	-25 - 120°C / -13 - 248°F (surge to 140°C / 284°F)

<b>Maximum Diameter:</b>	1,650mm
<b>Maximum Length:</b>	1,000mm
<b>Available with SS Rings?</b>	No
<b>Available with Plastic Rings?</b>	No
<b>Available as TR (Tool Release) option?</b>	Yes (≤ Ø650mm)



\* Longer lengths only

Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
80	30763	156	30764	171	30856	187	30869	210	30929	238	30779	272	30780	297	30912	335	30930	364	31109	375	31121	404	31136	463	31151	491
100	30782	156	30806	171	30776	187	30760	210	30748	238	30731	272	30739	297	30836	335	30767	364	30827	375	30837	404	30925	463	31029	491
150	30773	164	30753	180	30746	198	30761	223	30762	253	30769	289	30727	317	30730	357	30790	387	30891	401	30832	433	31137	493	30890	524
200	30788	173	30908	190	30726	209	30729	236	30740	269	30771	306	30766	336	30770	378	30768	411	30732	427	30797	461	30794	524	30755	556
250	30887	181	31045	200	30777	219	30778	249	30818	284	30723	323	30867	356	30781	400	30951	435	30972	453	31122	489	30858	554	31152	588
300	30789	190	30988	209	30803	230	30831	261	30785	299	30819	340	30826	376	30888	421	31096	459	30855	479	30962	517	31138	585	31153	621
350	30933	198	31046	219	31057	241	30843	275	30821	314	30889	358	30913	396	30986	443	31097	483	30859	505	31123	546	30866	615	31154	653
400	30934	207	31047	229	31058	251	30845	287	31065	329	30744	375	30765	415	31086	465	31098	507	31110	532	31124	573	31139	645	31155	686
450	30935	215	30970	239	30917	262	30943	301	30820	345	31073	392	30846	435	30939	486	31099	531	30896	558	31125	602	31140	676	31156	719
500	31038	224	31048	248	31012	273	30942	313	30754	360	30931	410	31079	454	31087	508	31100	555	31111	584	31126	630	31141	706	31157	751
550	30857	232	31049	258	30906	284	31060	326	30863	375	30798	427	30904	474	30745	530	31101	579	31112	610	31127	658	31142	736	31158	784
600	30851	241	30910	268	30997	295	30811	339	30828	390	30796	444	30886	494	31088	551	30737	603	31113	636	31128	686	31143	767	31159	816
650	31039	249	31050	278	30918	306	30909	352	31066	405	31074	461	30847	513	31089	573	31102	627	31114	662	31129	714	31144	798	31160	849
700	31040	258	31051	287	30919	316	31061	365	31067	420	31075	478	31080	533	31090	595	31103	651	31115	688	31130	742	31145	828	31161	881
750	31041	266	31052	297	31059	327	31062	377	31068	435	31076	495	31081	553	31091	617	31104	675	31116	714	31131	770	31146	858	31162	914
800	31042	275	31053	307	30860	338	30873	391	31069	450	30932	513	31082	572	31092	638	31105	699	31117	740	31132	799	31147	889	31163	947
850	30861	284	31054	317	30959	348	31063	403	31070	466	31077	530	31083	592	31093	660	31106	723	31118	767	31133	827	31148	919	31164	979
900	31043	292	31055	326	30981	359	30998	416	31071	481	30905	547	31084	612	31094	682	31107	747	31119	793	31134	855	31149	949	31165	1012
950	31044	301	31056	336	30944	370	31064	429	31072	496	31078	564	31085	631	31095	703	31108	770	31120	818	31135	883	31150	980	31166	1045
1000	31030	309	31032	346	30772	381	30795	442	30877	512	30949	581	31033	651	31034	725	31035	794	31036	845	31037	912	31028	1011	31027	1077

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

## TR (Tool Release)

As an added safety option, all BFM® fitting connectors are available in a TR (Tool Release) version which have a firmer snap-band that is virtually impossible to remove by hand. To calculate the price of a TR version of a connector, **simply add the following to the RRP of the standard connector price (based on the Diameter):**

*Maximum possible diameter for TR is Ø650mm*

Diameter:	Ø100mm	Ø125mm	Ø150mm	Ø200mm	Ø250mm	Ø300mm	Ø350mm	Ø400mm	Ø450mm	Ø500mm	Ø550mm	Ø600mm	Ø650mm
	RRP US\$:	RRP US\$:	RRP US\$:	RRP US\$:	RRP US\$:	RRP US\$:	RRP US\$:	RRP US\$:	RRP US\$:	RRP US\$:	RRP US\$:	RRP US\$:	RRP US\$:
Add on to standard Connector price	15	15	18	21	22	25	28	32	61	62	66	69	73

## TR (Tool Release) Tools

To remove the TR Connectors, a special BFM® 'TR Tool' is required. Our standard TR Tool option features a rounded end tool and only requires the spigot to have a 6mm hole drilled in the outer most ridge. The 'Smiley Face' tool has an additional level of safety as it is used with a specially shaped hole (see adjacent information).

	Part No:	RRP US\$:
Standard Tool Release Tool	304990	50
Smiley Face Tool Release Tool	304991	50



## 'Smiley Face' Hole Punch

For additional security, and to avoid staff improvising tools to remove connectors, our 'Smiley Face' Tool Release option is a popular choice. There is a special pneumatic 'punch tool' (shown right) that makes the custom-shaped holes. Spigots can be supplied with the holes pre-punched for a small additional charge. Contact your local distributor for more information.

	Part No:	RRP US\$:
Smiley Face Hole Punch	10402	P.O.A.



*The prices shown above indicate our Recommended Retail Prices (RRP).*



## Quick Access Port

The Quick Access Port is a removable screw in plug that can be added to the wall of Seeflex O40E and Seeflex O60ES connectors to aid in-line testing/sampling (includes tapered versions).

For minimum 150mm diameter and 150mm length connectors.



	<b>RRP US\$:</b>
Add on to standard Connector RRP price	249

## Rings

Applicable to: Seeflex O40E (including Wash Sleeves and Blanking Socks/Bins). Seeflex O40AS, LM3, LM4, Teflex and Teflex NP.

Anti-collapse rings can be added to help keep the connector walls open. This is particularly useful if operating under vacuum or for longer connectors where there may be the potential for the connector walls to be 'sucked' inwards. Rings are available in stainless steel (to Ø500mm) or plastic (to Ø1,650mm & max operating temperature of 110°C/230°F) and can be added to connectors at least 150mm (5") long if made from the materials listed above (subject maximum applicable diameters).

To calculate the price of a ringed version of a connector, simply add the following price per ring to the RRP of the standard connector price (based on the Diameter):

DIA (mm):	Ø100	Ø125	Ø150	Ø200	Ø250	Ø300	Ø350	Ø400	Ø450	Ø500	Ø550	Ø600	Ø650	Ø700	Ø750	Ø800	Ø850	Ø900	Ø950	Ø1000	
	<b>RRP US\$:</b>	<b>RRP US\$:</b>	<b>RRP US\$:</b>	<b>RRP US\$:</b>	<b>RRP US\$:</b>	<b>RRP US\$:</b>	<b>RRP US\$:</b>	<b>RRP US\$:</b>	<b>RRP US\$:</b>	<b>RRP US\$:</b>	<b>RRP US\$:</b>	<b>RRP US\$:</b>	<b>RRP US\$:</b>	<b>RRP US\$:</b>	<b>RRP US\$:</b>	<b>RRP US\$:</b>	<b>RRP US\$:</b>	<b>RRP US\$:</b>	<b>RRP US\$:</b>	<b>RRP US\$:</b>	<b>RRP US\$:</b>
Stainless Steel Rings	52	55	62	73	76	80	90	97	104	111	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Plastic Rings	69	76	83	90	97	104	111	115	118	118	118	118	125	166	180	194	215	229	243	263	

- The distance between spigot & rings is 75mm (3") for 150mm long connectors, and 100mm (4") for all others.
- Multiple rings need to be evenly spaced at a minimum of 100mm (4") apart for connectors up to 800mm long inclusive (maximum 4 rings) and 200mm (8") apart for connectors 850mm long and over (maximum 10 rings). Refer to our 'Quick Ref Limitations Summary' document for more information.
- The diameter of the steel ring itself is 6mm (15/64), the plastic ring itself is 8mm (5/16") and the 'connector' that joins the plastic ring together is approx. 10mm (25/64").



The prices shown above indicate our Recommended Retail Prices (RRP).

## Flexi / Flexi-Light

Lightweight connector with support coil - ideal for bag feeders & filling heads




- A lightweight Seeflex connector with an encased 316 stainless steel wire coil to support flex and compression
- Used for bag feeders, filling heads or bulk bag fillers.
- Flexi-Light features a slightly lighter material and wire coil

### PHYSICAL PROPERTIES:

<b>Material</b>	Ether-based thermoplastic polyurethane with a 316 stainless steel wire coil	
<b>Wall Thickness (±10%):</b>	<b>FLEXi</b>	0.60mm / 1/32" (Ø100 - 200mm / 4 - 8") 0.70mm / 1/32" (Ø250 - 300mm/10 - 12")
	<b>FLEXI-LIGHT</b>	0.4mm / 1/64"
<b>Wire Coil Diameter</b>	<b>FLEXI</b>	2.6mm / 1/8"
	<b>FLEXI-LIGHT</b>	1.6mm / 1/16"
<b>Operating Temp Range:</b>	- 20 to 85°C / - 4 to 185°F	

<b>Available Diameters:</b>	100mm, 150mm, 200mm, 250mm, 300mm
<b>Minimum Length:</b>	200mm
<b>Maximum Length:</b>	6,000mm
<b>Available as TR (Tool Release) option?</b>	Yes



\* Subject to length & movement restrictions.

### FLEXI:

DIA:	Ø100mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm	
LENGTH: (mm)	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
200	25701	482	26152	498	22116	535	25910	659	21197	690
250	26905	491	26139	514	22190	559	26000	688	22938	725
300	26009	503	25871	525	21623	577	26825	712	21732	757
350	26233	512	25898	541	22136	600	26419	741	23104	787
400	25877	520	25615	554	23100	622	25789	768	21765	820
450	26156	530	25798	573	23101	642	25836	797	23099	853
500	26027	541	25899	581	23102	663	26415	822	60023	887
550	28884	553	25950	595	23103	685	25790	840	40277	922
600	25761	562	26640	610	23087	706	25791	859	22757	956
650	29278	573	28090	625	23111	730	28503	891	25207	988
700	26246	583	26252	640	24293	748	26430	922	25507	1020
750	28883	591	26033	654	24645	770	26371	954	23105	1052
800	25592	602	26358	668	22392	791	25720	985	22793	1088
850	29028	614	25593	681	24660	815	26904	1009	22804	1122
900	26525	619	25999	698	24818	836	25650	1031	22137	1155
950	26067	629	29970	714	26681	857	25668	1058	25671	1189
1000	25927	638	25928	731	24334	877	26581	1094	26866	1222

### FLEXI - LIGHT:

DIA:	Ø100mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm	
LENGTH: (mm)	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
200	28372	460	28279	479	28278	495	28869	597	29260	625
250	29479	469	28201	493	28200	514	29241	622	29736	655
300	40300	481	28262	507	28264	534	28261	646	28742	684
350	40301	493	29077	521	29194	553	29067	670	28744	714
400	29565	505	28934	535	28199	573	28877	694	28743	743
450	40302	517	28280	549	29259	592	28768	719	28500	773
500	28914	529	29157	563	29274	611	29193	743	29504	802
550	40303	536	40312	576	29569	631	40321	767	28918	832
600	28856	544	40313	590	29566	650	28494	791	29322	861
650	40304	553	40314	604	29328	670	40322	816	40258	891
700	40305	561	28281	618	40319	689	28941	840	40257	920
750	40306	569	40315	632	29060	708	40323	864	40267	949
800	40307	577	28552	646	29641	728	40324	888	40329	978
850	40308	586	40316	660	40320	747	40325	913	29607	1009
900	40309	594	29547	673	40150	767	28481	937	40330	1038
950	40310	602	40317	687	29966	787	40326	961	40331	1067
1000	40311	610	40318	701	29593	806	40327	985	40332	1096

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector, please refer to the 'Add-ons' pages.

## Flexi-Earthed

Flexi-connector with support coil & earthing terminal lugs



- A standard Flexi connector with built-in terminal earthing lugs attached to the ends of the wire coil.
- Terminal lugs are designed to be attached to earthing cables to provide maximum electrostatic safety.

### PHYSICAL PROPERTIES:

<b>Material</b>	Ether-based thermoplastic polyurethane with a 316 stainless steel wire coil & Ø5mm SS earthing lugs
<b>Wall Thickness (±10%):</b>	0.60mm / 1/32" (Ø100 - 200mm / 4 - 8") 0.70mm / 1/32" (Ø250 - 300mm/10 - 12")
<b>Wire Coil Diameter</b>	2.6mm / 1/64"
<b>Operating Temp Range:</b>	- 20 to 85°C / - 4 to 185°F

**Available Diameters:**

100mm, 150mm, 200mm, 250mm, 300mm


**Minimum Length:**

250mm

**Maximum Length:**

6,000mm

**Available as TR (Tool Release) option?** Yes



\* Subject to length and movement restrictions

### FLEXI - EARTHED:

DIA:	Ø100mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm	
LENGTH: (mm)	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
250	29256	540	28795	563	28360	608	28845	736	28432	773
300	28825	551	28826	574	28314	626	28412	760	28872	806
350	40363	560	40265	589	28741	648	28448	789	28875	835
400	29083	568	28472	602	28864	670	29017	816	28519	869
450	40766	579	29023	622	28345	690	28701	845	28471	902
500	29497	589	28849	630	28529	712	28491	871	28660	936
550	40298	601	29917	644	29665	733	29942	889	28963	970
600	40360	610	29551	659	28833	755	28359	908	29321	1004
650	29627	621	40770	673	29196	778	40774	939	40778	1037
700	40767	631	29197	689	28848	796	28897	970	40779	1068
750	40299	639	40771	702	28766	818	40755	1002	40780	1101
800	29967	651	29292	716	28185	840	29057	1033	40781	1137
850	40768	662	40772	730	28501	864	40775	1058	40782	1171
900	29074	667	29075	747	28957	885	40776	1080	29390	1204
950	40769	677	29577	763	40400	905	40777	1107	40783	1237
1000	29289	687	40773	780	28765	925	28730	1142	28775	1270



Flexi-Earthed Terminal Lugs:



The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector, please refer to the 'Add-ons' pages.

**BFM® GLOBAL LTD.** | To order BFM® fitting products, please contact your local Distributor - you can find them at [BFMfitting.com](http://BFMfitting.com)

## Teflex Woven

100% woven Polyester - suitable for higher temperatures



- Capable of running at high temperatures – continuously operating at 260°C / 500°F with short term surges at 280°C / 536°F.
- Can be used on products across the full pH scale, i.e. either caustic or acid products will not effect Teflex Woven.


### PHYSICAL PROPERTIES:

Material	Woven PTFE	
Weight (±10%)	678g/m <sup>2</sup> / 20oz/yd <sup>2</sup>	
Operating Temp Range	-40 - 260°C / -40 - 500°F (surge to 280°C / 536°F)	
Air Permeability	(cm <sup>3</sup> /cm <sup>2</sup> /sec@125Pa)	(ft <sup>3</sup> /ft <sup>2</sup> /min@0.5" wg)
	0.3	0.5

**Maximum Diameter:** 1,650mm  
**Maximum Length (≤ Ø650mm):** 1,500mm  
**Available with SS Rings?** Yes (≤ Ø500mm)  
**Available with Plastic Rings?\*** Yes

**Available as TR (Tool Release) option?** Yes (≤ Ø650mm)

\*to Max. Operating Temp of 110°C / 230° F



Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
80	30465	279	40909	300	26659	399	30443	561	25395	638	30308	716	25284	742	30488	767	31280	837	26304	927	31281	1022	31282	1414	31283	1533
100	30079	279	30080	300	30081	399	21507	561	30065	638	21534	716	21470	742	30082	767	30083	837	30084	927	30085	1022	21535	1414	30086	1533
150	30001	310	30056	375	21537	441	21939	565	30063	665	21928	774	21505	820	21637	956	21926	1076	30311	1200	30312	1298	21927	1525	30310	1739
200	30096	333	30638	397	30061	461	21439	569	30057	672	20558	803	21506	879	20557	1024	20556	1076	30058	1200	30059	1298	21577	1525	30060	1739
250	30186	418	40235	479	21986	542	21341	679	21473	819	21475	963	21471	1085	21472	1232	21492	1373	21474	1520	24847	1669	26300	1794	27083	1939
300	30107	461	30804	530	30103	601	21343	753	30210	908	21339	1068	21957	1206	22898	1370	21166	1526	30101	1690	26051	1854	26052	1994	30160	2156
350	28881	503	40910	582	30209	660	21527	828	30211	997	30212	1174	21528	1328	24748	1507	24991	1678	21686	1859	41082	2039	40393	2194	30155	2373
400	40895	546	40911	634	30176	718	22357	903	21558	1087	30280	1279	25171	1449	24749	1644	21627	1831	30223	2028	30224	2224	41103	2395	22011	2591
450	30325	588	40912	685	26204	777	22483	978	24711	1176	30259	1384	29047	1571	21337	1782	21600	1984	29923	2197	41083	2409	28034	2595	28032	2808
500	30605	630	40913	737	30392	835	30273	1052	23150	1265	30366	1489	40976	1692	24297	1920	41013	2137	30196	2366	41084	2594	28035	2795	41119	3025

# All BFM fitting connectors comply with 3-A 60-64 Sanitary Fittings

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

## Teflex NP Black

PTFE laminate for temperature & chemical extremes



- Non-permeable PTFE laminate that can be used on products across the full pH scale, ie. caustic or acid products will not effect Teflex NP Black
- Capable of running at high and low temperatures
- Designed to dissipate electrical charge - 10<sup>6</sup>Ω

**Maximum Diameter:** 500mm  
**Maximum Length:** 1,000mm  
**Available with SS Rings?** Yes  
**Available with Plastic Rings?** No  
**Available as TR (Tool Release) option?** Yes

### PHYSICAL PROPERTIES:

Material	Pure PTFE
Weight (±10%)	459g/m <sup>2</sup> / 13.5oz/yd <sup>2</sup>
Operating Temp Range	-73 - 300°C / -99 - 572°F (surge to 316°C / 600°F)
Surface Resistivity (Ohms)	10 <sup>6</sup>

VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	FOOD SAFETY			ATEX

\* Expect shorter life-span if used #All BFM® fitting connectors comply with 3-A 60-64 Sanitary Fittings

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm	
LENGTH: (mm)	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
80	41175	251	41176	270	29938	338	29859	449	29858	532	29631	602	41296	667	29820	690	41297	753	41313	834
100	40873	251	41060	270	29093	338	29041	449	29043	532	29042	602	29787	667	29531	690	29532	753	29816	834
150	41042	279	41061	338	29106	370	29124	462	29133	548	29087	618	29788	738	29506	860	41298	968	29844	1080
200	41043	299	41062	357	29108	386	28819	472	29135	559	28718	651	29552	791	29501	921	29510	968	40152	1080
250	41044	376	41063	431	29127	452	29071	636	29137	750	29147	848	29927	977	29489	1109	29760	1235	41314	1368
300	41045	415	41064	478	29129	501	29078	669	29144	789	29080	930	29763	1086	29845	1233	41299	1373	41295	1521
350	41046	452	41065	524	41179	593	29629	745	41253	898	29800	1057	29910	1195	41282	1356	41300	1511	29924	1673
400	41047	491	41066	571	29601	646	29757	813	29936	978	40657	1151	40764	1304	41283	1480	41301	1648	29925	1825
450	41048	529	41067	617	29602	699	29535	880	40188	1058	40658	1246	40765	1413	29511	1604	40337	1785	29926	1977
500	41049	567	41068	663	40174	752	29852	947	29630	1138	29930	1341	41271	1523	29513	1727	41302	1923	41315	2129
550	41050	605	41069	710	41180	805	41247	1014	29937	1218	41261	1435	41272	1632	41284	1851	41303	2061	41316	2281
600	41051	644	41070	757	41181	857	40269	1081	40232	1298	41262	1530	41273	1741	41285	1975	41304	2198	41317	2434
650	41052	682	41071	803	41241	910	41248	1148	41254	1379	41263	1625	41274	1850	41286	2099	41305	2335	41318	2586
700	41053	720	41072	849	41242	962	41249	1216	41255	1459	41264	1719	41276	1959	41287	2222	41306	2473	41319	2738
750	41054	759	41073	896	41243	1015	41250	1283	41256	1539	41265	1814	41277	2068	41288	2346	41307	2611	41320	2890
800	41055	796	41074	942	40355	1067	40872	1350	41257	1620	41266	1909	41278	2177	41289	2470	41308	2748	41321	3042
850	41056	835	41075	989	41244	1120	41251	1417	41258	1700	41267	2003	41279	2286	41290	2593	41309	2885	41322	3195
900	41057	873	41076	1036	41245	1172	40663	1484	41259	1780	41268	2099	41280	2396	41291	2717	41310	3023	41323	3347
950	41058	911	41077	1082	41246	1225	41252	1552	41260	1860	41269	2193	41281	2505	41292	2841	41311	3160	41324	3499
1000	41059	949	41078	1128	29972	1278	40346	1618	40133	1940	40343	2288	41293	2614	41294	2964	41312	3298	41325	3651



The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.



## Teflex NP Opaque

Semi-transparent PTFE laminate for temperature & chemical extremes



- Non-permeable PTFE laminate that can be used on products across the full pH scale, ie. caustic or acid products will not effect Teflex NP Opaque
- Capable of running at high and low temperatures
- Semi-transparent to allow product-flow visibility

**Maximum Diameter:** 500mm  
**Maximum Length:** 1,000mm  
**Available with SS Rings?** Yes  
**Available with Plastic Rings?** No  
**Available as TR (Tool Release) option?** Yes

### PHYSICAL PROPERTIES:

Material	Pure PTFE
Weight (±10%)	459g/m <sup>2</sup> / 13.5oz/yd <sup>2</sup>
Operating Temp Range	-73 - 300°C / -99 - 572°F (surge to 316°C / 600°F)
Surface Resistivity (Ohms)	Insulative

VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	FOOD SAFETY	ATEX
-----------	-------------	-------------	------------	-------------	------

\* Expect shorter life-span if used #All BFM<sup>®</sup> fitting connectors comply with 3-A 60-64 Sanitary Fittings

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm	
LENGTH: (mm)	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
80	41177	251	41178	270	29900	338	40250	449	41356	532	40247	602	40252	667	41396	690	41412	753	40749	834
100	41137	251	41156	270	40649	338	29934	449	29687	532	40256	602	40248	667	40630	690	41413	753	40251	834
150	41138	279	41157	338	29861	370	29933	462	29943	548	40246	618	41381	738	40661	860	41414	968	41430	1080
200	41139	299	41158	357	40249	386	29905	472	40270	559	29751	651	40245	791	40852	921	29963	968	41431	1080
250	41140	376	41159	431	40639	452	29866	636	41357	750	29850	848	41009	977	41397	1109	29907	1235	40638	1368
300	41141	415	41160	478	29929	501	29847	669	29848	789	29849	930	29906	1086	29846	1233	41415	1373	41432	1521
350	41142	452	41161	524	41328	593	41343	745	41007	898	41008	1057	41382	1195	41398	1356	41416	1511	41433	1673
400	41143	491	41162	571	29904	646	40746	813	41358	978	40832	1151	41383	1304	41399	1480	41417	1648	41434	1825
450	41144	529	41163	617	41329	699	41344	880	41359	1058	41370	1246	41384	1413	41400	1604	41418	1785	41435	1977
500	41145	567	41164	663	41330	752	40874	947	41360	1138	41371	1341	41385	1523	41401	1727	41419	1923	41436	2129
550	41146	605	41165	710	41331	805	41345	1014	41361	1218	41372	1435	41386	1632	41402	1851	41420	2061	41437	2281
600	41147	644	41166	757	41332	857	41346	1081	41362	1298	40888	1530	41387	1741	41403	1975	41421	2198	41438	2434
650	41148	682	41167	803	41333	910	41347	1148	41363	1379	41373	1625	41388	1850	41404	2099	41422	2335	41439	2586
700	41149	720	41168	849	41334	962	41348	1216	41364	1459	41374	1719	41389	1959	41405	2222	41423	2473	41440	2738
750	41150	759	41169	896	41335	1015	41349	1283	41365	1539	41375	1814	41390	2068	41406	2346	41424	2611	41441	2890
800	41151	796	41170	942	41336	1067	40875	1350	41366	1620	41376	1909	41391	2177	41407	2470	41425	2748	41442	3042
850	41152	835	41171	989	41337	1120	41352	1417	41367	1700	41377	2003	41392	2286	41408	2593	41426	2885	41443	3195
900	41153	873	41172	1036	41338	1172	41353	1484	41368	1780	41378	2099	41393	2396	41409	2717	41427	3023	41444	3347
950	41154	911	41173	1082	41339	1225	41354	1552	41369	1860	41379	2193	41394	2505	41410	2841	41428	3160	41445	3499
1000	41155	949	41174	1128	41342	1278	41355	1618	40351	1940	41380	2288	41395	2614	41411	2964	41429	3298	41446	3651

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

## LM3

100% Woven polypropylene - breathable & suitable for low temperatures




- Ideal for low temperature environments (down to -70°C/-94°F)
- Perfect for food processing, especially when some breathability is required to alleviate pressure.

### PHYSICAL PROPERTIES:

Material	100% woven polypropylene	
Weight (±10%)	295g/m <sup>2</sup> / 8.7oz/yd <sup>2</sup>	
Operating Temp. Range	-70 to 94°C / -94 to 201°F (surge to 107°C / 225°F)	
Air Permeability	(cm <sup>3</sup> /cm <sup>2</sup> /sec@125Pa)	(ft <sup>3</sup> /ft <sup>2</sup> /min@0.5" wg)
	13	25

**Maximum Diameter:** 1,650mm  
**Maximum Length (≤ Ø650mm):** 1,500mm  
**Available with SS Rings?** Yes (≤ Ø500mm)  
**Available with Plastic Rings?** Yes  
**Available as TR (Tool Release) option?** Yes (≤ Ø650mm)



#All BFM® fitting connectors comply with 3-A 60-64 Sanitary Fittings

Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
80	50671	75	51087	78	50768	82	50670	92	50709	101	50623	106	51206	120	51227	129	51248	144	51274	166	51298	178	51327	188	51355	199
100	50602	75	50522	78	50539	82	50520	92	50540	101	50541	106	50542	120	50543	129	50544	144	50603	166	50647	178	51328	188	50707	199
150	50628	77	50672	79	50521	83	50546	93	50665	101	50622	112	51207	122	50669	131	51619	144	50604	168	51299	179	50777	191	51356	202
200	50701	88	51088	90	25277	95	50519	95	50532	103	50552	117	50715	125	50553	139	50783	150	50605	173	51300	185	51329	196	51357	209
250	50710	91	51089	95	50594	99	50626	113	50627	127	50625	137	50789	151	50711	175	51249	194	50780	215	51301	260	51330	273	51358	285
300	30751	95	50751	98	26870	103	26871	118	25275	132	50644	143	50645	158	51476	182	51250	202	50613	223	51302	268	51331	282	51359	295
350	51066	98	51090	103	51139	108	50641	123	25276	138	50723	149	50747	164	51753	189	51251	209	51275	231	51303	275	51332	290	51360	304
400	51067	102	50750	107	50722	113	50759	128	50754	143	25296	156	50767	171	51228	197	51252	217	26701	240	51304	284	51333	299	51361	313
450	50525	106	50752	111	50535	117	50736	133	50746	149	26837	162	51057	178	26838	203	51253	224	51276	248	51305	291	50656	307	51362	322
500	50526	109	51091	115	50634	122	50635	137	26921	154	26923	168	51208	185	51754	211	51254	232	51277	256	51306	299	51334	315	51363	331
550	51068	113	51092	120	51140	127	51154	142	51171	159	51188	175	51209	192	51229	218	51255	239	51278	265	51307	307	51335	324	51364	341
600	51138	117	51093	123	50776	131	50774	147	50708	165	50652	181	50787	198	51230	226	51256	246	51279	273	51308	314	51336	332	51365	350
650	51069	120	51094	128	51141	136	51155	152	51172	171	51189	187	51210	205	51231	232	51257	254	51280	282	51309	322	51337	340	51366	359
700	51070	124	51095	132	51142	140	50779	158	51173	176	51190	193	51211	212	51232	240	51258	261	51281	290	51310	330	51338	349	51367	368
750	51071	127	51096	137	51143	146	51156	163	51174	181	51191	200	51212	219	50705	247	50706	269	51282	298	51311	338	51339	357	51368	377
800	51072	131	51097	140	51755	150	50775	167	50712	187	51192	206	51213	226	51233	255	51259	277	51283	307	51312	346	51340	366	51369	386
850	51073	135	51098	145	51144	154	51157	172	51175	192	51193	212	51214	232	51234	261	51260	284	51284	315	51313	353	51341	374	51370	396
900	51074	139	51099	149	51145	159	51158	177	51176	198	51194	219	51752	239	51235	268	51261	292	51285	323	51314	361	51342	382	51371	405
950	51075	142	51100	153	51146	164	51159	182	51177	203	51195	225	51215	246	51236	276	51262	299	51286	331	51315	369	51343	391	51372	414
1000	51076	146	51101	158	51487	168	51160	187	26922	209	50655	231	51216	253	51237	283	51263	307	51287	340	51316	377	51344	399	51373	423

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.



## LM4

100% woven Polyester - suitable for higher temperatures




- Used for higher temperature environments (up to 130°C / 266°F).
- Ideal for use where air needs to be vented through the walls of the flexible connector.

### PHYSICAL PROPERTIES:

Material	100% woven polyester fibre	
Weight (±10%)	393g/m <sup>2</sup> / 11.6oz/yd <sup>2</sup>	
Operating Temp Range	-40 - 130°C / -40 - 266°F (surge to 150°C / 302°F)	
Air Permeability	(cm <sup>3</sup> /cm <sup>2</sup> /sec@125Pa)	(ft <sup>3</sup> /ft <sup>2</sup> /min@0.5" wg)
	0.4	0.8

Maximum Diameter:	1,650mm
Maximum Length (≤ Ø650mm):	1,500mm
Available with SS Rings?	Yes (≤ Ø500mm)
Available with Plastic Rings?*	Yes
Available as TR (Tool Release) option?	Yes (≤ Ø650mm)

\*to Max. Operating Temp of 110°C / 230° F



#All BFM<sup>®</sup> fitting connectors comply with 3-A 60-64 Sanitary Fittings

Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
80	26101	75	41664	78	50506	83	26344	92	50507	101	26239	106	29840	120	26262	129	21453	144	26305	166	41665	178	41666	188	41667	199
100	20900	75	51000	78	20901	83	20902	92	20903	101	20904	106	20905	120	20906	129	20907	144	20908	166	20909	178	20910	188	20911	199
150	20509	77	51001	79	19569	82	50009	93	50014	101	50015	112	50406	122	22089	131	50424	144	50425	168	50426	179	50427	191	50428	202
200	20912	88	51002	90	21847	95	19399	95	20510	103	20511	117	20512	125	20483	139	20513	150	20514	173	20515	185	20516	196	20517	209
250	25238	91	50140	95	21987	99	21477	113	21614	127	21812	137	22897	151	21622	175	22927	194	26531	215	40791	260	24391	273	28822	285
300	20914	95	50137	98	20915	103	20916	118	21924	132	20918	143	20919	158	20920	182	20921	202	20922	223	20923	268	20924	282	20925	295
350	25595	98	23146	103	21883	108	22367	123	50004	138	22852	149	20314	164	26532	189	50523	209	26533	231	29965	275	41226	290	41233	304
400	20926	102	28689	107	20927	113	20928	128	20929	143	20650	156	20931	171	20932	197	20933	217	20934	240	20935	284	20936	299	20937	313
450	26254	106	29187	111	22366	117	22800	133	50404	149	50405	162	50407	178	50499	203	29589	224	28349	248	50501	291	26567	307	24486	322
500	22758	109	23206	115	20939	122	22208	137	20941	154	20942	168	20943	185	24296	211	20945	232	25410	256	20947	299	20948	315	20949	331
550	26381	113	41192	120	28688	127	26243	142	41201	159	29564	175	24809	192	41207	218	41209	239	41213	265	41219	307	41227	324	41234	341
600	20956	117	28431	123	20957	131	20958	147	20959	165	20960	181	20961	198	20962	226	20963	246	20964	273	20965	314	20966	332	20967	350
650	26141	120	41193	128	26087	136	25862	152	28716	171	23017	187	41206	205	22376	232	41210	254	41214	282	41220	322	41228	340	23199	359
700	41188	124	41194	132	50013	140	22132	158	22131	176	25669	193	23228	212	41208	240	29585	261	21355	290	41221	330	41229	349	41235	368
750	26346	127	50619	137	41197	146	24951	163	23051	181	22965	200	40237	219	25642	247	24955	269	21754	298	41222	338	41230	357	41236	377
800	20968	131	25560	140	50673	150	20970	167	20971	187	21903	206	20973	226	20974	255	20975	277	41215	307	20977	346	20978	366	20979	386
850	41189	135	25561	145	41198	154	22163	172	41202	192	41204	212	24833	232	24835	261	25111	284	41216	315	41223	353	41231	374	41237	396
900	41190	139	41195	149	41199	159	22162	177	24283	198	21901	219	24834	239	22395	268	41211	292	41217	323	41224	361	22982	382	41238	405
950	41191	142	41196	153	41200	164	25966	182	41203	203	41205	225	40111	246	24836	276	41212	299	41218	331	41225	369	41232	391	41239	414
1000	20980	146	25607	158	20981	168	21878	187	20983	209	20985	231	26215	253	20986	283	20987	307	20988	340	20989	377	20990	399	20991	423

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

## FM1 Breather

Woven polyester breather bag for venting contained vessels




- Designed for breathing applications such as venting hoppers and other contained vessels
- The BFM® breather may become required as the BFM® connectors create a 100% sealed system.

### PHYSICAL PROPERTIES:

Material	100% woven polyester needlefelt	
Weight (±10%)	550g/m <sup>2</sup> / 16.22oz/yd <sup>2</sup>	
Operating Temp Range	-20 - 130°C / -4 - 266°F (surge to 150°C / 302°F)	
Air Permeability	(cm <sup>3</sup> /cm <sup>2</sup> /sec@125Pa)	(ft <sup>3</sup> /ft <sup>2</sup> /min@0.5" wg)
	17	33

Maximum Diameter:	650mm
Maximum Length (≤ Ø650mm):	1,000mm
Available with SS Rings?	No
Available with Plastic Rings?	No
Available as TR (Tool Release) option?	Yes



# All BFM® fitting connectors comply with 3-A 60-64 Sanitary Fittings

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
100	30544	100	30711	103	30553	106	30562	111	30546	116	30612	126	30807	131	31234	170	30608	199	30654	248	31421	304	31422	321	31424	341
150	30534	100	30668	103	30566	108	30590	112	30716	116	30635	126	30632	132	31235	172	30669	199	31254	250	31426	309	31441	326	31455	345
200	30528	100	30533	103	30569	108	30530	112	30602	117	30629	126	30630	133	30572	174	30689	200	31255	253	31427	313	31167	330	31456	350
250	30540	100	30576	104	30586	109	30601	117	30588	119	30607	127	31229	134	31236	180	31243	200	30805	256	31428	318	31442	335	31457	355
300	30517	101	30525	105	30258	111	30334	117	30545	119	30615	127	30631	136	30604	185	31244	201	30532	256	31429	322	31443	339	31458	359
350	30661	106	30625	106	30600	111	30535	118	30624	123	30637	127	31207	137	31237	186	31245	202	31256	263	31430	326	31444	343	31459	364
400	30589	108	30702	108	30542	112	30567	118	30537	124	30551	127	31022	138	31238	188	30955	202	31201	269	31431	331	31445	348	31460	369
450	30568	108	30666	117	30585	123	30656	130	30791	147	31206	152	31004	160	31239	200	30593	207	31257	276	31432	335	31446	352	31461	374
500	30515	122	30640	125	30548	129	30539	131	30513	147	30557	155	30667	164	30559	205	30598	215	30597	282	31433	340	31447	357	31462	378
550	31200	123	31214	127	30616	132	30606	141	30963	147	30937	157	31230	164	30704	214	31246	216	30623	288	31434	344	31448	361	31463	383
600	30571	123	30854	132	30583	132	30580	141	30541	147	30717	157	30985	164	31240	214	31247	217	30840	292	31435	348	30543	365	31464	387
650	30718	123	31215	132	30610	132	30662	141	30783	147	30619	158	31231	165	31241	215	31248	217	31258	296	31436	353	31449	370	31465	392
700	32190	127	31216	132	30878	132	30688	151	30660	151	30646	159	30956	166	31242	216	32110	219	30671	299	30577	357	31450	374	31466	397
750	30757	133	31217	133	30621	133	30645	151	30524	151	30676	161	31232	171	30850	217	31249	229	31259	303	30574	362	31451	379	31467	402
800	30613	133	31218	133	30614	133	30563	152	30633	153	30558	161	30971	173	30560	219	31250	239	31260	306	31437	366	30651	383	31468	406
850	31210	137	31219	153	30611	153	31222	159	31224	160	31227	175	31182	186	31183	226	31251	249	31261	310	31438	370	31452	387	31469	411
900	31211	140	31220	155	30581	173	30659	173	31225	175	32116	187	31181	198	30808	230	32109	260	31262	313	31439	375	31453	392	31470	416
950	31212	143	31221	158	31180	173	31223	174	31226	176	31228	188	31233	198	31190	236	31252	270	31263	316	31440	381	31454	396	31296	419
1000	32091	146	30674	159	30675	173	30617	175	30564	177	30626	189	30591	199	30677	241	31253	280	30650	319	30516	385	31423	400	31289	423

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of an FM1 Breather Bag, please refer to the 'Add-ons' page 6.

## Blanking Cap (Seeflex 040E)

Prevents contamination/used as sight-glasses




- Used to prevent contamination during clean down or change-over.
- They protect products and prevent dust emission into the factory.
- Ideal as sight-glasses for sifters, and other equipment.

**Maximum Diameter:** 1,650mm  
**Available as TR (Tool Release) option?** Yes (≤ 650mm)

### PHYSICAL PROPERTIES:

Material	Ether-based thermoplastic polyurethane alloy
Wall Thickness (±10%)	0.9mm / 1/32 inch
Operating Temp Range	-25 to 110°C / -13 to 230°F (surge to 120°C to 248°F)
Height (Length)	30mm (1 1/16")



DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm	
	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
	20750	86	20761	89	20751	92	20752	99	20709	107	20753	122	20754	142	20755	168	20756	180	20757	218	20758	270

DIA:	Ø600mm		Ø650mm		Ø700mm		Ø750mm		Ø800mm		Ø850mm		Ø900mm		Ø950mm		Ø1,000mm		Ø1,050mm		Ø1,100mm	
	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
	20759	292	20760	307	21865	530	22868	541	21476	545	25086	554	28285	570	60013	591	21866	714	24667	769	21867	784

DIA:	Ø1,150mm		Ø1,200mm		Ø1,250mm		Ø1,300mm		Ø1,350mm		Ø1,400mm		Ø1,450mm		Ø1,500mm		Ø1,550mm		Ø1,600mm		Ø1,650mm	
	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
	22382	838	25197	874	22345	917	29391	978	26468	1023	40402	1067	24668	1109	24576	1257	40403	1308	26743	1358	28202	1415



The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a Tool Release version of a Blanking Cap, please refer to the 'Add-ons' page 6.

## Blanking Bin (Seeflex 040E)

Ideal for sifter oversize collection bins




- Used for collecting overs/reject product on sifters/sieves etc.
- Can be lined with plastic bags for easy disposal of reject product.
- Allows for visibility of product full level and reject consistency.

### PHYSICAL PROPERTIES:

Material	Seeflex ether-based thermoplastic polyurethane
Wall Thickness (±10%)	0.9mm / 1/32 inch
Operating Temp Range	-25 to 110°C / -13 to 230°F (surge to 120°C to 248°F)
Height (Length)	30mm (1 1/16")

Maximum Diameter:	1,650mm
Maximum Length:	1,000mm
Available with SS Rings:	Yes (≤ Ø500mm)
Available with Plastic Rings:	No
Available as TR (Tool Release) option?	Yes (≤ Ø650mm)



DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
100	25117	137	29059	147	22733	161	24323	168	22732	185	24437	214	25868	226	26258	292	27033	331	26129	382	29568	421	27032	462	40397	503
150	22851	140	21852	151	25630	166	21709	175	28216	194	21589	225	26194	240	28011	306	24451	346	40474	399	40487	439	40504	482	40521	524
200	21576	144	23022	155	22744	171	24360	183	25350	204	22546	236	26193	253	26709	319	40461	361	29222	415	25870	457	40505	501	40522	545
250	24779	146	22352	159	21309	175	25379	190	24450	214	23039	248	28226	267	40444	333	40462	376	40476	432	40489	476	40506	520	40523	566
300	21967	149	22161	163	21458	180	22878	197	26319	223	25869	259	25842	281	27125	347	50510	391	26624	449	40490	494	40507	540	40524	587
350	21170	152	21804	167	24774	185	60020	205	26176	233	40434	271	25843	295	40445	361	40464	406	40477	465	40491	512	40508	559	40525	608
400	21520	156	22353	171	24638	190	21171	212	23207	243	28530	282	25241	309	29004	375	21908	421	24531	482	40492	530	40509	579	40526	629
450	22946	159	26467	175	22742	195	22231	220	26454	253	22042	294	26200	323	24464	389	28942	437	40479	498	40493	548	40510	599	40527	650
500	22716	162	22212	179	22528	200	21791	227	22885	262	25199	305	25844	336	24938	403	26334	452	28874	515	40494	566	40511	618	40528	672
550	22717	165	40423	183	24755	205	26598	234	27052	272	26950	316	40438	350	40455	416	40467	467	40480	532	40495	585	40512	638	40529	692
600	60012	168	24563	187	24306	209	22088	242	22530	282	22087	328	22487	364	24939	430	40468	482	28332	548	40496	603	40513	657	40530	713
650	26789	171	26798	191	24777	214	24456	249	40432	292	28702	339	40439	378	26337	444	40469	498	40481	565	40497	621	40514	677	40531	735
700	40415	174	26478	195	60017	219	22760	257	25210	301	28068	351	24727	392	25388	457	40470	513	40482	581	40498	639	40515	696	40532	755
750	27126	177	40427	199	25327	224	28514	265	21719	311	28151	362	40440	406	40457	471	24970	528	28072	598	40499	658	40516	716	40533	776
800	25425	180	29198	203	22759	229	22787	272	23156	321	24346	374	26540	420	25394	485	40472	543	40483	615	40500	676	40517	735	40534	798
850	25753	183	40428	207	29600	234	22756	279	29039	331	40435	385	40441	433	24776	499	40473	558	40484	631	40501	694	40518	755	40535	818
900	40417	186	40429	211	25663	238	26014	287	26013	340	25692	396	25780	447	40459	513	25186	573	40485	648	40502	713	40519	774	40536	839
950	40418	190	40430	215	29250	243	28446	294	24794	350	25727	408	40443	461	40460	527	29674	588	40486	665	40503	731	40520	793	40537	861
1000	60026	193	29038	219	60027	248	60028	302	25892	360	25057	420	40385	475	40389	541	28772	604	40391	681	40398	749	40406	813	40407	881

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a Tool Release version or to add Rings, please refer to the 'Add-ons' page 6.

## Kevlar Cover

Flame resistant cover to reduce the risk of consequential fires



- Typically used in over pressure and potentially explosive applications.
- Designed to fit over existing connectors and tightened onto the BFM<sup>®</sup> spigot using butterfly clamps.

**Maximum Diameter:** 1,650mm  
**Maximum Length:** 1,000mm  
**Available with SS Rings?** No  
**Available with Plastic Rings?** No

### PHYSICAL PROPERTIES:

<b>Material</b>	Woven Kevlar (Aramid) fibre
<b>Weight (±10%)</b>	447g/m <sup>2</sup> / 13.2oz/yd <sup>2</sup>
<b>Max. Operating Temp</b>	260°C / 500°F (surge to 300°C / 572°F) (NB: Limited to max. operating temperature of connector underneath)

VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	FOOD SAFETY	ATEX

\* Does not come in contact with product therefore can be used in conjunction with a 3A certified inner connector  
 Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
80	80273	295	80274	300	80049	304	80130	314	80137	326	80136	335	80135	339	80131	354	80327	375	80141	396	80345	416	80133	437	80134	459
100	80044	295	80123	300	80089	304	80022	314	80068	326	80030	335	80031	339	80098	354	80099	375	80041	396	80055	416	80122	437	80077	459
150	80026	303	80124	309	80025	316	80034	338	80086	351	80023	365	80011	379	80043	394	80085	420	80058	446	80162	472	80016	491	80079	518
200	80045	312	80109	320	80050	326	80002	338	80027	351	80003	365	80057	379	80029	394	80061	420	80004	446	80013	472	80028	491	80095	518
250	80145	322	80275	331	80108	338	80071	350	80090	367	80129	384	80180	401	80069	418	80174	445	80054	473	80175	501	80173	524	80176	553
300	80046	332	80246	343	80019	348	80018	363	80020	384	80021	403	80172	423	80103	442	80212	471	80116	500	80117	530	80118	555	80114	587
350	80263	341	80276	354	80210	360	80119	375	80226	401	80190	423	80177	444	80104	466	80239	497	80217	527	80346	558	80249	587	80231	622
400	80047	351	80277	365	80248	370	80084	387	80216	418	80150	442	80036	466	80017	490	80037	522	80009	554	80347	587	80359	619	80369	657
450	80264	360	80278	376	80289	382	80297	399	80148	434	80107	461	80208	488	80235	514	80328	548	80163	581	80348	616	80144	651	80214	692
500	80048	370	80279	387	80051	392	80052	412	80053	451	80311	480	80065	509	80066	538	80067	574	80243	609	80349	644	80170	683	80370	726
550	80265	380	80280	399	80186	404	80298	424	80300	467	80386	499	80230	531	80183	562	80329	600	80337	636	80350	673	80360	714	80371	762
600	80222	389	80281	410	80236	415	80229	437	80038	484	80205	518	80178	553	80070	586	80330	625	80338	663	80351	702	80361	747	80372	796
650	80266	399	80282	421	80290	426	80299	449	80302	501	80312	537	80211	575	80322	610	80331	651	80339	690	80352	731	80362	778	80223	831
700	80267	409	80283	432	80291	437	80221	461	80305	518	80313	557	80191	596	80152	634	80153	677	80340	716	80353	760	80363	810	80373	866
750	80268	418	80284	444	80292	448	80301	474	80306	535	80014	576	80097	618	80101	658	80332	702	80096	743	80354	789	80364	842	80374	901
800	80269	428	80285	455	80293	459	80181	486	80106	551	80314	595	80318	639	80323	682	80333	728	80341	770	80355	818	80365	874	80375	936
850	80270	437	80286	466	80294	470	80234	498	80307	568	80315	614	80319	661	80324	706	80334	753	80342	798	80356	846	80366	906	80376	970
900	80271	447	80287	478	80295	481	80303	510	80308	585	80316	633	80320	683	80325	730	80335	779	80343	825	80357	875	80367	937	80377	1005
950	80272	457	80288	488	80296	492	80304	523	80309	602	80317	653	80321	704	80326	754	80336	805	80344	852	80358	904	80368	970	80378	1040
1000	80252	466	80032	500	80253	503	80254	535	80128	618	80255	672	80256	726	80257	778	80258	830	80259	881	80260	933	80261	1002	80262	1075

The prices shown above indicate our Recommended Retail Prices (RRP).



## Black-out Cover

Designed for light sensitive applications, fits over our entire connector range.



- The cover cuts out all light and is for use in light sensitive areas
- Designed to fit over existing BFM® connectors.
- Easy to install and no tools are required.

**Maximum Diameter:** 1,650mm  
**Maximum Length:** 1,000mm  
**Available with SS Rings?** No  
**Available with Plastic Rings?** No

### PHYSICAL PROPERTIES:

<b>Material</b>	Polypropylene (wire used for the holders is 6mm 304 stainless steel)
<b>Weight (±10%)</b>	207 g/m <sup>2</sup> / 6.1 oz/yd <sup>2</sup>
<b>Max. Operating Temp</b>	95°C / 203°F

VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	FOOD SAFETY	ATEX

\* Does not come in contact with product therefore can be used in conjunction with a 3A certified inner connector

Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
80	60057	267	60214	272	60188	276	60184	285	60032	296	60034	304	60037	307	60311	321	60325	340	60189	358	60352	377	60078	396	60381	416
100	60108	267	60234	272	80245	276	60058	285	60033	296	60035	304	60038	307	60039	321	60061	340	60044	358	60074	377	60076	396	60060	416
150	60097	275	60235	280	60046	286	60056	307	60066	318	60036	331	60086	344	60040	357	60201	381	60065	404	60055	428	60219	445	60215	469
200	60220	284	60236	290	60182	296	60030	307	60031	318	60042	331	60048	344	60049	357	60102	381	60045	404	60202	428	60043	445	60187	469
250	60221	292	60237	301	60104	306	60105	318	60073	333	60068	348	60081	364	60064	379	60218	404	60067	430	60353	454	60367	474	60382	501
300	60080	301	60238	311	60178	316	60216	329	60089	348	60287	366	60213	383	60312	401	60099	427	60339	454	60354	480	60368	503	60383	533
350	60222	309	60239	321	60179	326	60262	340	60274	364	60209	383	60300	403	60106	423	60103	450	60340	479	60355	507	60075	532	60384	564
400	60223	318	60240	331	60180	336	60053	352	60275	379	60288	401	60072	423	60088	444	60326	473	60341	503	60356	532	60369	561	60385	596
450	60224	327	60241	341	60253	346	60263	362	60276	394	60289	418	60217	442	60313	466	60327	497	60342	528	60357	559	60370	590	60386	627
500	60183	336	60242	352	60490	356	60264	374	60098	409	60290	435	60181	462	60314	488	60328	520	60343	553	60191	585	60371	619	60493	659
550	60054	345	60243	362	60491	366	60265	385	60277	424	60291	453	60301	481	60315	510	60329	543	60344	577	60358	611	60372	648	60387	690
600	60225	353	60244	372	60254	376	60266	396	60278	439	60292	470	60302	501	60316	532	60330	566	60194	602	60192	637	60205	677	60193	722
650	60226	362	60245	382	60255	386	60267	407	60279	454	60293	488	60303	521	60317	553	60331	590	60345	626	60359	663	60373	706	60388	753
700	60227	370	60246	392	60256	396	60063	418	60280	470	60294	505	60304	541	60318	575	60332	612	60346	651	60360	689	60374	735	60389	786
750	60228	379	60247	403	60257	406	60268	430	60281	485	60295	522	60305	560	60319	597	60333	636	60203	676	60361	716	60375	764	60204	817
800	60229	388	60248	413	60258	416	60269	440	60282	500	60296	540	60306	580	60320	619	60334	659	60347	700	60362	742	60376	793	60391	849
850	60230	397	60249	423	60259	427	60270	452	60283	515	60297	557	60307	600	60321	641	60335	683	60348	725	60363	768	60377	822	60392	880
900	60231	406	60250	433	60260	437	60271	463	60284	530	60210	575	60308	619	60322	662	60336	706	60349	749	60364	794	60378	851	60393	912
950	60232	415	60251	443	60185	446	60272	474	60285	546	60298	592	60309	639	60323	684	60337	729	60350	774	60365	820	60379	879	60394	943
1000	60233	423	60252	453	60261	456	60273	485	60286	561	60299	609	60310	659	60324	706	60338	753	60351	801	60366	846	60380	908	60395	975

The prices shown above indicate our Recommended Retail Prices (RRP).

## Bulk Bag Loader

A three-layered, inflatable filling head featuring a stainless steel core fully encased in Seeflex ether-based urethane.



- Includes external air fitting that plugs into an 8mm pneumatic air line to inflate super strong & flexible outer layer.
- Top of loader simply snaps into a BFM® fitting spigot and features a fully encapsulated stainless steel ring to support lower end.
- All Bulk Bag Loaders are a standard length of 330mm.

### PHYSICAL PROPERTIES:

Material	Seeflex -Ether-based thermoplastic polyurethane with stainless steel core
Wall Thickness (±10%)	0.9mm / 1/32 inch
Operating Temp Range	-25 to 110°C / -13 to 230°F (surge to 120°C to 248°F)
Surface Resistivity(Ohms)	10 <sup>10</sup>

Maximum Diameter:	450mm
Available with SS Rings?	No
Available with Plastic Rings?	No



\* Material only

DIA:	Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm	
LENGTH: (mm)	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:	Part No:	RRP US\$:
330mm	305078	901	305075	936	304794	970	304793	1005	304791	1040	302363	1074	304828	1143



The prices shown above indicate our Recommended Retail Prices (RRP).

**BFM® GLOBAL LTD.** | To order BFM® fitting products, please contact your local Distributor - you can find them at [BFMfitting.com](http://BFMfitting.com)