


Spigots

- BFM® spigots are available in Stainless Steel T316L and T304L, as well as C22 Hastelloy.
- Available in a range of exact sizes, eliminating the imprecise nature of hose-clamp style connection widths and ensuring a perfect fit with the BFM® connector.
- All spigot diameters are measured at the base of the tail. The spigot design is slightly tapered, so the OD at the top of the tail is 5mm / 1³/₆₄" greater than the base
- BFM® spigots have a tail 52mm (2³/₆₄" long). These can be easily cut down or cut on an angle to suit your existing pipework (we recommend leaving at least 15mm (1¹/₂" on the tail).
- To enable the installation of a TR (Tool Release connector), a 6mm / 1⁵/₆₄" hole is drilled in the top seat of the spigot head.



PHYSICAL PROPERTIES:

Material	Stainless Steel T316L Stainless Steel T304L or C22 Hastelloy (limited sizes)
Interior Finish	≤ 0.8Ra micro-metres (32Ra micro-inches)
Wall Thickness	2.0mm / 5 ¹ / ₆₄ "
Length (for all diameters)	89mm / 3 1 ¹ / ₂ " (Head: 37mm / 1 1 ¹ / ₂ " (Tail: 52mm / 2 3 ³ / ₆₄ "

AVAILABLE SIZES: (In 50mm (2") increments)

Diameter	
Stainless Steel Spigots (also available in 125mm/5")	Ø100mm* - 1,650mm (Ø4" - 65")
Hastelloy Spigots	Ø150mm - 500mm (Ø5" - 19 1 ¹ / ₆₄ "

(* Ø100mm measured externally (OD) - all other diameters measured internally (ID). Note that there is a -1 / + 3mm tolerance on the tail diameter of all spigot sizes.)

Note: For applications where there is a possibility for static build up, e.g. wood dust, flour, milk powder etc., we recommend using a static dissipative wire (strip), connecting the two BFM® spigots together.