



Recommended Retail Price

The prices indicated in this document are our Recommended Retail Prices (RRP). There may be slight price variations in local markets.

These prices are based on a NZD/EUR exchange rate of 1 NZD:0.55 EUR. Exchange rates are reviewed at the end of each month. If there is a movement greater than 5% to this rate then the price list will be updated & uploaded by working day 5 of the following month. End of month rates are obtained from <https://www.reuters.com/markets/currencies>

BFM® STANDARD RANGE

Connectors • Caps • Covers • Spigots

Contents

Spigots01

Lipped Spigot 01

Seeflex 02

Seeflex 040E02

Seeflex 040AS03

Seeflex 020E04

Seeflex 060ES05

Add-Ons 06

TR (Tool Release)06

TR (Tool Release) Tools06

‘Smiley Face’ Hole Punch06

TR Lock-Out Safety System06

Quick Access Port07

Rings07

Flexi 08

Flexi / Flexi-Light08

Flexi-Earthed09

Teflex10

Teflex Woven 10

Teflex NP Black11

Teflex NP Opaque 12

LM3 13

LM4 14

FM1 Breather15

Blanking Cap (Seeflex 040E) 16

Blanking Bin (Seeflex 040E)17

Kevlar Cover..... 18

Black-out Cover 19

Bulk Bag Loader 20

Other Products21

Weighing Bellows 21

Venting Surge Hopper 21

Tapers 21

Corner Connector (040E & 060ES) 21

Spigots

Welds to your pipes to allow snap-in fitting of BFM® connectors



- Available in 304L SS and 316L SS (Hastelloy available on request)
- The spigot design is slightly tapered, so the OD at the top of the tail is 5mm / 13/64" greater than the base
- BFM® spigots are 89mm (3½") in total length - made up of a head of 37mm (1 29/64") and a 'tail' that is 52mm (2") long

PHYSICAL PROPERTIES:

Material	304L SS or 316L SS
Wall Thickness	2.0mm/ 5/64"

Note:

- The 'tail' of the spigot can be cut to tailor the perfect fit for your available space (ensure caution is used when welding not to distort spigot head).
- Download the BFM® IG (Installation Gap) Calculator App to ensure correct between spigots before welding or contact your BFM® Distributor for help.



DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
304LSS	20000	114	21287	115	20001	118	20002	128	20003	147	20004	164	20005	185	20006	209	20007	226	20008	262	20009	311	20010	341	20011	355
316LSS	20020	180	21288	184	20021	206	20022	227	20023	251	20024	286	20025	328	20026	370	20027	446	20028	466	20029	510	20030	523	20031	530

* Ø100mm measured externally (OD), all other Ø measured internally (ID).

DIA:	Ø700mm		Ø750mm		Ø800mm		Ø850mm		Ø900mm		Ø950mm		Ø1,000mm		Ø1,050mm		Ø1,100mm		Ø1,150mm		Ø1,200mm		Ø1,250mm		Ø1,300mm	
	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	RRP EUR:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
304LSS	20012	736	20013	831	20014	912	20015	1009	20016	1044	20017	1151	20018	1175	22222	1247	21203	1424	22815	1417	21161	1466	21434	1476	20019	1495
316LSS	20032	809	20033	879	20034	1179	20035	1297	20036	1388	20037	1399	20038	1423	22794	1519	21853	1611	22795	1623	21934	1665	25426	1753	60022	1843

DIA:	Ø1,350mm		Ø1,400mm		Ø1,450mm		Ø1,500mm		Ø1,550mm		Ø1,600mm		Ø1,650mm	
	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
304LSS	21435	1513	21436	1531	22223	1616	21125	1708	22802	1780	21012	2065	21121	2076
316LSS	25406	1940	25427	2021	25432	2133	22317	2253	25428	2351	25429	2449	22007	2740

Tool Release Holes: Spigots can be supplied with standard round tool-release holes pre-drilled or smiley-face tool release holes pre-punched for an additional fee of EU€28 per hole. **PLEASE NOTE:** These pre-drilled/punched TR spigots have different part numbers to those shown here.

Lipped Spigot

Allows easy integration with quick-connect, clamped modular tubing/piping systems

To enable a BFM® fitting system to be integrated with 'quick connect' modular tubing/piping, a range of our 304SS spigots are available with a 6mm rolled 'lip'. The lip of the spigot clamps in place with the corresponding modular lip using quick-release clamp systems like Jacob.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm	
	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
304LSS	20039	147	20040	149	20041	151	20042	161	20043	180	20044	197	20045	218	20046	242



NOTE: a BFM® Lipped Spigot has a 6mm shorter overall height/ length of 83mm.

The prices shown above indicate our Recommended Retail Prices (RRP) per spigot - to fit a standard BFM® connector as sealed, flexible connection, you will need two spigots (ie. one top, one bottom.)

Seeflex 040E

Strong, resilient, multi-purpose connector



- Used on all types of stationary, vibratory and gyratory sifters, screeners, feeders, bin discharges, hoppers, conveyors, any packing or product handling equipment.
- Superior wear resistance - used in CIP and washing.
- Available as a specially-marked “ Wash Sleeve “version (add EU€7 to price below).
- Available as Quick Access Port option

- Maximum Diameter: 1,650mm
Maximum Length (≤ Ø650mm): 6,000mm
Available with SS Rings? Yes (≤ Ø500mm)
Available with Plastic Rings? Yes
Available as TR (Tool Release) option? Yes (≤ Ø650mm)

PHYSICAL PROPERTIES:

Material	Ether-based thermoplastic polyurethane alloy
Wall Thickness (±10%)	0.9mm / 1/32 inch
Operating Temp Range	-25 to 110°C / -13 to 230°F (surge to 120°C to 248°F)
Surface Resistivity (Ohms)	10 ¹⁰

VIBRATION

OSCILLATION

COMPRESSION

DUST TIGHT

FOOD SAFETY

ATEX

Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
80	21871	80	22554	89	21756	92	21395	106	21259	122	21969	140	21984	155	22564	189	22566	208	22166	235	22569	244	22573	295	22413	312
100	20050	84	22000	94	20061	97	20072	112	20083	128	20094	147	20105	164	20116	199	20127	219	20138	239	20149	256	20160	311	20171	328
150	20051	87	22001	95	20062	104	20073	116	20084	133	20095	153	20106	171	20117	213	20128	231	20139	240	20150	267	20161	322	20172	342
200	20052	90	22002	101	20063	111	20074	122	20085	140	20096	161	20107	180	20118	218	20129	243	20140	252	20151	281	20162	339	20173	360
250	20053	102	22168	120	20064	125	20075	149	20086	174	20097	196	20108	228	20119	267	20130	308	20141	323	20152	361	20163	424	20174	450
300	20054	111	22247	133	20065	135	20076	161	20087	188	20098	216	20109	246	20120	289	20131	331	20142	347	20153	389	20164	459	20175	487
350	20055	116	22555	142	20066	145	20077	164	20088	219	20099	221	20110	255	20121	307	20132	338	20143	371	20154	395	20165	483	20176	531
400	20056	117	22071	146	20067	145	20078	164	20089	222	20100	222	20111	262	20122	307	20133	355	20144	372	20155	416	20166	485	20177	532
450	20057	128	22556	161	20068	158	20079	189	20090	231	20101	255	20112	282	20123	342	20134	379	20145	413	20156	444	20167	530	20178	566
500	20058	135	22003	162	20069	166	20080	199	20091	259	20102	269	20113	286	20124	360	20135	399	20146	435	20157	467	20168	558	20179	596
550	20059	145	22557	167	20070	171	20081	216	20092	265	20103	281	20114	301	20125	395	20136	447	20147	478	20158	515	20169	613	20180	652
600	20060	149	21386	168	20071	172	20082	216	20093	274	20104	285	20115	311	20126	424	20137	475	20148	513	20159	554	20170	653	20181	686
650	22552	152	22558	173	21385	184	21208	235	21955	275	21742	305	22562	322	22500	427	22567	477	22170	516	22572	559	22577	656	22578	701
700	21278	153	22559	174	21231	194	21569	245	21353	287	22280	306	22563	338	21405	429	22249	480	21262	521	22571	562	22576	658	22579	704
750	22553	155	22560	184	21794	195	21560	247	21691	288	22338	310	23005	367	22252	439	22568	505	22506	526	22570	592	22575	686	22580	727
800	20570	156	21387	197	20571	196	20572	248	20573	289	20574	326	20575	368	20576	444	20577	514	20578	529	20579	611	20580	688	20581	728
850	24431	186	25562	207	21675	233	21839	275	22874	321	24964	369	24496	376	24771	470	26756	553	26657	574	40695	669	40696	719	40697	774
900	24593	195	28310	216	21943	243	21257	288	21786	333	21282	384	23088	395	21956	493	24320	575	22748	602	40726	697	22803	750	40728	806
950	22855	204	40724	226	22326	254	21607	300	22169	346	22099	399	24424	415	29732	515	21561	598	40725	629	40727	725	26267	779	26453	838
1000	20590	211	21468	234	20591	265	20592	313	20593	358	20594	413	20595	436	20596	537	20597	622	20598	656	20599	753	20600	810	20601	870

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

Seeflex 040AS

Designed to dissipate static, ideal for potentially explosive areas



- Semi - transparent, 'anti-static' connector, designed to dissipate static
- Excellent abrasion, chemical and puncture resistance

PHYSICAL PROPERTIES:

Material	Ether-based thermoplastic polyurethane alloy with an anti-static infusion
Wall Thickness (±10%)	0.9mm / 1/32 inch
Operating Temp Range	-25 to 95°C / -13 to 203°F (surge to 100°C to 212°F)
Surface Resistivity (Ohms)	10 ⁸ (very good at dissipating static)

Maximum Diameter:	1,650mm
Maximum Length (≤ Ø650mm):	6,000mm
Available with SS Rings?	Yes (≤ Ø500mm)
Available with Plastic Rings?	Yes
Available as TR (Tool Release) option?	Yes (≤ Ø650mm)

					
VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	FOOD SAFETY	ATEX

Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
80	70082	99	70098	113	70114	120	70130	135	70146	154	70162	178	70178	197	70194	244	70210	268	70226	311	70242	318	70258	401	70274	408
100	70083	104	70099	119	70115	126	70131	142	70147	162	70163	187	70179	208	70195	256	70211	286	70227	320	70243	335	70259	404	70275	428
150	70084	105	70100	129	70116	140	70132	149	70148	173	70164	200	70180	222	70196	279	70212	310	70228	323	70244	360	70260	432	70276	459
200	70085	112	70101	129	70117	147	70133	154	70149	183	70165	211	70181	234	70197	289	70213	326	70229	340	70245	379	70261	455	70277	483
250	70086	118	70102	140	70118	152	70134	178	70150	211	70166	246	70182	251	70198	326	70214	378	70230	396	70246	447	70262	521	70278	556
300	70087	125	70103	142	70119	160	70135	187	70151	222	70167	259	70183	293	70199	342	70215	397	70231	417	70247	470	70263	548	70279	585
350	70088	130	70104	150	70120	169	70136	192	70152	267	70168	275	70184	304	70200	367	70216	411	70232	452	70248	485	70264	585	70280	625
400	70089	133	70105	174	70121	172	70137	193	70153	272	70169	286	70185	316	70201	368	70217	432	70233	452	70249	509	70265	587	70281	628
450	70090	147	70106	189	70122	191	70138	226	70154	306	70170	311	70186	348	70202	407	70218	455	70234	499	70250	539	70266	640	70282	686
500	70091	155	70107	201	70123	199	70139	238	70155	322	70171	327	70187	359	70203	428	70219	480	70235	525	70251	568	70267	674	70283	722
550	70092	169	70108	206	70124	206	70140	281	70156	338	70172	349	70188	414	70204	478	70220	540	70236	591	70252	639	70268	754	70284	805
600	70093	182	70109	208	70125	208	70141	282	70157	339	70173	354	70189	451	70205	512	70221	582	70237	649	70253	695	70269	804	70285	834
650	70094	182	70110	212	70126	227	70142	287	70158	340	70174	383	70190	459	70206	532	70222	587	70238	653	70254	700	70270	812	70286	862
700	70095	186	70111	217	70127	242	70143	293	70159	348	70175	398	70191	463	70207	538	70223	601	70239	688	70255	714	70271	829	70287	889
750	70096	188	70112	223	70128	247	70144	296	70160	351	70176	411	70192	466	70208	543	70224	613	70240	708	70256	729	70272	838	70288	899
800	70097	189	70113	235	70129	245	70145	298	70161	353	70177	414	70193	468	70209	545	70225	632	70241	727	70257	752	70273	840	70290	901
850	71021	222	70944	265	70389	279	70352	350	70933	408	71161	475	71162	529	71164	599	71165	704	71167	781	71169	850	71171	946	71173	1015
900	70805	231	71149	274	70392	290	70488	365	70291	426	71086	496	70587	552	71183	625	71186	730	71189	811	71192	882	71195	980	71198	1053
950	71177	240	71178	282	70505	301	70487	380	71179	444	71155	516	71180	575	71184	651	71187	757	71190	840	71193	914	71196	1015	71199	1090
1000	70795	248	70752	292	70533	312	70379	395	70303	461	70423	536	71182	598	71185	678	71188	784	71191	870	71194	947	71197	1049	71200	1128

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

Seeflex 020E

Lightweight & flexible, ideal for weighscale applications



- Transparent, light weight Seeflex media, specifically designed for load and weigh scale type equipment
- Also very good in applications with vertical movement as it is particularly flexible

PHYSICAL PROPERTIES:

Material	Ether-based thermoplastic polyurethane alloy
Wall Thickness (±10%)	0.35mm / 1/64 inch
Operating Temp Range	-25 to 80°C / -13 to 176°F (surge to 100°C to 212°F)
Surface Resistivity (Ohms)	10 ¹⁰

Maximum Diameter:	1,650mm
Maximum Length (≤ Ø650mm):	6,000mm
Available with SS Rings?	On request only
Available with Plastic Rings?	On request only
Available as TR (Tool Release) option?	Yes (≤ Ø650mm)

VIBRATION

OSCILLATION

COMPRESSION

DUST TIGHT

FOOD SAFETY

ATEX

Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
80	22155	80	22598	89	22610	92	22615	106	22360	122	21680	140	22622	155	22244	189	22646	208	22156	235	22672	244	22243	295	22699	312
100	20789	84	23000	94	20790	97	20791	112	20792	128	20793	147	21360	164	21361	199	21362	219	21363	239	21364	256	21365	311	21366	328
150	20690	87	23001	95	21222	104	21432	116	21317	133	21787	153	22623	171	22548	213	22647	231	22659	240	22673	267	22686	322	22700	342
200	21849	90	23002	101	21438	111	20692	122	20693	140	20694	161	21207	180	20695	218	20696	243	20697	252	20698	281	20699	339	20703	360
250	22425	102	22599	120	21781	125	21997	149	21613	174	21398	196	22624	228	22635	267	22648	308	22660	323	22674	361	22687	424	22701	450
300	21922	111	22342	133	21195	135	21837	161	21194	188	21384	216	22349	246	22636	289	22649	331	22661	347	22675	389	22688	459	22702	487
350	22590	116	22600	142	21882	145	21838	164	21774	219	21408	221	22625	255	22637	318	22650	338	22662	371	22676	395	22689	483	22703	531
400	22491	117	22601	146	21415	145	21308	164	21307	222	21784	222	22626	262	21806	307	22651	355	22063	372	22677	416	22690	485	22704	532
450	22591	128	22602	161	22492	158	22616	189	22316	231	22620	255	22627	282	22638	342	22652	379	22663	413	22678	444	22691	530	22705	566
500	23004	135	22603	162	22216	166	21303	199	21726	259	21915	269	22628	286	22639	360	22653	399	22664	435	22679	467	22692	558	22706	596
550	22592	145	22604	167	22611	171	21321	216	22445	265	21827	281	22629	301	22640	395	21913	447	22665	478	22680	515	22693	613	22707	652
600	22593	149	22605	168	21941	172	22040	216	22499	274	22621	285	22630	311	22641	424	22654	475	22666	513	22681	554	22694	653	22708	686
650	22594	152	22606	173	21369	184	22336	235	22618	275	21591	305	22631	322	22642	427	22655	477	22667	516	22682	559	22695	656	22709	701
700	22595	153	22607	174	22612	194	22104	245	22619	287	21636	306	22632	338	22643	429	22656	480	22668	521	22683	562	22696	658	22710	704
750	22596	155	22608	184	22613	195	22617	247	22150	288	21624	310	22633	367	22644	439	22657	505	22669	526	22684	592	22697	686	22711	727
800	22597	156	22609	197	22614	196	21714	248	22142	289	21189	326	22634	368	22645	444	22658	514	22670	529	22685	611	22698	688	22712	728
850	29178	186	41568	207	29459	233	24342	275	22315	321	23059	369	24837	376	24839	470	41573	553	26658	574	41581	669	41585	719	41588	774
900	41566	195	41569	216	22077	243	23154	288	23167	333	23168	384	24838	395	24840	493	41574	575	41578	602	41582	697	41586	750	41589	806
950	41567	204	41570	226	24767	254	22034	300	21699	346	40701	399	41571	415	24841	515	41575	598	41579	629	41583	725	41587	779	41590	838
1000	27031	211	26569	234	40148	265	21448	313	21631	358	21592	413	41572	436	41577	537	41576	622	41580	656	41584	753	22058	810	41591	870

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

Seeflex 060ES

Superior strength for over-pressure situations



- Pressure-resistant Seeflex 060ES is a semi-transparent connector with an internal polyester scrim
- The internally bonded scrim restricts the Seeflex sleeve from stretching
- For over-pressure situations for continuous pressure up to 1.7 bar

PHYSICAL PROPERTIES:

Material	Seeflex - Ether-based thermoplastic polyurethane alloy with internally bonded polyester scrim
Wall Thickness (±10%)	1.3mm / 1/16 inch
Operating Temp Range:	-25 - 120°C / -13 - 248°F (surge to 140°C / 284°F)

Maximum Diameter:	1,650mm
Maximum Length:	1,000mm
Available with SS Rings?	No
Available with Plastic Rings?	No
Available as TR (Tool Release) option?	Yes (≤ Ø650mm)

VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	FOOD SAFETY	ATEX

* Longer lengths only

Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
80	30763	150	30764	164	30856	180	30869	202	30929	229	30779	262	30780	287	30912	322	30930	350	31109	361	31121	389	31136	446	31151	472
100	30782	150	30806	164	30776	180	30760	202	30748	229	30731	262	30739	287	30836	322	30767	350	30827	361	30837	389	30925	446	31029	472
150	30773	158	30753	173	30746	191	30761	215	30762	244	30769	278	30727	305	30730	343	30790	373	30891	386	30832	416	31137	475	30890	504
200	30788	167	30908	183	30726	201	30729	227	30740	259	30771	295	30766	324	30770	364	30768	396	30732	411	30797	444	30794	504	30755	535
250	30887	174	31045	193	30777	211	30778	240	30818	274	30723	311	30867	343	30781	385	30951	419	30972	436	31122	471	30858	534	31152	567
300	30789	183	30988	201	30803	221	30831	252	30785	288	30819	327	30826	362	30888	405	31096	442	30855	461	30962	498	31138	563	31153	598
350	30933	191	31046	211	31057	232	30843	265	30821	303	30889	344	30913	381	30986	426	31097	465	30859	486	31123	525	30866	592	31154	629
400	30934	199	31047	220	31058	242	30845	277	31065	317	30744	361	30765	400	31086	448	31098	488	31110	512	31124	552	31139	621	31155	660
450	30935	207	30970	230	30917	252	30943	289	30820	332	31073	377	30846	419	30939	469	31099	511	30896	536	31125	579	31140	651	31156	692
500	31038	216	31048	239	31012	263	30942	301	30754	347	30931	394	31079	437	31087	489	31100	534	31111	562	31126	607	31141	680	31157	723
550	30857	223	31049	249	30906	273	31060	314	30863	361	30798	411	30904	457	30745	510	31101	557	31112	587	31127	633	31142	708	31158	754
600	30851	232	30910	257	30997	284	30811	326	30828	376	30796	427	30886	475	31088	531	30737	580	31113	612	31128	660	31143	739	31159	786
650	31039	240	31050	267	30918	294	30909	338	31066	390	31074	444	30847	494	31089	552	31102	603	31114	637	31129	688	31144	767	31160	817
700	31040	249	31051	277	30919	304	31061	351	31067	404	31075	460	31080	513	31090	573	31103	626	31115	662	31130	714	31145	797	31161	848
750	31041	256	31052	287	31059	315	31062	363	31068	419	31076	476	31081	532	31091	593	31104	650	31116	688	31131	741	31146	826	31162	880
800	31042	265	31053	295	30860	325	30873	376	31069	434	30932	494	31082	551	31092	614	31105	672	31117	713	31132	769	31147	856	31163	911
850	30861	273	31054	305	30959	336	31063	388	31070	449	31077	510	31083	569	31093	635	31106	695	31118	738	31133	796	31148	885	31164	943
900	31043	281	31055	314	30981	346	30998	401	31071	463	30905	526	31084	589	31094	656	31107	718	31119	763	31134	823	31149	914	31165	974
950	31044	289	31056	323	30944	356	31064	413	31072	477	31078	543	31085	608	31095	677	31108	741	31120	788	31135	850	31150	944	31166	1005
1000	31030	298	31032	333	30772	366	30795	426	30877	493	30949	559	31033	626	31034	698	31035	765	31036	813	31037	877	31028	972	31027	1036

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

TR (Tool Release)

As an added safety option, all BFM® fitting connectors are available in a TR (Tool Release) version which have a firmer snap-band that is virtually impossible to remove by hand. To calculate the price of a TR version of a connector, **simply add the following to the RRP of the standard connector price (based on the Diameter):**

Maximum possible diameter for TR is Ø650mm


DIA:	Ø100mm	Ø125mm	Ø150mm	Ø200mm	Ø250mm	Ø300mm	Ø350mm	Ø400mm	Ø450mm	Ø500mm	Ø550mm	Ø600mm	Ø650mm
	RRPEUR:	RRPEUR:	RRPEUR:	RRPEUR:	RRPEUR:	RRPEUR:	RRPEUR:	RRPEUR:	RRPEUR:	RRPEUR:	RRPEUR:	RRPEUR:	RRPEUR:
Surcharge on standard Connector	14	14	16	19	20	23	25	29	56	57	61	63	67

Please Note: The TR version of a BFM® fitting connector has a different part number to the standard version.

TR (Tool Release) Tools

To remove the TR Connectors, a special BFM® 'TR Tool' is required. Our standard TR Tool option features a rounded end tool and only requires the spigot to have a 6mm hole drilled in the outer most ridge. The 'Smiley Face' tool has an additional level of safety as it is used with a specially shaped hole (see adjacent information).

	Part No:	RRPEUR:
Standard TR Tool	304990	48
Smiley Face TR Tool	304991	48



'Smiley Face' Hole Punch

For additional security, and to avoid staff improvising tools to remove connectors, our 'Smiley Face' Tool Release option is a popular choice. There is a special pneumatic 'punch tool' (shown right) that makes the custom-shaped holes. Spigots can be supplied with the holes pre-punched for a small additional charge. Contact your local distributor for more information.

	Part No:	RRP EUC:
Smiley Face Hole Punch	10402	P.O.A.



TR Lock-Out Safety System

Our Tool Release (TR) connector range is a popular way to add a layer of safety to applications where the connector is mounted very close to equipment that is rotating or spinning very fast, such as above rotary valves or rotary knives.

	Part No:	RRPEUR:
TR Lock-Out Safety Tube	305275	14



The prices shown above indicate our Recommended Retail Prices (RRP).

Quick Access Port

The Quick Access Port is a removable screw in plug that can be added to the wall of Seeflex 040E and Seeflex 060ES connectors to aid in-line testing/sampling (includes tapered versions).

For minimum 150mm diameter and 150mm length connectors.

	RRP EUR:
Surcharge on standard Connector RRP price	240



Rings

Applicable to: Seeflex 040E (including Wash Sleeves and Blanking Socks/Bins). Seeflex 040AS, LM3, LM4, Teflex and Teflex NP.

Anti-collapse rings can be added to help keep the connector walls open. This is particularly useful if operating under vacuum or for longer connectors where there may be the potential for the connector walls to be 'sucked' inwards. Rings are available in stainless steel (to Ø500mm) or plastic (to Ø1,650mm & max operating temperature of 110°C/230°F) and can be added to connectors at least 150mm (5") long if made from the materials listed above (subject maximum applicable diameters).

To calculate the price of a ringed version of a connector, simply add the following price per ring to the RRP of the standard connector price (based on the Diameter):

DIA(mm):	Ø100	Ø125	Ø150	Ø200	Ø250	Ø300	Ø350	Ø400	Ø450	Ø500	Ø550	Ø600	Ø650	Ø700	Ø750	Ø800	Ø850	Ø900	Ø950	Ø1000
	RRP EUR:	RRP EUR:	RRP EUR:	RRP EUR:	RRP EUR:	RRP EUR:	RRP EUR:	RRP EUR:	RRP EUR:	RRP EUR:	RRP EUR:	RRP EUR:	RRP EUR:	RRP EUR:	RRP EUR:	RRP EUR:	RRP EUR:	RRP EUR:	RRP EUR:	RRP EUR:
Stainless Steel Rings	50	53	60	70	73	77	87	94	100	107	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Plastic Rings	67	73	80	87	94	100	107	111	113	113	113	113	120	160	173	186	207	220	233	254



- The distance between spigot & rings is 75mm (3") for 150mm long connectors, and 100mm (4") for all others.
- Multiple rings need to be evenly spaced at a minimum of 100mm (4") apart for connectors up to 800mm long inclusive (maximum 4 rings) and 200mm (8") apart for connectors 850mm long and over (maximum 10 rings). Maximum length restrictions apply to certain materials. Refer to our 'Quick Ref Limitations Summary' document for more information.
- The diameter of the steel ring itself is 6mm (¼"), the plastic ring itself is 8mm (5⁄16") and the 'connector' that joins the plastic ring together is approx. 10mm (¾").
- Ringed connectors have different part numbers to their standard equivalents.

The prices shown above indicate our Recommended Retail Prices (RRP).

Flexi / Flexi-Light

Lightweight connector with support coil - ideal for bag feeders & filling heads



- A lightweight Seeflex connector with an encased 316 stainless steel wire coil to support flex and compression
- Used for bag feeders, filling heads or bulk bag fillers.
- Flexi-Light features a slightly lighter material and wire coil

PHYSICAL PROPERTIES:

Material	Ether-based thermoplastic polyurethane with a 316 stainless steel wire coil	
Wall Thickness (±10%):	FLEXi	0.60mm / 1/32" (Ø100 – 200mm / 4 – 8")
		0.70mm / 1/32" (Ø250 – 300mm/10 – 12")
Wire Coil Diameter	FLEXi	0.4mm / 1/64"
	FLEXi-LIGHT	0.4mm / 1/64"
Operating Temp Range:	FLEXi	2.6mm / 3/64"
	FLEXi-LIGHT	1.6mm / 1/16"

Available Diameters:	100mm, 150mm, 200mm, 250mm, 300mm
Minimum Length:	200mm
Maximum Length:	6,000mm
Available as TR (Tool Release) option?	Yes

VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	FOOD SAFETY	ATEX

* Subject to length & movement restrictions.

FLEXI:

DIA:	Ø100mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm	
LENGTH: (mm)	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
200	25701	464	26152	480	22116	515	25910	634	21197	664
250	26905	473	26139	495	22190	538	26000	662	22938	697
300	26009	484	25871	506	21623	556	26825	685	21732	729
350	26233	493	25898	520	22136	578	26419	713	23104	757
400	25877	500	25615	533	23100	598	25789	739	21765	789
450	26156	510	25798	552	23101	618	25836	767	23099	821
500	26027	520	25899	559	23102	639	26415	791	60023	854
550	28884	532	25950	573	23103	659	25790	809	40277	887
600	25761	541	26640	587	23087	680	25791	827	22757	920
650	29278	551	28090	602	23111	702	28503	857	25207	951
700	26246	561	26252	616	24293	719	26430	887	25507	982
750	28883	569	26033	630	24645	741	26371	919	23105	1013
800	25592	580	26358	643	22392	762	25720	948	22793	1047
850	29028	591	25593	656	24660	785	26904	971	22804	1080
900	26525	596	25999	672	24818	805	25650	993	22137	1112
950	26067	605	29970	688	26681	824	25668	1019	25671	1144
1000	25927	614	25928	704	24334	844	26581	1053	26866	1176

FLEXI - LIGHT:

DIA:	Ø100mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm	
LENGTH: (mm)	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
200	28372	443	28279	461	28278	476	28869	575	29260	602
250	29479	452	28201	475	28200	495	29241	598	29736	631
300	40300	463	28262	488	28264	513	28261	622	28742	658
350	40301	475	29077	501	29194	532	29067	645	28744	688
400	29565	486	28934	515	28199	551	28877	668	28743	715
450	40302	498	28280	529	29259	569	28768	692	28500	744
500	28914	509	29157	542	29274	589	29193	715	29504	772
550	40303	516	40312	555	29569	607	40321	739	28918	800
600	28856	524	40313	568	29566	626	28494	762	29322	828
650	40304	532	40314	581	29328	645	40322	785	40258	857
700	40305	540	28281	595	40319	663	28941	809	40257	886
750	40306	547	40315	608	29060	681	40323	832	40267	914
800	40307	556	28552	622	29641	701	40324	855	40329	942
850	40308	564	40316	635	40320	719	40325	878	29607	971
900	40309	572	29547	648	40150	738	28481	901	40330	998
950	40310	580	40317	662	29966	757	40326	925	40331	1027
1000	40311	587	40318	675	29593	776	40327	948	40332	1055

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector, please refer to the 'Add-ons' pages.

Flexi-Earthed

Flexi-connector with support coil & earthing terminal lugs




- A standard Flexi connector with built-in terminal earthing lugs attached to the ends of the wire coil.
- Terminal lugs are designed to be attached to earthing cables to provide maximum electrostatic safety.

PHYSICAL PROPERTIES:

Material	Ether-based thermoplastic polyurethane with a 316 stainless steel wire coil & Ø5mm SS earthing lugs
Wall Thickness (±10%):	0.60mm / 1/32" (Ø100 – 200mm / 4 – 8") 0.70mm / 1/32" (Ø250 – 300mm/10 – 12")
Wire Coil Diameter	2.6mm / 1/64"
Operating Temp Range:	- 20 to 85°C / - 4 to 185°F

Available Diameters:	100mm, 150mm, 200mm, 250mm, 300mm
Minimum Length:	250mm
Maximum Length:	6,000mm
Available as TR (Tool Release) option?	Yes

					
VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	FOOD SAFETY	ATEX

* Subject to length and movement restrictions

FLEXI - EARTHED:

DIA:	Ø100mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm	
LENGTH: (mm)	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
250	29256	520	28795	542	28360	585	28845	708	28432	744
300	28825	531	28826	553	28314	602	28412	732	28872	776
350	40363	539	40265	567	28741	624	28448	760	28875	804
400	29083	547	28472	580	28864	645	29017	786	28519	836
450	40766	557	29023	598	28345	665	28701	813	28471	868
500	29497	567	28849	607	28529	685	28491	838	28660	900
550	40298	579	29917	620	29665	706	29942	856	28963	934
600	40360	587	29551	634	28833	727	28359	874	29321	967
650	29627	598	40770	648	29196	749	40774	904	40778	998
700	40767	608	29197	663	28848	766	28897	934	40779	1029
750	40299	615	40771	677	28766	788	40755	965	40780	1059
800	29967	626	29292	690	28185	809	29057	994	40781	1094
850	40768	637	40772	702	28501	832	40775	1018	40782	1127
900	29074	642	29075	718	28957	851	40776	1040	29390	1159
950	40769	652	29577	735	40400	871	40777	1065	40783	1191
1000	29289	661	40773	751	28765	890	28730	1099	28775	1223



The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector, please refer to the 'Add-ons' pages.

Teflex Woven

100% woven Polyester - suitable for higher temperatures



- Capable of running at high temperatures – continuously operating at 260°C / 500°F with short term surges at 280°C / 536°F.
- Can be used on products across the full pH scale, i.e. either caustic or acid products will not effect Teflex Woven.

PHYSICAL PROPERTIES:

Material	Woven PTFE	
Weight (±10%)	678g/m ² / 20oz/yd ²	
Operating Temp Range	-40 - 260°C / -40 - 500°F (surge to 280°C / 536°F)	
Air Permeability	(cm ³ /cm ² /sec@125Pa)	(ft ³ /ft ² /min@0.5" wg)
	0.3	0.5

Maximum Diameter: 1,650mm
Maximum Length (≤ Ø650mm): 1,500mm
Available with SS Rings? Yes (≤ Ø500mm)
Available with Plastic Rings?* Yes
Available as TR (Tool Release) option? Yes (≤ Ø650mm)

*to Max. Operating Temp of 110°C / 230° F

VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	FOOD SAFETY	ATEX

Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
80	30465	268	40909	289	26659	384	30443	541	25395	614	30308	689	25284	714	30488	739	31280	805	26304	892	31281	984	31282	1361	31283	1476
100	30079	268	30080	289	30081	384	21507	541	30065	614	21534	689	21470	714	30082	739	30083	805	30084	892	30085	984	21535	1361	30086	1476
150	30001	299	30056	361	21537	425	21939	544	30063	640	21928	745	21505	789	21637	920	21926	1036	30311	1154	30312	1249	21927	1467	30310	1674
200	30096	320	30638	382	30061	444	21439	547	30057	646	20558	773	21506	846	20557	985	20556	1036	30058	1154	30059	1249	21577	1467	30060	1674
250	30186	402	40235	461	21986	522	21341	654	21473	788	21475	927	21471	1044	21472	1186	21492	1321	21474	1464	24847	1606	26300	1726	27083	1867
300	30107	443	30804	510	30103	579	21343	725	30210	875	21339	1029	21957	1162	22898	1318	21166	1469	30101	1626	26051	1785	26052	1919	30160	2075
350	28881	484	40910	560	30209	635	21527	798	30211	960	30212	1130	21528	1278	24748	1451	24991	1615	21686	1789	41082	1962	40393	2112	30155	2284
400	40895	525	40911	610	30176	691	22357	869	21558	1046	30280	1231	25171	1395	24749	1583	21627	1763	30223	1952	30224	2141	41103	2305	22011	2494
450	30325	566	40912	659	26204	748	22483	942	24711	1131	30259	1332	29047	1512	21337	1714	21600	1909	29923	2114	41083	2319	28034	2498	28032	2703
500	30605	607	40913	710	30392	804	30273	1013	23150	1217	30366	1433	40976	1628	24297	1847	41013	2057	30196	2277	41084	2497	28035	2691	41119	2911

All BFM[®] fitting connectors comply with 3-A 60-64 Sanitary Fittings

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

Teflex NP Black

PTFE laminate for temperature & chemical extremes



- Non-permeable PTFE laminate that can be used on products across the full pH scale, ie. caustic or acid products will not effect Teflex NP Black
- Capable of running at high and low temperatures
- Very good at to dissipating electrical charge - 10⁶ Ω

PHYSICAL PROPERTIES:

Material	Pure PTFE
Weight (±10%)	459g/m ² / 13.5oz/yd ²
Operating Temp Range	-73 - 300°C / -99 - 572°F (surge to 316°C / 600°F)
Surface Resistivity (Ohms)	10 ⁶

Maximum Diameter:	500mm
Maximum Length:	1,000mm
Available with SS Rings?	Yes
Available with Plastic Rings?	No
Available as TR (Tool Release) option?	Yes

VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	FOOD SAFETY	ATEX

* Expect shorter life-span if used # All BFM® fitting connectors comply with 3-A 60-64 Sanitary Fittings

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm	
LENGTH: (mm)	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
80	41175	242	41176	260	29938	325	29859	432	29858	512	29631	579	41296	642	29820	665	41297	725	41313	803
100	40873	242	41060	260	29093	325	29041	432	29043	512	29042	579	29787	642	29531	665	29532	725	29816	803
150	41042	268	41061	325	29106	356	29124	446	29133	528	29087	595	29788	711	29506	828	41298	932	29844	1040
200	41043	288	41062	344	29108	372	28819	454	29135	538	28718	626	29552	761	29501	887	29510	932	40152	1040
250	41044	362	41063	415	29127	435	29071	612	29137	722	29147	816	29927	940	29489	1067	29760	1189	41314	1317
300	41045	399	41064	460	29129	483	29078	644	29144	760	29080	895	29763	1046	29845	1187	41299	1321	41295	1464
350	41046	436	41065	505	41179	571	29629	717	41253	864	29800	1017	29910	1151	41282	1306	41300	1454	29924	1610
400	41047	472	41066	549	29601	622	29757	783	29936	942	40657	1108	40764	1256	41283	1424	41301	1586	29925	1757
450	41048	509	41067	593	29602	672	29535	847	40188	1018	40658	1200	40765	1360	29511	1544	40337	1719	29926	1903
500	41049	546	41068	639	40174	724	29852	911	29630	1096	29930	1290	41271	1466	29513	1663	41302	1851	41315	2049
550	41050	582	41069	683	41180	774	41247	977	29937	1173	41261	1382	41272	1571	41284	1781	41303	1984	41316	2196
600	41051	620	41070	728	41181	824	40269	1041	40232	1250	41262	1473	41273	1675	41285	1901	41304	2115	41317	2342
650	41052	656	41071	773	41241	876	41248	1106	41254	1327	41263	1564	41274	1780	41286	2020	41305	2248	41318	2489
700	41053	693	41072	817	41242	926	41249	1170	41255	1405	41264	1654	41276	1886	41287	2138	41306	2380	41319	2635
750	41054	730	41073	862	41243	977	41250	1235	41256	1481	41265	1746	41277	1990	41288	2258	41307	2513	41320	2782
800	41055	766	41074	908	40355	1027	40872	1300	41257	1559	41266	1838	41278	2096	41289	2377	41308	2645	41321	2928
850	41056	804	41075	952	41244	1078	41251	1363	41258	1636	41267	1928	41279	2201	41290	2496	41309	2777	41322	3075
900	41057	840	41076	997	41245	1129	40663	1429	41259	1713	41268	2020	41280	2306	41291	2615	41310	2910	41323	3221
950	41058	877	41077	1041	41246	1179	41252	1493	41260	1791	41269	2111	41281	2411	41292	2734	41311	3042	41324	3368
1000	41059	914	41078	1086	29972	1230	40346	1558	40133	1868	40343	2203	41293	2516	41294	2853	41312	3175	41325	3514



The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

Teflex NP Opaque

Semi-transparent PTFE laminate for temperature & chemical extremes



- Non-permeable PTFE laminate that can be used on products across the full pH scale, ie. caustic or acid products will not effect Teflex NP Opaque
- Capable of running at high and low temperatures
- Semi-transparent to allow product-flow visibility

PHYSICAL PROPERTIES:

Material	Pure PTFE
Weight (±10%)	459g/m² / 13.5oz/yd²
Operating Temp Range	-73 - 300°C / -99 - 572°F (surge to 316°C / 600°F)
Surface Resistivity (Ohms)	Insulative

Maximum Diameter:	500mm
Maximum Length:	1,000mm
Available with SS Rings?	Yes
Available with Plastic Rings?	No
Available as TR (Tool Release) option?	Yes

VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	FOOD SAFETY	ATEX

* Expect shorter life-span if used # All BFM® fitting connectors comply with 3-A 60-64 Sanitary Fittings

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm	
LENGTH: (mm)	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
80	41177	242	41178	260	29900	325	40250	432	41356	512	40247	579	40252	642	41396	665	41412	725	40749	803
100	41137	242	41156	260	40649	325	29934	432	29687	512	40256	579	40248	642	40630	665	41413	725	40251	803
150	41138	268	41157	325	29861	356	29933	446	29943	528	40246	595	41381	711	40661	828	41414	932	41430	1040
200	41139	288	41158	344	40249	372	29905	454	40270	538	29751	626	40245	761	40852	887	29963	932	41431	1040
250	41140	362	41159	415	40639	435	29866	612	41357	722	29850	816	41009	940	41397	1067	29907	1189	40638	1317
300	41141	399	41160	460	29929	483	29847	644	29848	760	29849	895	29906	1046	29846	1187	41415	1321	41432	1464
350	41142	436	41161	505	41328	571	41343	717	41007	864	41008	1017	41382	1151	41398	1306	41416	1454	41433	1610
400	41143	472	41162	549	29904	622	40746	783	41358	942	40832	1108	41383	1256	41399	1424	41417	1586	41434	1757
450	41144	509	41163	593	41329	672	41344	847	41359	1018	41370	1200	41384	1360	41400	1544	41418	1719	41435	1903
500	41145	546	41164	639	41330	724	40874	911	41360	1096	41371	1290	41385	1466	41401	1663	41419	1851	41436	2049
550	41146	582	41165	683	41331	774	41345	977	41361	1173	41372	1382	41386	1571	41402	1781	41420	1984	41437	2196
600	41147	620	41166	728	41332	824	41346	1041	41362	1250	40888	1473	41387	1675	41403	1901	41421	2115	41438	2342
650	41148	656	41167	773	41333	876	41347	1106	41363	1327	41373	1564	41388	1780	41404	2020	41422	2248	41439	2489
700	41149	693	41168	817	41334	926	41348	1170	41364	1405	41374	1654	41389	1886	41405	2138	41423	2380	41440	2635
750	41150	730	41169	862	41335	977	41349	1235	41365	1481	41375	1746	41390	1990	41406	2258	41424	2513	41441	2782
800	41151	766	41170	908	41336	1027	40875	1300	41366	1559	41376	1838	41391	2096	41407	2377	41425	2645	41442	2928
850	41152	804	41171	952	41337	1078	41352	1363	41367	1636	41377	1928	41392	2201	41408	2496	41426	2777	41443	3075
900	41153	840	41172	997	41338	1129	41353	1429	41368	1713	41378	2020	41393	2306	41409	2615	41427	2910	41444	3221
950	41154	877	41173	1041	41339	1179	41354	1493	41369	1791	41379	2111	41394	2411	41410	2734	41428	3042	41445	3368
1000	41155	914	41174	1086	41342	1230	41355	1558	40351	1868	41380	2203	41395	2516	41411	2853	41429	3175	41446	3514

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

LM3

100% Woven polypropylene - breathable & suitable for low temperatures



- Ideal for low temperature environments (down to -70°C/-94°F)
- Perfect for food processing, especially when some breathability is required to alleviate pressure.

PHYSICAL PROPERTIES:

Material	100% woven polypropylene	
Weight (±10%)	295g/m ² / 8.7oz/yd ²	
Operating Temp. Range	-70 to 94°C / -94 to 201°F (surge to 107°C / 225°F)	
Air Permeability	(cm ³ /cm ² /sec@125Pa)	(ft ³ /ft ² /min@0.5" wg)
	13	25

Maximum Diameter:	1,650mm
Maximum Length (≤ Ø650mm):	1,500mm
Available with SS Rings?	Yes (≤ Ø500mm)
Available with Plastic Rings?	Yes
Available as TR (Tool Release) option?	Yes (≤ Ø650mm)

VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	3-A 60-64	FDA	FOOD SAFETY	ATEX

All BFM® fitting connectors comply with 3-A 60-64 Sanitary Fittings
Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
80	50671	72	51087	75	50768	79	50670	89	50709	97	50623	102	51206	116	51227	124	51248	138	51274	160	51298	172	51327	182	51355	192
100	50602	72	50522	75	50539	79	50520	89	50540	97	50541	102	50542	116	50543	124	50544	138	50603	160	50647	172	51328	182	50707	192
150	50628	74	50672	76	50521	80	50546	89	50665	97	50622	107	51207	117	50669	126	51619	139	50604	162	51299	172	50777	184	51356	195
200	50701	84	51088	87	25277	91	50519	91	50532	100	50552	113	50715	120	50553	134	50783	145	50605	166	51300	178	51329	189	51357	201
250	50710	87	51089	91	50594	95	50626	108	50627	122	50625	131	50789	146	50711	168	51249	186	50780	207	51301	251	51330	263	51358	275
300	30751	91	50751	95	26870	100	26871	113	25275	128	50644	138	50645	152	51476	175	51250	194	50613	215	51302	257	51331	271	51479	284
350	51066	95	51090	99	51139	105	50641	118	25276	133	50723	144	50747	158	51753	182	51251	201	51275	222	51303	265	51332	279	51360	292
400	51067	98	50750	103	50722	108	50759	123	50754	138	25296	150	50767	165	51228	189	51252	208	26701	231	51304	273	51333	288	51361	301
450	50525	102	50752	107	50535	113	50736	128	50746	143	26837	156	51057	172	26838	196	51253	216	51276	239	51305	280	50656	295	51362	310
500	50526	105	51091	111	50634	118	50635	132	26921	149	26923	162	51208	178	51754	204	51254	223	51277	246	51306	288	51334	303	51363	319
550	51068	108	51092	116	51140	122	51154	137	51171	153	51188	168	51209	184	51229	210	51255	230	51278	255	51307	295	51335	312	51364	328
600	51138	112	51093	119	50776	126	50774	142	50708	159	50652	174	50787	191	51230	217	51256	238	51279	263	51308	303	51336	320	51365	337
650	51069	116	51094	123	51141	131	51155	147	51172	164	51189	180	51210	197	51231	223	51257	244	51280	271	51309	310	51337	327	51366	346
700	51070	119	51095	128	51142	135	50779	152	51173	169	51190	186	51211	205	51232	231	51258	252	51281	279	51310	318	51338	336	51367	354
750	51071	123	51096	131	51143	140	51156	157	51174	174	51191	193	51212	211	50705	238	50706	259	51282	287	51311	325	51339	344	51368	363
800	51072	126	51097	135	51755	145	50775	161	50712	180	51192	198	51213	217	51233	245	51259	266	51283	295	51312	333	51340	353	51369	372
850	51073	130	51098	140	51144	149	51157	166	51175	185	51193	205	51214	223	51234	252	51260	274	51284	303	51313	340	51341	360	51370	381
900	51074	134	51099	144	51145	153	51158	171	51176	191	51194	210	51752	230	51235	258	51261	281	51285	311	51314	348	51342	368	51371	390
950	51075	137	51100	147	51146	158	51159	175	51177	196	51195	217	51215	238	51236	266	51262	288	51286	319	51315	355	51343	377	51372	399
1000	51076	140	51101	152	51487	162	51160	180	26922	201	50655	222	51216	244	51237	272	51263	295	51287	327	51316	362	51344	384	51373	408

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

LM4

100% woven Polyester - suitable for higher temperatures



- Used for higher temperature environments (up to 130°C / 266°F).
- Ideal for use where air needs to be vented through the walls of the flexible connector.

PHYSICAL PROPERTIES:

Material	100% woven polyester fibre	
Weight (±10%)	393g/m² / 11.6oz/yd²	
Operating Temp Range	-55 - 130°C / -48 - 266°F (surge to 150°C / 302°F)	
Air Permeability	(cm³/cm²/sec@125Pa)	(ft³/ft²/min@0.5" wg)
	0.4	0.8

Maximum Diameter:	1,650mm
Maximum Length (≤ Ø650mm):	1,500mm
Available with SS Rings?	Yes (≤ Ø500mm)
Available with Plastic Rings?*	Yes
Available as TR (Tool Release) option?	Yes (≤ Ø650mm)
*to Max. Operating Temp of 110°C / 230° F	

VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	3-A	FOOD SAFETY	IC19AL3004	ATEX

#All BFM® fitting connectors comply with 3-A 60-64 Sanitary Fittings

Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
80	26101	72	41664	75	50506	80	26344	89	50507	97	26239	102	29840	116	26262	124	21453	138	26305	160	41665	172	41666	182	41667	192
100	20900	72	51000	75	20901	80	20902	89	20903	97	20904	102	20905	116	20906	124	20907	138	20908	160	20909	172	20910	182	20911	192
150	20509	74	51001	76	19569	79	50009	89	50014	97	50015	107	50406	117	22089	126	50424	139	50425	162	50426	172	50427	184	50428	195
200	20912	84	51002	87	21847	91	19399	91	20510	100	20511	113	20512	120	20483	134	20513	145	20514	166	20515	178	20516	189	20517	201
250	25238	87	50140	91	21987	95	21477	108	21614	122	21812	131	22897	146	21622	168	22927	186	26531	207	40791	251	24391	263	28822	275
300	20914	91	50137	95	20915	100	20916	113	21924	128	20918	138	20919	152	20920	175	20921	194	20922	215	20923	257	20924	271	20925	284
350	25595	95	23146	99	21883	105	22367	118	50004	133	22852	144	20314	158	26532	182	50523	201	26533	222	29965	265	41226	279	41233	292
400	20926	98	28689	103	20927	108	20928	123	20929	138	20650	150	20931	165	20932	189	20933	208	20934	231	20935	273	20936	288	20937	301
450	26254	102	29187	107	22366	113	22800	128	50404	143	50405	156	50407	172	50499	196	29589	216	28349	239	50501	280	26567	295	24486	310
500	22758	105	23206	111	20939	118	22208	132	20941	149	20942	162	20943	178	24296	204	20945	223	25410	246	20947	288	20948	303	20949	319
550	26381	108	41192	116	28688	122	26243	137	41201	153	29564	168	24809	184	41207	210	41209	230	41213	255	41219	295	41227	312	41234	328
600	20956	112	28431	119	20957	126	20958	142	20959	159	20960	174	20961	191	20962	217	20963	238	20964	263	20965	303	20966	320	20967	337
650	26141	116	41193	123	26087	131	25862	147	28716	164	23017	180	41206	197	22376	223	41210	244	41214	271	41220	310	41228	327	23199	346
700	41188	119	41194	128	50013	135	22132	152	22131	169	25669	186	23228	205	41208	231	29585	252	21355	279	41221	318	41229	336	41235	354
750	26346	123	50619	131	41197	140	24951	157	23051	174	22965	193	40237	211	25642	238	24955	259	21754	287	41222	325	41230	344	41236	363
800	20968	126	25560	135	50673	145	20970	161	20971	180	21903	198	20973	217	20974	245	20975	266	41215	295	20977	333	20978	353	20979	372
850	41189	130	25561	140	41198	149	22163	166	41202	185	41204	205	24833	223	24835	252	25111	274	41216	303	41223	340	41231	360	41237	381
900	41190	134	41195	144	41199	153	22162	171	24283	191	21901	210	24834	230	22395	258	41211	281	41217	311	41224	348	22982	368	41238	390
950	41191	137	41196	147	41200	158	25966	175	41203	196	41205	217	40111	238	24836	266	41212	288	41218	319	41225	355	41232	377	41239	399
1000	20980	140	25607	152	20981	162	21878	180	20983	201	20985	222	26215	244	20986	272	20987	295	20988	327	20989	362	20990	384	20991	408

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of a connector or to add Rings, please refer to the 'Add-ons' pages.

FM1 Breather

Woven polyester breather bag for venting contained vessels



- Designed for breathing applications such as venting hoppers and other contained vessels
- The BFM® breather may become required as the BFM® connectors create a 100% sealed system.

PHYSICAL PROPERTIES:

Material	100% woven polyester needlefelt	
Weight (±10%)	550g/m² / 16.22oz/yd²	
Operating Temp Range	-20 - 130 °C / -4 - 266 °F (surge to 150 °C / 302 °F)	
Air Permeability	(cm³/cm²/sec@125Pa)	(ft³/ft²/min@0.5" wg)
	17	33

Maximum Diameter:	650mm
Maximum Length (≤ Ø650mm):	1,000mm
Available with SS Rings?	No
Available with Plastic Rings?	No
Available as TR (Tool Release) option?	Yes

VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	FOOD SAFETY	ATEX

All BFM® fitting connectors comply with 3-A 60-64 Sanitary Fittings

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
100	30544	96	30711	100	30553	102	30562	107	30546	112	30612	122	30807	126	31234	164	30608	192	30654	239	31421	293	31422	310	31424	328
150	30534	96	30668	100	30566	104	30590	107	30716	112	30635	122	30632	127	31235	166	30669	192	31254	241	31426	298	31441	314	31455	332
200	30528	96	30533	100	30569	104	30530	108	30602	113	30629	122	30630	128	30572	168	30689	193	31255	244	31427	301	31167	318	31456	337
250	30540	96	30576	100	30586	105	30601	112	30588	114	30607	122	31229	129	31236	173	31243	193	30805	246	31428	305	31442	322	31457	342
300	30517	97	30525	101	30258	107	30334	113	30545	114	30615	122	30631	131	30604	178	31244	194	30532	246	31429	310	31443	326	31458	346
350	30661	102	30625	102	30600	107	30535	113	30624	118	30637	123	31207	132	31237	180	31245	194	31256	253	31430	314	31444	331	31459	350
400	30589	104	30702	105	30542	107	30567	114	30537	119	30551	123	31022	133	31238	182	30955	195	31201	259	31431	318	31445	335	31460	355
450	30568	105	30666	112	30585	119	30656	125	30791	141	31206	147	31004	154	31239	193	30593	199	31257	266	31432	323	31446	339	31461	360
500	30515	117	30640	120	30548	124	30539	126	30513	141	30557	149	30667	158	30559	197	30598	207	30597	272	31433	327	31447	343	31462	364
550	31200	118	31214	123	30616	128	30606	136	30963	141	30937	151	31230	158	30704	206	31246	208	30623	277	31434	331	31448	348	31463	369
600	30571	119	30854	128	30583	128	30580	136	30541	142	30717	151	30985	158	31240	206	31247	208	30840	281	31435	336	30543	351	31464	373
650	30718	119	31215	128	30610	128	30662	136	30783	142	30619	152	31231	159	31241	207	31248	209	31258	285	31436	339	31449	356	31465	378
700	32190	122	31216	128	30878	128	30688	146	30660	146	30646	153	30956	160	31242	208	32110	210	30671	288	30577	344	31450	360	31466	382
750	30757	128	31217	128	30621	128	30645	146	30524	146	30676	155	31232	164	30850	208	31249	220	31259	292	30574	348	31451	365	31467	387
800	30613	128	31218	128	30614	128	30563	147	30633	147	30558	155	30971	166	30560	211	31250	230	31260	295	31437	353	30651	369	31468	391
850	31210	131	31219	147	30611	147	31222	153	31224	154	31227	168	31182	179	31183	217	31251	240	31261	299	31438	356	31452	373	31469	396
900	31211	135	31220	149	30581	166	30659	167	31225	169	32116	180	31181	191	30808	221	32109	251	31262	301	31439	361	31453	377	31470	400
950	31212	138	31221	152	31180	166	31223	168	31226	169	31228	182	31233	191	31190	227	31252	260	31263	304	31440	366	31454	381	31296	403
1000	32091	140	30674	153	30675	166	30617	168	30564	171	30626	182	30591	192	30677	232	31253	269	30650	307	30516	371	31423	385	31289	407

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a TR version of an FM1 Breather Bag, please refer to the 'Add-ons' page 6.

Blanking Cap (Seeflex 040E)

Prevents contamination/used as sight-glasses



- Used to prevent contamination during clean down or change-over.
- They protect products and prevent dust emission into the factory.
- Ideal as sight-glasses for sifters, and other equipment.

PHYSICAL PROPERTIES:

Material	Ether-based thermoplastic polyurethane alloy
Wall Thickness (±10%)	0.9mm / 1/32 inch
Operating Temp Range	-25 to 110°C / -13 to 230°F (surge to 120°C to 248°F)
Height (Length)	30mm (1 3/16")

Maximum Diameter: 1,650mm
Available as TR (Tool Release) option? Yes (≤ 650mm)

✓
VIBRATION

✓
OSCILLATION

✗
COMPRESSION

✓
DUST TIGHT

✓
3
63-20

✓
FDA

✓
100%
FOOD SAFETY

✓
ATEX

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm	
	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
	20750	83	20761	86	20751	89	20752	95	20709	104	20753	118	20754	137	20755	161	20756	173	20757	210	20758	260

DIA:	Ø600mm		Ø650mm		Ø700mm		Ø750mm		Ø800mm		Ø850mm		Ø900mm		Ø950mm		Ø1,000mm		Ø1,050mm		Ø1,100mm	
	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
	20759	281	20760	295	21865	510	22868	521	21476	525	25086	533	22359	551	60013	569	21866	688	24667	740	21867	755

DIA:	Ø1,150mm		Ø1,200mm		Ø1,250mm		Ø1,300mm		Ø1,350mm		Ø1,400mm		Ø1,450mm		Ø1,500mm		Ø1,550mm		Ø1,600mm		Ø1,650mm	
	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
	22382	807	25197	841	22345	882	29391	942	26468	985	40402	1027	24668	1068	24576	1210	40403	1259	26743	1307	28202	1362



The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a Tool Release version of a Blanking Cap, please refer to the 'Add-ons' page 6.

Blanking Bin (Seeflex 040E)

Ideal for sifter oversize collection bins



- Used for collecting overs/reject product on sifters/sieves etc.
- Can be lined with plastic bags for easy disposal of reject product.
- Allows for visibility of product full level and reject consistency.

PHYSICAL PROPERTIES:

Material	Seeflex ether-based thermoplastic polyurethane
Wall Thickness (±10%)	0.9mm / 1/32 inch
Operating Temp Range	-25 to 110 °C / -13 to 230 °F (surge to 120 °C to 248 °F)

Maximum Diameter:	1,650mm
Maximum Length:	1,000mm
Available with SS Rings:	Yes (≤ Ø500mm)
Available with Plastic Rings:	No
Available as TR (Tool Release) option?	Yes (≤ Ø650mm)

VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	FOOD SAFETY	ATEX

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
100	25117	132	29059	141	22733	155	24323	161	22732	178	24437	206	25868	218	26258	281	27033	318	26129	367	29568	405	27032	446	40397	485
150	22851	135	21852	146	25630	160	21709	169	28216	186	21589	217	26194	231	28011	294	24451	333	40474	384	40487	423	40504	464	40521	505
200	21576	138	23022	149	22744	164	24360	176	25350	196	22546	228	26193	244	26709	307	40461	348	29222	400	25870	440	40505	483	40522	524
250	24779	141	22352	153	21309	169	25379	183	24450	206	23039	239	28226	257	40444	321	40462	362	40476	415	40489	458	40506	501	40523	545
300	21967	144	22161	157	21458	173	22878	190	26319	215	25869	250	25842	270	27125	334	50510	377	26624	432	40490	475	40507	520	40524	565
350	21170	147	21804	161	24774	178	60020	197	26176	224	40434	261	25843	284	40445	348	40464	391	40477	448	40491	493	40508	538	40525	585
400	21520	150	22353	164	24638	183	21171	205	23207	233	28530	272	25241	298	29004	361	21908	405	24531	464	40492	510	40509	557	40526	606
450	22946	153	26467	169	22742	187	22231	211	26454	243	22042	282	26200	311	24464	374	28942	420	40479	480	40493	528	40510	576	40527	626
500	22716	156	22212	172	22528	193	21791	219	22885	252	25199	293	25844	324	24938	388	26334	435	28874	496	40494	545	40511	595	40528	646
550	22717	159	40423	176	24755	197	26598	226	27052	262	26950	304	40438	337	40455	401	40467	449	40480	512	40495	563	40512	614	40529	667
600	60012	162	24563	180	24306	201	22088	233	22530	271	22087	315	22487	350	24939	414	40468	464	28332	528	40496	580	40513	633	40530	686
650	26789	165	26798	184	24777	206	24456	240	40432	281	28702	326	40439	364	26337	427	40469	480	40481	544	40497	598	40514	651	40531	707
700	40415	168	26478	187	60017	211	22760	247	25210	290	28068	338	24727	377	25388	440	40470	494	40482	559	40498	615	40515	670	40532	727
750	27126	171	40427	192	25327	216	28514	255	21719	300	28151	349	40440	391	40457	453	24970	508	28072	575	40499	633	40516	689	40533	747
800	25425	173	29198	195	22759	220	22787	262	23156	309	24346	360	26540	404	25394	467	40472	523	40483	592	40500	651	40517	707	40534	767
850	25753	177	40428	199	29600	226	22756	268	29039	318	40435	371	40441	417	24776	481	40473	537	40484	608	40501	668	40518	727	40535	788
900	40417	180	40429	204	25663	229	26014	276	26013	327	25692	381	25780	431	40459	494	25186	552	40485	624	40502	686	40519	744	40536	808
950	40418	183	40430	207	29250	234	28446	283	24794	337	25727	392	40443	444	40460	507	29674	567	40486	640	40503	703	40520	763	40537	828
1000	60026	185	29038	211	60027	239	60028	290	25892	347	25057	404	40385	458	40389	520	28772	581	40391	656	40398	721	40406	783	40407	848

The prices shown above indicate our Recommended Retail Prices (RRP). To calculate the cost of a Tool Release version or to add Rings, please refer to the 'Add-ons' page 6.

Kevlar Cover

Flame resistant cover to reduce the risk of consequential fires



- Typically used in over pressure and potentially explosive applications.
- Designed to fit over existing connectors and tightened onto the BFM® spigot using butterfly clamps.

PHYSICAL PROPERTIES:

Material	Woven Kevlar (Aramid) fibre
Weight (±10%)	447g/m² / 13.2oz/yd²
Max. Operating Temp	260°C / 500°F (surge to 300°C / 572°F) (NB: Limited to max. operating temperature of connector underneath)

Maximum Diameter:	1,650mm
Maximum Length:	1,000mm
Available with SS Rings?	No
Available with Plastic Rings?	No

VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	FOOD SAFETY	ATEX

* Does not come in contact with product therefore can be used in conjunction with a 3A certified inner connector

Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
80	80273	284	80274	289	80049	293	80130	303	80137	314	80136	323	80135	326	80131	341	80327	361	80141	381	80345	400	80133	420	80134	442
100	80044	284	80123	289	80089	293	80022	303	80068	314	80030	323	80031	326	80098	341	80099	361	80041	381	80055	400	80122	420	80077	442
150	80026	292	80124	298	80025	304	80034	326	80086	338	80023	351	80011	365	80043	379	80085	404	80058	429	80162	454	80016	473	80079	498
200	80045	301	80109	308	80050	314	80002	326	80027	338	80003	351	80057	365	80029	379	80061	404	80004	429	80013	454	80028	473	80095	498
250	80145	310	80275	319	80108	325	80071	337	80090	354	80129	370	80180	386	80069	402	80174	428	80054	455	80175	482	80173	504	80176	532
300	80046	320	80246	330	80019	336	80018	349	80020	370	80021	388	80172	407	80103	425	80212	453	80116	482	80117	510	80118	534	80114	565
350	80263	328	80276	341	80210	347	80119	361	80226	386	80190	407	80177	427	80104	448	80239	478	80217	508	80346	537	80249	565	80231	599
400	80047	338	80277	351	80248	356	80084	373	80216	402	80150	425	80036	448	80017	471	80037	503	80009	534	80347	565	80359	596	80369	633
450	80264	347	80278	362	80289	367	80297	384	80148	417	80107	444	80208	470	80235	495	80328	528	80163	559	80348	593	80144	626	80214	666
500	80048	356	80279	373	80051	378	80052	397	80053	435	80311	462	80065	490	80066	518	80067	553	80243	586	80349	620	80170	657	80370	700
550	80265	366	80280	384	80186	389	80298	408	80300	450	80386	481	80230	511	80183	541	80329	578	80337	612	80350	648	80360	688	80371	733
600	80222	375	80281	395	80236	399	80229	420	80038	466	80205	499	80178	532	80070	564	80330	602	80338	638	80351	677	80361	718	80372	766
650	80266	384	80282	405	80290	410	80299	432	80302	482	80312	518	80211	553	80322	587	80331	626	80339	664	80352	704	80362	749	80223	800
700	80267	393	80283	416	80291	420	80221	444	80305	498	80313	536	80191	574	80152	610	80153	651	80340	690	80353	731	80363	780	80373	833
750	80268	403	80284	427	80292	431	80301	457	80306	515	80014	554	80097	595	80101	634	80332	676	80096	716	80354	760	80364	811	80374	867
800	80269	412	80285	438	80293	441	80181	468	80106	531	80314	573	80318	615	80323	657	80333	701	80341	741	80355	787	80365	841	80375	900
850	80270	421	80286	449	80294	452	80234	480	80307	547	80315	591	80319	636	80324	680	80334	725	80342	767	80356	815	80366	872	80376	934
900	80271	431	80287	460	80295	463	80303	492	80308	563	80316	609	80320	657	80325	703	80335	750	80343	794	80357	842	80367	902	80377	968
950	80272	439	80288	470	80296	474	80304	504	80309	579	80317	628	80321	678	80326	726	80336	774	80344	820	80358	870	80368	933	80378	1002
1000	80252	449	80032	481	80253	485	80254	515	80128	595	80255	646	80256	700	80257	749	80258	799	80259	848	80260	898	80261	965	80262	1035

The prices shown above indicate our Recommended Retail Prices (RRP).

Black-out Cover

Designed for light sensitive applications, fits over our entire connector range.



- The cover cuts out all light and is for use in light sensitive areas
- Designed to fit over existing BFM® connectors.
- Easy to install and no tools are required.

PHYSICAL PROPERTIES:

Material	Polypropylene (wire used for the holders is 6mm 304 stainless steel)
Weight (±10%)	207 g/m² / 6.1 oz/yd²
Max. Operating Temp	95°C / 203°F

Maximum Diameter:	1,650mm
Maximum Length:	1,000mm
Available with SS Rings?	No
Available with Plastic Rings?	No

VIBRATION	OSCILLATION	COMPRESSION	DUST TIGHT	FOOD SAFETY	ATEX

* Does not come in contact with product therefore can be used in conjunction with a 3A certified inner connector

Additional sizes are available up to 1,650mm diameter.

DIA:	Ø100mm		Ø125mm		Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm		Ø500mm		Ø550mm		Ø600mm		Ø650mm	
LENGTH: (mm)	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
80	60057	257	60214	262	60188	266	60184	275	60032	285	60034	293	60037	296	60311	310	60325	327	60189	345	60352	363	60078	381	60381	401
100	60108	257	60234	262	60245	266	60058	275	60033	285	60035	293	60038	296	60039	310	60061	327	60044	345	60074	363	60076	381	60060	401
150	60097	265	60235	270	60046	276	60056	295	60066	306	60036	319	60086	331	60040	344	60201	366	60065	389	60055	412	60219	428	60215	452
200	60220	273	60236	279	60182	285	60030	295	60031	306	60042	319	60048	331	60049	344	60102	366	60045	389	60202	412	60043	428	60187	452
250	60221	281	60237	289	60104	295	60105	306	60073	321	60068	336	60081	350	60064	365	60218	389	60067	414	60353	437	60367	457	60382	482
300	60080	290	60238	299	60178	304	60216	316	60089	336	60287	353	60213	369	60312	386	60099	411	60339	437	60354	462	60368	485	60383	513
350	60222	298	60239	310	60179	314	60262	327	60274	350	60209	369	60300	388	60106	407	60103	434	60340	461	60355	487	60075	512	60384	543
400	60223	306	60240	319	60180	323	60053	338	60275	365	60288	386	60072	407	60088	427	60326	455	60341	485	60356	512	60369	541	60385	574
450	60224	315	60241	328	60253	333	60263	349	60276	379	60289	403	60217	426	60313	449	60327	478	60342	508	60357	538	60370	568	60386	604
500	60183	323	60242	338	60490	343	60264	360	60098	393	60290	419	60181	445	60314	470	60328	500	60343	532	60191	563	60371	596	60493	634
550	60054	332	60243	348	60491	353	60265	371	60277	408	60291	436	60301	463	60315	490	60329	523	60344	556	60358	589	60372	624	60387	665
600	60225	340	60244	358	60254	362	60266	381	60278	423	60292	452	60302	483	60316	512	60330	545	60194	579	60192	613	60205	652	60193	695
650	60226	348	60245	367	60255	372	60267	392	60279	437	60293	470	60303	501	60317	532	60331	568	60345	603	60359	639	60373	679	60388	725
700	60227	356	60246	378	60256	381	60063	403	60280	452	60294	486	60304	520	60318	554	60332	590	60346	626	60360	663	60374	707	60389	756
750	60228	365	60247	388	60257	391	60268	414	60281	467	60295	503	60305	539	60319	574	60333	613	60203	651	60361	689	60375	735	60204	787
800	60229	373	60248	397	60258	401	60269	424	60282	482	60296	520	60306	558	60320	596	60334	634	60347	674	60362	714	60376	763	60391	817
850	60230	382	60249	407	60259	411	60270	435	60283	496	60297	536	60307	578	60321	617	60335	657	60348	698	60363	739	60377	790	60392	847
900	60231	391	60250	416	60260	420	60271	446	60284	510	60210	553	60308	596	60322	637	60336	679	60349	721	60364	764	60378	819	60393	877
950	60232	399	60251	426	60185	429	60272	457	60285	525	60298	569	60309	615	60323	658	60337	702	60350	745	60365	789	60379	846	60394	908
1000	60233	407	60252	436	60261	439	60273	467	60286	540	60299	586	60310	634	60324	679	60338	725	60351	771	60366	815	60380	875	60395	938

The prices shown above indicate our Recommended Retail Prices (RRP).

Bulk Bag Loader

A three-layered, inflatable filling head featuring a stainless steel core fully encased in Seeflex ether-based urethane.



- Includes external air fitting that plugs into an 8mm pneumatic air line to inflate super strong & flexible outer layer.
- Top of loader simply snaps into a BFM® fitting spigot and features a fully encapsulated stainless steel ring to support lower end.
- All Bulk Bag Loaders are a standard length of 330mm.
- Built-in pressure relief valve to prevent over-inflation

PHYSICAL PROPERTIES:

Material	Seeflex -Ether-based thermoplastic polyurethane with stainless steel core
Wall Thickness (±10%)	0.9mm / 1/32 inch (Seeflex Section)
Operating Temp Range	-25 to 110°C / -13 to 230°F (surge to 120°C to 248°F)
Surface Resistivity(Ohms)	10 ¹⁰

Maximum Diameter: 450mm
Available with SS Rings? No
Available with Plastic Rings? No

DUST TIGHT

FOOD SAFETY

FOOD SAFETY

ATEX

#All BFM® fitting connectors comply with 3-A 60-64 Sanitary Fittings
* Material only

DIA:	Ø150mm		Ø200mm		Ø250mm		Ø300mm		Ø350mm		Ø400mm		Ø450mm	
LENGTH: (mm)	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
330mm*	305078	867	305075	900	304794	934	304793	967	304791	1001	302363	1034	304828	1101



The prices shown above indicate our Recommended Retail Prices (RRP).

Weighing Bellows



- Made from strong, durable, transparent Seeflex 040E urethane alloy (3A & EU Compliant)
- Patented design provides minimal resistance to absorb vibrations/movement without affecting weighing equipment below
- Asymmetrical conical shape eliminates the possibility of product build-up inside connector, affecting weighing
- BFM® snap-fit blue-band cuff and spigot system means fast, easy installation, cleaning and replacement

DIA:	Ø100mm		Ø150mm		Ø200mm	
LENGTH: (mm)	Part No:	RRP EUR:	Part No:	RRP EUR:	Part No:	RRP EUR:
80	305216	212	305218	273	305219	334

The prices shown above indicate our Recommended Retail Prices (RRP).

The following products are also available, but due to the variables involved, are quoted on request:

Venting Surge Hopper



- Tapered and angled connector with built-in partition
- Ideal for use as an intermediary hopper above a rotary valve to prevent bridging of product and encourage flow
- Partition allows powder to flow in on one side of the partition and displaced air to flow up and out the other
- Gives visibility of product flow without having to open an inspection hatch
- Easy to remove for cleaning in between product runs

Tapers



- Used as intermediary hoppers to give visibility and control over product flow/feed into process.
- Can be used to transition a larger pipe into a smaller diameter pipe to reduce flow rate or control flow rate properties or simply where two identical diameter inlet/outlets aren't possible.
- Used to reduce product contact with the walls of connector when smaller diameter is positioned at the top and larger diameter at the bottom (ideal for abrasive products/high velocity flow).

Corner Connector



Corner Connector 040E

- CIP (clean-in-place) wash processes to replace traditional steel tun-dish and swiveling pipework.
- Designed for applications where product/material needs to be transported around a bend.
- Custom diameter and length combinations available (Subject to limitations)



Corner Connector 060ES

- CIP (Clean-In-Place) wash processes to replace traditional steel tun-dish and swiveling pipework.
- Made from pressure-resistant Seeflex 060ES so ideal for high head-pressure CIP applications.
- Custom diameter and length combinations available (Subject to limitations)